INGECON



# **Solar Energy Solutions**Product Catalogue

Ingeteam



# **INDEX**

#### 6 **PRODUCT RANGE**

ALL OUR PRODUCTS ARE CERTIFIED ACCORDING TO INTERNATIONAL STANDARDS

9	SOLAR INVERTERS
99	BATTERY INVERTERS
135	MICRO-WIND INVERTERS
143	ENERGY MANAGEMENT SOLUTIONS
151	DIESEL-PV SOLUTIONS
159	ACCESSORIES

- 173 INGECON® SUN TRAINING
  - THE BEST TRAINING PLATFORM FOR PROFESSIONALS
- 177 **SERVICE AND MAINTENANCE**
- 183 **REFERENCES**

# MORE THAN 37 GW SUPPLIED TO THE RENEWABLE ENERGY MARKET WORLDWIDE

USA MEXICO PANAMA

Energy

Industry

Marine

Traction

Basic Technologies

Services










CHILE





Ingeteam is a global corporation specialized in 6 different sectors (Energy, Industry, Marine, Traction, Basic Technologies and Services), all customer oriented and based on power and control electronics, electrical machines and application engineering.

With more than 60 years experience in the electricity sector, more than 3000 professionals dedicated to engineering and project development, and more than 37 GW supplied to the renewable energy market worldwide, Ingeteam is

committed to investing in technology and innovation as the drivers of future growth.

Since 1990, the Energy business unit of Ingeteam Power Technology, S.A. has been dedicated to supplying equipment for the renewable energies sector (wind power, photovoltaic, solar thermal, hydropower, biomass and biofuels).

# WE DESIGN AND MANUFACTURE A WIDE RANGE OF INVERTERS

MORE THAN 4 GW SUPPLIED TO THE SOLAR PV MARKET WORLDWIDE













Ingeteam is a leading company in the PV sector worldwide. The electronics and software have been especially developed for the INGECON® inverters, resulting in a high-quality end product, adaptable to the specific characteristics of each plant.

With an annual 3 GW production capacity, Ingeteam offers the following product range:

- Grid-connected inverters from 2.5 to 3500 kVA.
- Battery inverters from 3 to 1070 kVA.

- Energy management solutions.
- String currents monitoring equipment.
- Communications, software and hardware.

All these products are customized to suit the requirements of each and every customer, in line with one of Ingeteam's core values: Customer guidance, service and adaptability.

# **PRODUCT RANGE**

# ALL OUR PRODUCTS ARE CERTIFIED ACCORDING TO INTERNATIONAL STANDARDS

Solar inverters



SUN 1Play **2.5 - 6 kW** 

p. 10



SUN Lite 2.5 - 10 kW

p. 26



SUN 3Play 10 - 33 kW

p. 30



SUN Power **50 - 250 kW** 

p. 42

**Battery inverters** 



SUN STORAGE 1Play 3 - 6 kW

p. 102



SUN STORAGE Power 60 - 250 kW

p. 110



SUN STORAGE PowerMax

500 - 1164 kW

p. 114



SUN STORAGE Box

p. 132

Diesel-PV Solutions



Diesel-PV Solutions

p. 152

Accessories

SUN ComBox

p. 160



SUN WeatherBox

p. 161



SUN Communication

p. 162



SUN Manager

p. 164





SUN PowerMax 300 - 1164 kVA

p. 52



SUN PowerStation SHELTER 300 - 2330 kVA

p. 86



SUN PowerStation CONTAINER 300 - 3500 kVA

p. 90

Micro-wind inverters



μWIND 2.5 - 6 kW

p. 136



μWIND Interface 2.5 - 18 kW

p. 140



EMS Manager

p. 146



**EMS** Plant Controller

p. 148





iSun Monitor









p. 166



**EMS** Tools

p. 167



SUN Remote operation and SCADA


p. 168




SUN String Control

p. 169

p. 165





INGECON SUN

SOLAR INVERTERS

#### INGECON SUN 1Play

TL M



# 2.5TL M / 2.7TL M / 3TL M / 3.3TL M / 3.68TL M / 4.6TL M / 5TL M / 5.5TL M / 6TL M

Single-phase TL inverter with a double MPPT system

The INGECON® SUN 1Play TL M inverters have been designed to maximize the power generation and also to facilitate user access to the PV plant. This solar inverter family is valid for low kilowatt residential applications, and also for decentralized commercial and industrial systems rated up to several hundred kilowatts. In domestic installations, these inverters present the great advantage of being compatible with 30 mA RCDs, the most commonly used to protect the people against electric discharges.

#### High efficiency system

Ingeteam has developed its own technology to maximize the efficiency rates of the INGECON® SUN 1Play TL M inverter family. Thanks to this *High efficiency system* and to the use of innovative electronic conversion topologies, values of up to 98% can be achieved. Furthermore, an advanced double-MPPT algorithm makes it possible to harness the maximum energy from the PV array at all times, even in difficult situations, such as scattered clouds and partial shadings.

#### Easy to install

The INGECON® SUN 1Play TL M inverters feature fast-on connectors on the DC side (type 4) and the AC side for a fast and easy connection to the system. Every country-specific configuration and language can be easily selected from the inverter screen. Moreover, the INGECON® SUN 1Play TL M inverters are compatible with all the PV module technologies on the market.

#### Simple operation and maintenance

Ingeteam is at the forefront of innovative firmware. As a result, the INGECON® SUN 1Play TL M inverters are extremely easy to operate. The menu displayed on the LCD screen has been designed so that it is simple and easy to use. These inverters feature an internal datalogger for several months data storage, accessible from a PC.

Every inverter can be accessed from either a remote PC or onsite from the inverter front touch key-pad through its LCD screen. The display also features a number of LEDs to indicate the inverter operating status.

These LED indicators light up whenever any incident is detected, thereby simplifying and facilitating equipment maintenance tasks.

#### Firmware updating

The INGECON®SUN 1Play TL Minverters allow the user to perform the firmware (FW) updating himself. It is as easy as to download the latest version of the firmware from the Ingeteam website: www.ingeteam.com, and update it using a simple SD memory card.

#### Monitoring and communication

The internal operating variables and the internal datalogger can be monitored through a number of media such as USB communications, supplied as standard. Also, RS-485, Ethernet, Wi-Fi, Bluetooth and GSM / GPRS communications are available upon demand.

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its Smartphone version iSun Monitor -available on the App Store- for monitoring and recording the inverter data over the Internet.

#### Able to withstand extreme conditions

The INGECON® SUN 1Play TL M inverter housing is suitable for outdoor use (IP65 protection rating). Likewise, it can be used under extreme atmospheric conditions with temperature ranges from -25 °C to +65 °C, although its main cooling system is air convection.

#### SiC technology

This solar inverter presents silicon carbide (SiC) components. SiC technology allows higher efficiency levels and also a more reliable, light and compact equipment.

#### Service life of more than 20 years

Ingeteam takes every care in the selection and sizing of the electronic components used for its inverters. The 1Play inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to.

# Standard 5 year warranty, extendable for up to 25 years.

#### OPTIONAL ACCESSORIES

- Inverter communication via RS-485, Ethernet, Bluetooth, Wi-Fi or GSM / GPRS.
- DC switch.
- INGECON® SUN WeatherBox for meteorological values measurement and registration.
- Digital inputs.
- Self-consumption kit.


#### PROTECTIONS

- Reverse polarity.
- Input and output overvoltages with type 3 surge arresters.
- Output shortcircuits and overloads.
- Anti-islanding with automatic disconnection.
- Insulation failures.

#### MAIN FEATURES

- Compatible with 30 mA RCDs.
- Double-MPPT system.
- Available from 2.5 up to 6 kW.
- 98% maximum efficiency.
- SiC Technology inside.
- Inverter updating by the user through a SD memory card.
- USB communications supplied as standard.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD Display.
- Easy maintenance.
- Suitable for indoor and outdoor installations (IP65).
- Display-configurable potential free contact, to indicate insulation fault or grid connection.
- Compact design.
- Language, Country Code and rated voltage configurable by display.






	2.5TL M	2.7TL M	3TL M	3.3TL M	3.68TL M
Input (DC)					
Recommended PV array power range(1)	2.8 - 3.3 kWp	3 - 3.6 kWp	3.2 - 4 kWp	3.8 - 4.4 kWp	3.9 - 4.8 kWp
Voltage range MPP1 <sup>(2)</sup>	125 - 750 V	125 - 750 V	125 - 750 V	125 - 750 V	125 - 750 V
Voltage range MPP2(2) (3)	90 - 750 V	90 - 750 V	90 - 750 V	90 - 750 V	90 - 750 V
Min. voltage for Pnom with parallel inputs	125 V	127 V	141 V	155 V	172 V
Maximum voltage <sup>(4)</sup>	850 V	850 V	850 V	850 V	850 V
Maximum current (Input 1 / Input 2)	11 / 11 A	11 / 11 A	11 / 11 A	11 / 11 A	11 / 11 A
Inputs (Input 1 / Input 2) <sup>(5)</sup>	1/1	1/1	1/1	1/1	1/1
MPPT	2	2	2	2	2
Output (AC)					
Rated power	2.5 kW	2.7 kW	3 kW	3.3 kW	3.68 kW
Max. temperature at rated power <sup>(6)</sup>	60 °C	57 °C	55 °C	52 °C	50 °C
Maximum current	16 A	16 A	16 A	16 A	16 A
Rated voltage	230 V	230 V	230 V	230 V	230 V
Voltage range	122 - 265 V	122 - 265 V	122 - 265 V	122 - 265 V	122 - 265 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=2.5 kVA	Yes. Smax=2.7 kVA	Yes. Smax=3 kVA	Yes. Smax=3.3 kVA	Yes. Smax=3.68 kV
THD	<3%	<3%	<3%	<3%	<3%
Efficiency					
Maximum efficiency	97.6%	97.6%	97.7%	97.7%	97.8%
Euroefficiency	97.3%	97.3%	97.4%	97.4%	97.5%
General Information					
Refrigeration system			Air convection		
Stand-by consumption <sup>(7)</sup>	<10 W	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W	0 W
Ambient temperature	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	IP65	IP65	IP65	IP65	IP65
Marking			CE		
EMC & Security standards	EN 61000-6-1, EN 61		61000-6-4, EN 61000-3-11, I EN 50178, FCC Part 15, AS31	EN 61000-3-12, EN 62109-1, 00	EN 62109-2, IEC62103,
Grid connection standards	IEC 61727, UNE 2	06007-1, ABNT NBR 16149, AE	BNT NBR 16150, South African	G59/2, G83/2 <sup>(8)</sup> , P.O.12.3, AS47 Grid code, Chilean Grid Code, F rements, DEWA (Dubai) Grid Cod	Romanian Grid Code,

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> The output power will be conditioned by the voltage and current configuration selected at each input <sup>(3)</sup> To drop to 90 V, the other input must be at least at 125 V <sup>(4)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(5)</sup> Optionally, the DC inputs could be duplicated <sup>(6)</sup> For each <sup>9</sup>C of increase, the output power will be reduced at the rate of 1.8% <sup>(7)</sup> Consumption from PV field <sup>(8)</sup> Related only inverters up to 16 A.



Size and weight (mm)




2.5TL M / 2.7TL M / 3TL M / 3.3TL M / 3.68TL M  $20\ \mbox{kg}.$ 

	4.6TL M	5TL M	5.5TL M	6TL M		
Input (DC)						
Recommended PV array power range <sup>(1)</sup>	5.2 - 6 kWp	5.7 - 6.5 kWp	6 - 6.8 kWp	6.3 - 7 kWp		
Voltage range MPP1 <sup>(2)</sup>	125 - 750 V	125 - 750 V	125 - 750 V	125 - 750 V		
Voltage range MPP2 <sup>(2) (3)</sup>	90 - 750 V	90 - 750 V	90 - 750 V	90 - 750 V		
Min. voltage for Pnom with parallel inputs	216 V	234 V	258 V	281 V		
Maximum voltage <sup>(4)</sup>	850 V	850 V	850 V	850 V		
Maximum current (Input 1 / Input 2)	11 / 11 A	11 / 11 A	11 / 11 A	11 / 11 A		
Inputs (Input 1 / Input 2) <sup>(5)</sup>	1/1	1/1	1/1	1/1		
MPPT	2	2	2	2		
Output (AC)						
Rated power	4.6 kW	5 kW	5.5 kW	6 kW		
Max. temperature at rated power <sup>(6)</sup>	58 °C	55 °C	50 °C	45 °C		
Maximum current	26.2 A	26.2 A	26.2 A	26.2 A		
Rated voltage	230 V	230 V	230 V	230 V		
Voltage range	122 - 265 V	122 - 265 V	122 - 265 V	122 - 265 V		
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz		
Phi Cosine	1	1	1	1		
Phi Cosine adjustable	Yes. Smax=4.6 kVA	Yes. Smax=5 kVA	Yes. Smax=5.5 kVA	Yes. Smax=6 kVA		
THD	<3%	<3%	<3%	<3%		
Efficiency						
Maximum efficiency	97.9%	98%	98%	98%		
Euroefficiency	97.5%	97.6%	97.6%	97.6%		
General Information						
Refrigeration system		Air co	pnvection			
Stand-by consumption <sup>(7)</sup>	<10 W	<10 W	<10 W	<10 W		
Consumption at night	0 W	0 W	0 W	0 W		
Ambient temperature	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C		
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%		
Protection class	IP65	IP65	IP65	IP65		
Marking			CE			
EMC & Security standards	EN 61000-6-1, EN 61000-6-2,		N 61000-3-11, EN 61000-3-12, EN 621 C Part 15, AS3100	109-1, EN 62109-2, IEC62103,		
Grid connection standards	RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2 <sup>(8)</sup> , P.O.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code					

**Notes:**  $^{(1)}$  Depending on the type of installation and geographical location  $^{(2)}$  The output power will be conditioned by the voltage and current configuration selected at each input  $^{(3)}$  To drop to 90 V, the other input must be at least at 125 V  $^{(4)}$  Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures  $^{(5)}$  Optionally, the DC inputs could be duplicated  $^{(6)}$  For each  $^{(2)}$  C on fincrease, the output power will be reduced at the rate of 1.8%  $^{(7)}$  Consumption from PV field  $^{(8)}$  Related only inverters up to 16 A.



Size and weight (mm)



**4.6TL M / 5TL M / 5.5TL M / 6TL M** 21 kg.

#### INGECON SUN 1Play

HF



#### 2.5HF / 2.7HF / 3HF / 3.3HF / 3.68HF / 4.6HF / 5HF / 5.5HF / 6HF

Single-phase string inverter with a high-frequency transformer

The INGECON® SUN 1Play HF inverters have been designed to achieve maximum energy performance and also to facilitate user access to the PV plant. This solar inverter family is valid for low kilowatt residential applications, and also for decentralized commercial and industrial systems rated up to several hundred kilowatts. In domestic installations, these inverters present the great advantage of being compatible with 30 mA RCDs, the most commonly used to protect the people against fatal electric discharges.

#### High-frequency technology

A high-frequency transformer provides galvanic isolation between the input and

output sides. This kind of transformer also reduces the weight of the inverter and increases the efficiency in relation to low frequency inverters with conventional galvanic isolation (50 / 60 Hz).

The INGECON® SUN 1Play HF inverters are compatible with all the PV module technologies on the market, whilst allowing the PV generator to be grounded whenever required.

#### Easy to install

The INGECON® SUN 1Play HF inverters feature fast-on connectors on the DC side (type 4) and the AC side for a fast and easy connection to the system. The grounding of the PV generator is also

facilitated through built-in fuse holders. Every country-specific configuration and language can be easily selected from the inverter screen.

#### Maximum efficiency values

These inverters feature an innovative electronic conversion topology which, together with an advanced maximum power point tracking system (MPPT), leads of maximum efficiency rates of up to 96%, positioning them as market leaders.

#### Simple operation and maintenance

Ingeteam is at the forefront of innovative firmware. As a result, the INGECON® SUN 1Play HF inverters are extremely easy to operate.

The menu displayed on the LCD screen has been designed so that it is simple and easy to use.

These inverters feature an internal datalogger for several months data storage, accessible from a PC. Every inverter can be accessed from either a remote PC or on-site from the inverter front touch keypad through its LCD screen.

The display also features a number of LEDs to indicate the inverter operating status. These LED indicators light up whenever any incident is detected, thereby simplifying and facilitating equipment maintenance tasks.

#### Firmware updating

The INGECON® SUN 1Play HF inverters allow the user to perform the firmware updating himself. It is as easy as to download the latest version of the firmware from the Ingeteam website: **www.ingeteam.com**, and update it using a simple SD memory card.

#### Monitoring and communication

The internal operating variables and the internal datalogger can be monitored through a number of media such as USB communications, supplied as standard. Also, RS-485, Ethernet, Wi-Fi, Bluetooth and GSM / GPRS communications are available upon demand.

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its Smartphone version iSun Monitor -available on the App Store- for monitoring and recording the inverter data over the Internet.

#### Able to withstand extreme conditions

The INGECON® SUN 1Play HF inverter housing is suitable for outdoor use (IP65 protection rating). Likewise, its innovative ventilation system allows it to be used in extreme atmospheric conditions with temperature ranges from -25 °C to +65 °C.

#### Compact design

This solar inverter presents a compact design. Older equipment used to have an external transformer that was coupled to the inverter's main body, but this new single-phase transformer inverter features an integrated topology that combines the transformer and the converter inside the same casing.

#### Service life of more than 20 years

Ingeteam takes every care in the selection and sizing of the electronic components used for its inverters. The 1Play inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to.

# Standard 5 year warranty, extendable for up to 25 years.

#### OPTIONAL ACCESSORIES

- Inverter communication via RS-485, Ethernet, Bluetooth, Wi-Fi or GSM / GPRS.
- DC switch
- INGECON® SUN WeatherBox for meteorological values measurement and registration.
- Digital inputs.
- Self-consumption kit.

#### PROTECTIONS

- Galvanic isolation between the DC and AC sides.
- Reverse polarity.
- Input and output overvoltages with type 3 surge arresters.
- Output shortcircuits and overloads.
- Anti-islanding with automatic disconnection.
- Insulation failures.
- Grounding kit if required for the PV modules.

#### MAIN FEATURES

- Compatible with grounded installations.
- High-frequency technology.
- Compatible with 30 mA RCDs.
- Available from 2.5 up to 6 kW.
- 96% maximum efficiency.
- Higher efficiency rates.
- Inverter updating by the user through a SD memory card.
- USB communications supplied as standard.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD Display.
- Easy maintenance.
- Suitable for indoor and outdoor installations (IP65).
- Display-configurable potential free contact, to indicate insulation fault or grid connection.
- Compact design.
- Language, Country Code and rated voltage configurable by display.


# PV input Optional Optional N AC output for grid connection

	2.5HF	2.7HF	3HF	3.3HF	3.68HF
Input (DC)					
Recommended PV array power range(1)	2.8 - 3.3 kWp	3 - 3.6 kWp	3.2 - 4 kWp	3.8 - 4.3 kWp	3.9 - 4.8 kWp
Voltage range MPP	125 - 500 V	125 - 500 V	125 - 500 V	125 - 500 V	125 - 500 V
Min. voltage for rated power	147 V	159 V	142 V	150 V	167 V
Maximum voltage <sup>(2)</sup>	550 V	550 V	550 V	550 V	550 V
Maximum current	17 A	17 A	22 A	22 A	22 A
Inputs <sup>(3)</sup>	2	2	2	3	3
MPPT	1	1	1	1	1
Output (AC)					
Rated power	2.5 kW	2.7 kW	3 kW	3.3 kW	3.68 kW
Max. temperature at rated power <sup>(4)</sup>	51 °C	48 °C	55 °C	52 °C	45 °C
Maximum current	13.5 A	13.5 A	16 A	16 A	16 A
Rated voltage	230 V	230 V	230 V	230 V	230 V
Voltage range	122 - 285 V	122 - 285 V	122 - 285 V	122 - 285 V	122 - 285 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=2.5 kVA	Yes. Smax=2.7 kVA	Yes. Smax=3 kVA	Yes. Smax=3.3 kVA	Yes. Smax=3.68 kVA
THD	<3%	<3%	<3%	<3%	<3%
Efficiency					
Maximum efficiency	95.6%	95.6%	95.8%	95.8%	95.8%
Euroefficiency	95%	95.1%	95.2%	95.2%	95.1%
General Information					
Refrigeration system	Air cor	nvection		Forced ventilation	
Air flow			45 m³/h	45 m³/h	45 m³/h
Stand-by consumption <sup>(5)</sup>	<10 W	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W	0 W
Ambient temperature	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	IP65	IP65	IP65	IP65	IP65
Marking			CE		
EMC & Security standards	EN 61000-6-1, EN 6	1000-6-2, EN 61000-6-3, EN	61000-6-4, EN 61000-3-2, EN 50178, FCC Part 15, AS 3:		EN 62109-2, IEC62103,
Grid connection standards	IEC 61727, UNE 2	E V 0126-1-1, EN 50438, CEI 0- 06007-1, ABNT NBR 16149, AB ode, Peruvian Grid code, IEEE 9	21, VDE-AR-N 4105:2011-08, ( BNT NBR 16150, South African	G59/2, G83/2 <sup>(6)</sup> , P.O.12.3, AS47 Grid code, Chilean Grid Code, F	Romanian Grid Code,

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> Optionally, the DC inputs could be duplicated <sup>(4)</sup> For each °C of increase, the output power will be reduced at the rate of 1.8% <sup>(5)</sup> Consumption from PV field <sup>(6)</sup> Related only inverters up to 16 A.




#### Size and weight (mm)




**2.5HF / 2.7HF** 20 kg. **3HF / 3.3HF / 3.68HF** 22 kg.

	4.6HF	5HF	5.5HF	6HF	
Input (DC)					
Recommended PV array power range <sup>(1)</sup>	5.2 - 6 kWp	5.7 - 6.5 kWp	6 - 6.8 kWp	6.3 - 7 kWp	
Voltage range MPP	125 - 500 V	125 - 500 V	125 - 500 V	125 - 500 V	
Min. voltage for rated power	146 V	158 V	174 V	190 V	
Maximum voltage(2)	550 V	550 V	550 V	550 V	
Maximum current	33 A	33 A	33 A	33 A	
Inputs <sup>(3)</sup>	3	3	3	3	
MPPT	1	1	1	1	
Output (AC)					
Rated power	4.6 kW	5 kW	5.5 kW	6 kW	
Max. temperature at rated power <sup>(4)</sup>	58 °C	55 ℃	50 °C	45 °C	
Maximum current	26.2 A	26.2 A	26.2 A	26.2 A	
Rated voltage	230 V	230 V	230 V	230 V	
Voltage range	122 - 285 V	122 - 285 V	122 - 285 V	122 - 285 V	
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	
Phi Cosine	1	1	1	1	
Phi Cosine adjustable	Yes. Smax=4.6 kVA	Yes. Smax=5 kVA	Yes. Smax=5.5 kVA	Yes. Smax=6 kVA	
THD	<3%	<3%	<3%	<3%	
Efficiency					
Maximum efficiency	96%	96%	96%	96%	
Euroefficiency	95.2%	95.2%	95.3%	95.3%	
General Information					
Refrigeration system		Forced v	ventilation		
Air flow	90 m³/h	90 m³/h	90 m³/h	90 m³/h	
Stand-by consumption <sup>(5)</sup>	<10 W	<10 W	<10 W	<10 W	
Consumption at night	0 W	0 W	0 W	0 W	
Ambient temperature	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	-25 °C to +65 °C	
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	
Protection class	IP65	IP65	IP65	IP65	
Marking		(	CE		
EMC & Security standards	EN 61000-6-1, EN 61000-6-2		61000-3-11, EN 61000-3-12, EN 621 Part 15, AS 3100	.09-1, EN 62109-2, IEC62103,	
Grid connection standards	RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2 <sup>(6)</sup> , P.O.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code				

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> Optionally, the DC inputs could be duplicated <sup>(4)</sup> For each °C of increase, the output power will be reduced at the rate of 1.8% <sup>(5)</sup> Consumption from PV field <sup>(6)</sup> Related only inverters up to 16 A.



Size and weight (mm)



**4.6HF / 5HF / 5.5HF / 6HF** 25 kg.

#### INGECON SUN 1Play

TL U M



#### 2.8TL U M / 3.3TL U M / 5TL U M / 6TL U M

Single-phase TL inverter with a double MPPT system

The INGECON® SUN 1Play TL U M inverters have been designed to maximize the power generation and also to facilitate user access to the PV plant. This solar inverter family is valid for low kilowatt residential applications, and also for decentralized commercial and utility-scale systems rated up to several hundred kilowatts. In domestic installations, these inverters present the great advantage of integrating an arc fault circuit interruption system (AFCI). Moreover, they are compatible with 30 mA RCDs, the most commonly used to protect the people against fatal electric discharges.

#### High efficiency system

Ingeteam has developed its own technology to maximize the efficiency rates of the INGECON® SUN 1Play TL U M inverter family. Thanks to this high efficiency system and to the use of inno-

vative electronic conversion topologies, values of up to 98.4% can be achieved. Furthermore, an advanced double-MPPT algorithm makes it possible to harness the maximum energy from the PV array at all times, even in difficult situations, such as scattered clouds and partial shadings.

#### Easy to install

Every country-specific configuration and language can be easily selected from the inverter screen. Moreover, the INGECON® SUN 1Play TL U M inverters are compatible with all the PV module technologies on the market.

#### Simple operation and maintenance

Ingeteam is at the forefront of innovative firmware. As a result, the INGECON® SUN 1Play TL U M inverters are extremely easy to operate. The menu displayed on the LCD screen has been designed so that it is simple and easy to use.

These inverters feature an internal datalogger for several months data storage, accessible from a PC. Every inverter can be accessed from either a remote PC or on-site from the inverter front touch keypad through its LCD screen. The display also features a number of LEDs to indicate the inverter operating status. These LED indicators light up whenever any incident is detected, thereby simplifying and facilitating equipment maintenance tasks.

#### Firmware updating

The INGECON® SUN 1Play TL U M inverters allow the user to perform the firmware (FW) updating himself. It is as easy as to download the latest version of the firmware from the Ingeteam website: www.ingeteam.com, and update it using a simple SD memory card. These photovoltaic inverters feature a SD input slit to facilitate the firmware updating by the user.



## INGECON SUN 1Play

#### TL U M

#### Monitoring and communication

The internal operating variables and the historical production data can be monitored through a number of media such as USB communications, supplied as standard. Also, RS-485, Ethernet, Bluetooth and GSM / GPRS communications are available upon demand. Included at no extra cost are the INGECON® SUN Manager, INGECON® SUN Monitor and its Smartphone version iSun Monitor -available on the App Store- for monitoring and recording the inverter data over the Internet.

#### Able to withstand extreme conditions

The INGECON® SUN 1Play TLU M inverter housing is suitable for outdoor use (NEMA 3R protection rating). Likewise, it can be used under extreme atmospheric conditions with temperature ranges from -13 °F to +149 °F, although its main cooling system is natural air convection.

#### SiC technology

This solar inverter presents silicon carbide (SiC) components. SiC technology allows higher efficiency levels and also a more reliable, light and compact equipment.

#### Easy rooftop installation

Vertical or horizontal mounting, enabling the location of the inverter next to the PV modules and avoiding the installation of any additional rapid shutdown device.

# Standard 10 year warranty, extendable for up to 20 years

#### OPTIONAL ACCESSORIES

- Inverter communication via RS-485,
   Ethernet, Bluetooth or GSM / GPRS.
- Combiner Box with arc-fault circuit interruption and DC switch.
- INGECON® SUN WeatherBox for meteorological values measurement and registration.
- Self-consumption kit.


#### PROTECTIONS

- Reverse polarity.
- Input and output overvoltages with type 3 surge arresters.
- Out shortcircuits and overloads.
- Anti-islanding with automatic disconnection.
- Insulation failures.

#### MAIN FEATURES

- AFCI (Arc Fault Circuit Interrupt).
- Compatible with 30 mA RCDs.
- Easy rooftop installation.
- Double-MPPT system.
- Available from 2.8 up to 6 kW.
- 98.4% maximum efficiency.
- SiC Technology inside.
- Inverter updating by the user through a SD memory card.
- USB communications supplied as standard.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD Display.
- Easy maintenance.
- Suitable for indoor and outdoor installations (NEMA 3R).
- Display-configurable potential free contact, to indicate insulation fault or grid connection.
- Compact design.
- Plug & Play technology.
- Language, Country Code and rated voltage configurable by display.






#### **Combiner Box**

The Combiner Box is supplied with two inputs per MPPT, DC switch.

#### COMBINER BOX MAIN FEATURES

- DC switch.
- 2 MPPTs (2 inputs per MPPT).
- Fuses not required, according to NEC 2014 690.9.






	2.8TL U M	3.3TL U M	5TL U M	6TL U M	
Input (DC)					
Recommended PV array power range <sup>(1)</sup>	2.8 - 3.6 kW	3.4 - 4.3 kW	5.1 - 6.5 kW	6.1 - 7.8 kW	
Voltage range MPP <sup>(2)</sup>	125 - 750 V	125 - 750 V	125 - 750 V	125 - 750 V	
Voltage range MPP2 <sup>(2)(3)</sup>	90 - 750 V	90 - 750 V	90 - 750 V	90 - 750 V	
Min. voltage for Pnom with parallel inputs	127 V	155 V	234 V	281 V	
Maximum voltage <sup>(4)</sup>	850 V	850 V	850 V	850 V	
Maximum current (Input 1 / Input 2)	11 / 11 A	11 / 11 A	11 / 11 A	11 / 11 A	
Inputs (Input 1 / Input 2)	1/1	1/1	1/1	1/1	
MPPT	2	2	2	2	
Output (AC)					
Rated power	2.8 kW	3.3 kW	5 kW	6 kW	
Max. temperature at rated power <sup>(5)</sup>	113 °F	113 °F	113 °F	113 °F	
Maximum current	16 A	16 A	26.2 A	26.2 A	
Rated voltage	208 / 240 V	208 / 240 V	208 / 240 V	240 V	
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	
Phi Cosine	1	1	1	1	
Phi Cosine adjustable	Yes. Smax=2.8 kVA	Yes. Smax=3.3 kVA	Yes. Smax=5 kVA	Yes. Smax=6 kVA	
THD	<3%	<3%	<3%	<3%	
Efficiency					
Maximum efficiency	98.4%	98.4%	98.4%	98.4%	
CEC - Weighted efficiency	97.5%	97.5%	97.5%	97.5%	
General Information					
Refrigeration system		Natural air	r convection		
Stand-by consumption <sup>(6)</sup>	<10 W	<10 W	<10 W	<10 W	
Consumption at night	0 W	0 W	0 W	0 W	
Ambient temperature	-13 °F to 149 °F	-13 °F to 149 °F	-13 °F to 149 °F	-13 °F to 149 °F	
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	
Protection class	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R	
DC AFCI	17.				
Marking			, ETL		
EMC & Security standards		· · · · · · · · · · · · · · · · · · ·	E C37.90.1, IEEE C37.90.2		
	IEC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CODE				

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> The output power will be conditioned by the voltage and current configuration selected at each input <sup>(3)</sup> To drop to 90 V, the other input must be at least at 125 V <sup>(4)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(5)</sup> The output power will be reduced at the rate of 1% for each 1% of increase <sup>(6)</sup> Consumption from PV field.



#### Size and weight (mm)



2.8TL U M / 3.3TL U M 44.1 pounds 5TL U M / 6TL U M 46.3 pounds

#### INGECON SUN 1Play

HF U



#### 2.8HF U / 2.3HF U / 5HF U / 6HF U

Single-phase string inverter with a high-frequency transformer

The INGECON® SUN 1Play HF U inverters have been designed to maximize the power generation and also to facilitate user access to the PV plant. This solar inverter family is valid for low kilowatt residential applications, and also for decentralized commercial and utility-scale systems rated up to several hundred kilowatts. In domestic installations, these inverters present the great advantage of integrating an arc fault circuit interruption system (AFCI). Moreover, they are compatible with 30 mA RCDs, the most commonly used to protect the people against fatal electric discharges. The other main advantage is that it allows grounding the PV array.

#### High-frequency technology

A high-frequency transformer provides galvanic isolation between the input and output sides. This kind of transformer also reduces the weight of the inverter and increases the efficiency in relation to low frequency inverters with conventional galvanic isolation.

The INGECON® SUN 1Play HF U inverters are compatible with all the PV module technologies on the market, whilst allowing the PV generator to be grounded whenever required.

#### Easy to install

The grounding of the PV generator is also facilitated through built-in fuse holders. Every country-specific configuration and language can be easily selected from the inverter screen.

#### Maximum efficiency values

These inverters feature an innovative electronic conversion topology which, together with an advanced maximum power point tracking system (MPPT), leads of maximum efficiency rates of up to 96.3%, positioning them as market leaders.


#### Simple operation and maintenance

Ingeteam is at the forefront of innovative firmware. As a result, the INGECON® SUN 1Play HF U inverters are extremely easy to operate.

The menu displayed on the LCD screen has been designed so that it is simple and easy to use. These inverters feature an internal datalogger for several months data storage, accessible from a PC. Every inverter can be accessed from either a remote PC or on-site from the inverter front touch keypad through its LCD screen. The display also features a number of LEDs to indicate the inverter operating status. These LED indicators light up whenever any incident is detected, thereby simplifying and facilitating equipment maintenance tasks.

#### Firmware updating

The INGECON® SUN 1Play HF U inverters allow the user to perform the firmware updating himself. It is as easy as to download the latest version of the firmware from the Ingeteam website: **www.ingeteam.com**, and update it using a simple SD memory card.



## INGECON SUN 1Play

HF U

#### Monitoring and communication

The internal operating variables and the historical production data can be monitored through a number of media such as USB communications, supplied as standard. Also, RS-485, Ethernet, Bluetooth and GSM / GPRS communications are available upon demand. Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its Smartphone version iSun Monitor -available on the App Store- for monitoring and recording the inverter data over the Internet.

#### Able to withstand extreme conditions

The INGECON® SUN 1Play HF U inverter housing is suitable for outdoor use (NEMA 3R protection rating). Likewise, its innovative ventilation system allows it to be used in extreme atmospheric conditions with temperature ranges from -13 °F to +149 °F.

#### Compact design

This solar inverter presents a compact design. Older equipment used to have an external transformer that was coupled to the inverter's main body, but this new single-phase transformer inverter features an integrated topology that combines the transformer and the converter inside the same casing.

#### Easy rooftop installation

Vertical or horizontal mounting, enabling the location of the inverter next to the PV modules and avoiding the installation of any additional rapid shutdown device.

# Standard 10 year warranty, extendable for up to 20 years

#### OPTIONAL ACCESSORIES


- Inverter communication via RS-485, Ethernet, Bluetooth or GSM / GPRS.
- Combiner Box with DC fuses, DC switch.
- INGECON® SUN WeatherBox for meteorological values measurement and registration.
- Digital inputs.
- Self-consumption kit.

#### PROTECTIONS

- Galvanic isolation between the DC and AC sides.
- Reverse polarity.
- Input and output overvoltages with type 3 surge arresters.
- Out shortcircuits and overloads.
- Anti-islanding with automatic disconnection.
- Insulation failures.
- Grounding kit if required for the PV modules.

#### MAIN FEATURES

- AFCI (Arc Fault Circuit Interrupt).
- Compatible with grounded installations.
- High-frequency technology.
- Compatible with 30 mA RCDs.
- Available from 2.8 up to 6 kW.
- 96.3% maximum efficiency
- Inverter updating by the user through a SD memory card.
- USB communications supplied as standard.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD Display.
- Easy maintenance.
- Suitable for indoor and outdoor installations (NEMA 3R).
- Display-configurable potential free contact, to indicate insulation fault or grid connection.
- Compact design.
- Plug & Play technology.
- Language, Country Code and rated voltage configurable by display.




#### **Combiner Box**

The Combiner Box is supplied with four inputs, fuses on each pole, DC switch.

#### COMBINER BOX MAIN FEATURES


- DC switch.
- 4 inputs.
- 4 fuses per pole. Fuse rating: 20 A.
- Maximum current per input: 12 A.






	2.8HF U	3.3HF U	5HF U	6HF U
Input (DC)				
Recommended PV array power range <sup>(1)</sup>	2.9 - 3.6 kW	3.4 - 4.3 kW	5.2 - 6.5 kW	6.3 - 7.8 kW
Voltage range MPP	125 - 500 V	125 - 500 V	125 - 500 V	125 - 500 V
Min. voltage for rated power	165 V	150 V	152 V	182 V
Maximum voltage <sup>(2)</sup>	550 V	550 V	550 V	550 V
Maximum current	17 A	22 A	33 A	33 A
Inputs	1	1	1	1
MPPT	1	1	1	1
Output (AC)				
Rated power	2.8 kW	3.3 kW	5 kW	6 kW
Max. temperature at rated power <sup>(3)</sup>	120 °F	126 °F	131 °F	113 °F
Maximum current	13.5 A	16 A	26.2 A	26.2 A
Rated voltage	208 / 240 / 277 V	208 / 240 / 277 V	208 / 240 / 277 V	240 / 277 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz
Phi Cosine	1	1	1	1
Phi Cosine adjustable	Yes. Smax=2.8 kVA	Yes. Smax=3.3 kVA	Yes. Smax=5 kVA	Yes. Smax=6 kVA
THD	<3%	<3%	<3%	<3%
Efficiency				
Maximum efficiency	96.3%	96.3%	96.3%	96.3%
CEC - Weighted efficiency	95.5%	95.5%	95.5%	95.5%
General Information				
Refrigeration system	Air convection		Forced ventilation	
Air flow	-	0.44 ft <sup>3</sup> /s	0.88 ft <sup>3</sup> /s	0.88 ft <sup>3</sup> /s
Stand-by consumption <sup>(4)</sup>	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W
Ambient temperature	-13 °F to 149 °F	-13 °F to 149 °F	-13 °F to 149 °F	-13 °F to 149 °F
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R
DC AFCI		<b>√</b>	,	
Marking		CE,	ETL	
EMC & Security standards		UL1741, FCC Part 15, IEE	E C37.90.1, IEEE C37.90.2	
Grid connection standards		IEC 62116, UL1741, IEEE15	547, IEEE1547.1, NEC CODE	

**Notes:**  $^{(1)}$  Depending on the type of installation and geographical location  $^{(2)}$  Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures  $^{(3)}$  The output power will be reduced at the rate of 1% for each 1 °F of increase  $^{(4)}$  Consumption from PV field.



Size and weight (mm)



**2.8HF U / 3.3HF U / 5HF U / 6HF U** 55.12 pounds

## INGECON SUN Lite

TL



# 2.5TL / 3TL / 3.3TL / 3.68TL / 4.6TL / 5TL / 6TL / 7.5TL / 8.2TL / 8.6TL / 10TL

An inverter family with a wide range of outputs from 2.5 to 10 kW

Singlephase transformerless inverters, intended for the residential sector and for larger, decentralised projects.

#### Wide range of AC power outputs

The INGECON® SUN Lite TL single phase inverters offer an extensive range of power outputs from 2.5 to 10 kW. As a new addition, this range of inverters can now be supplied for 7.5 kW, 8.2 kW, 8.6 kW and 10 kW.

#### Simple installation and maintenance

Fast-on connectors on the DC side (type 4) and the AC side and RS-485 serial communications. The country-specific configuration and language can be easily selected from the inverter screen.

The INGECON® SUN Lite TL inverters feature an internal datalogger for three months' data storage with control from either a remote PC or on-site from the inverter front keypad through its LCD screen. Status and alarm LED indicators.

Fans are easily replaceable by the user. Configurable for self-consumption mode.

#### Software included

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor smartphone version for monitoring and recording the inverter data over the internet.

Standard 5 year warranty, extendable for up to 25 years

#### Size and weight (mm)



**2.5TL / 3TL** 18.3 kg.

**3.3TL / 3.68TL** 19.7 kg.

**4.6TL / 5TL / 6TL** 23.3 kg.


**7.5TL / 8.2TL / 8.6TL / 10TL** 25.2 kg.


#### PROTECTIONS

- Reverse polarity.
- Input and output overvoltages, type 3 surge arresters.
- Output short circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.

#### OPTIONAL ACCESSORIES

- DC switch.
- Inter-inverter communication via Bluetooth or Ethernet.
- GSM / GPRS remote communication.
- Potential free contact for insulation fault indication (by default) or inverter connected to the grid (optional).





	2.5TL	3TL	3.3TL	3.68TL	4.6TL	5TL
Input (DC)						
Recommended PV array power range(1)	2.8 - 3.3 kWp	3.2 - 4 kWp	3.8 - 4.3 kWp	3.9 - 4.8 kWp	5.2 - 6 kWp	5.7 - 6.5 kWp
Voltage range MPP	100 - 450 V	100 - 450 V	100 - 450 V	100 - 450 V	100 - 450 V	100 - 450 V
Minimum voltage for rated	160 V	195 V	155 V	175 V	145 V	160 V
Maximun voltage(2)	550 V	550 V	550 V	550 V	550 V	550 V
Maximum current	17 A	17 A	22 A	22 A	33 A	33 A
Inputs	3	3	3	3	4	4
MPPT	1	1	1	1	1	1
Output (AC)						
Rated power <sup>(3)</sup>	2.7 kW	3 kW	3.63 kW	3.68 kW	5 kW	5.5 kW
Maximum current	13 A	13.5 A	16 A	16 A	24.2 A	26.2 A
Rated voltage	230 / 240 V	230 / 240 V	230 / 240 V	230 / 240 V	230 / 240 V	230 / 240 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=2.7 kVA	Yes. Smax=3 kVA	Yes. Smax=3.63 kVA	Yes. Smax=3.68 kVA	Yes. Smax=5 kVA	Yes. Smax=5.5 kVA
THD	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency						
Maximum efficiency	96.6%	96.6%	96.8%	96.8%	97%	97%
Euroefficiency	95%	95.1%	95.2%	95.2%	96%	96.1%
General Information						
Air cooling	30 m³/h	30 m³/h	45 m³/h	45 m³/h	90 m³/h	90 m³/h
Stand-by consumption <sup>(5)</sup>	<10 W	<10 W	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W	0 W	0 W
Ambient temperature	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	IP65	IP65	IP65	IP65	IP65	IP65

	6TL	7.5TL	8.2TL	8.6TL	10TL
Input (DC)					
Recommended PV array power range <sup>(1)</sup>	6.3 - 7 kWp	8.7 - 10.3 kWp	9.5 - 11.2 kWp	10 - 11.8 kWp	11.6 - 13.7 kWp
Voltage range MPP	100 - 450 V	100 - 450 V	100 - 450 V	100 - 450 V	100 - 450 V
Minimum voltage for Pnom	190 V	215 V	235 V	245 V	300 V
Maximun voltage(2)	550 V	550 V	550 V	550 V	550 V
Maximum current	33 A	35 A	35 A	35 A	35 A
Inputs	4	4	4	4	4
MPPT	1	1	1	1	1
Output (AC)					
Rated power <sup>(3)</sup>	6 kW	7.5 kW	8.2 kW	8.6 kW	10 kW
Maximum current	26.2 A	36.1 A	36.1 A	36.1 A	36.1 A
Rated voltage	230 / 240 V	208 / 230 / 240 / 277 V <sup>(4)</sup>	230 / 240 / 277 V <sup>(4)</sup>	240 / 277 V <sup>(4)</sup>	277 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=6 kVA	Yes. Smax=7.5 kVA	Yes. Smax=8.2 kVA	Yes. Smax=8.6 kVA	Yes. Smax=10 kVA
THD	<3%	<3%	<3%	<3%	<3%
Efficiency					
Maximum efficiency	97%	97.5%	97.6%	97.7%	98%
Euroefficiency	96.1%	96.5%	96.6%	96.6%	96.8%
General Information					
Air cooling	90 m³/h	90 m³/h	90 m³/h	90 m³/h	90 m³/h
Stand-by consumption <sup>(5)</sup>	<10 W	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W	0 W
Ambient temperature	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	IP65	IP65	IP65	IP65	IP65

Marking: CE. EMC & Security standards: EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100. Grid connection standards: RD1699/2011, DIN V VDE V 0126-1-1, CEI 0-21, VDE-AR-N 4105:2011-08, 659/2, G83/2\*\*, P.O.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code Notes: (1) Depending on the type of installation and geographical location (2) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (3) AC Power for 45 °C ambient temperature (4) Voltage configurable through the display (5) Consumption from PV field (6) Related only inverters up to 16 A.

### INGECON SUN Lite

TL





#### 3.6TL U / 5TL U / 6TL U / 7.5TL U / 8.6TL U / 10TL U

Single phase TL inverters designed for the residential sector and larger, decentralized projects

The INGECON® SUN Lite TL U inverters are designed to adapt to the standards and regulations in force in the different international markets. The inverters are apt for different types of installations, ranging from residential up to commercial solar systems.

#### Maximum efficiency and flexibility

The INGECON® SUN Lite TL U inverters are compatible with all the PV module technology on the market, thereby permitting greater flexibility when sizing PV installations. Furthermore, they feature an advanced maximum power point tracker system (MPPT) to extract the maximum power from the PV array.

#### Software included

It includes, without any extra cost, RS-485 communications as well as the

software INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor Smartphone version for monitoring, displaying and recording the data from the inverter through the Internet. Each inverter incorporates an internal datalogger for up to 3 months data storage, which can be accessed from either a remote PC or on-site from the inverter front panel, through a keypad.

#### Robust design

This inverter features an aluminium casing, for indoor and outdoor installation, capable of withstanding very high temperatures. The INGECON®SUN Lite TLU inverters have been designed with components which offer a useful life of more than 20 years.

Standard 10 year warranty, extendable for up to 20 years

#### PROTECTIONS

- Reverse polarity.
- Input and output overvoltage.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.

#### OPTIONAL ACCESSORIES


- Inter-inverter communication via Ethernet, GSM / GPRS or wireless.
- Combiner Box that includes DC switch and fuses.



	3.6TL U	5TL U	6TL U	7.5TL U	8.6TL U	10TL U
Input (DC)						
Recommended PV array power range(1)	3.8 - 4.7 kWp	5.3 - 6.5 kWp	6.3 - 7.4 kWp	7.9 - 9.3 kWp	9.1 - 11 kWp	10.5 - 13.7 kWp
Voltage range MPP	125 - 450 V	125 - 450 V	125 - 450 V	125 - 450 V	125 - 450 V	125 - 450 V
Minimum voltage for Pnom	200 V	200 V	200 V	225 V	250 V	300 V
Maximun voltage(2)	550 V	550 V	550 V	550 V	550 V	550 V
Maximum current	22 A	30 A	32 A	35 A	35 A	35 A
Inputs	4	4	4	4	4	4
MPPT	1	1	1	1	1	1
Output (AC)						
Rated power <sup>(3)</sup>	3.6 kW	5 kW	6 kW	7.5 kW	8.6 kW	10 kW
Maximum current	17.5 A	25 A	26.2 A	36.1 A	36.1 A	36.1 A
Rated voltage	208 / 240 / 277 V	208 / 240 / 277 V	240 / 277 V	208 / 240 / 277 V	240 / 277 V	277 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=3.6 kVA	Yes. Smax=5 kVA	Yes. Smax=6 kVA	Yes. Smax=7.5 kVA	Yes. Smax=8.6 kVA	Yes. Smax=10 kVA
THD <sup>(4)</sup>	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency						
Maximum efficiency	98%	97.2%	97.7%	97.8%	97.8%	97.8%
CEC - Weighted efficiency	96.5%	96%	96.5%	97%	97%	97%
General Information						
Stand-by consumption	<10 W	<10 W	<10 W	<10 W	<10 W	<10 W
Consumption at night	0 W	0 W	0 W	0 W	0 W	0 W
Ambient temperature	-4 °F to +150 °F	-4 °F to +150 °F	-4 °F to +150 °F	-4 °F to +150 °F	-4 °F to +150 °F	-4 °F to +150 °F
Relative humidity (non-condensing)	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%	0 - 100%
Protection class	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R
Marking			CE	, ETL		
EMC and security standards	UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90.2					
Grid connection standards		IEC	62116, UL1741, IEEE1	547, IEEE1547.1, NEC C	ODE	

**Notes:** (1) Depending on the type of installation and geographical location (2) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (3) AC Power for 45 °C ambient temperature (4) For Poul> 25% of the rated power.

# PV input Combiner Box (optional) Positive Inverter Inverter Inverter



TL



#### 10TL / 12.5TL / 15TL / 20TL / 28TL / 33TL

Three-phase TL inverters with the maximum efficiency at the best price

A three-phase inverter family for domestic, industrial and large-scale PV plants.

#### Maximum efficiency at the best price

A single DC-to-AC power conversion stage with an advanced single maximum power point tracking system (MPPT), that makes it possible to harness the maximum energy from the PV array at the most competitive price.

#### Plug & Play technology

Extremely easy to install. The inverter connection is fast and simple. The country-specific configuration and language can be easily selected from the inverter screen.

#### Rugged design

Steel casing, especially designed for indoor and outdoor applications (IP65). Able to withstand extreme temperatures. The INGECON® SUN 3Play TL inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to.

#### Ease of maintenance

Internal datalogger for up to 3 months data storage. Control either from a remote PC or on-site from the inverter front keypad. Status and alarm LED indicators. LCD screen.

#### Easy to operate

The INGECON® SUN 3Play TL inverters feature a LCD screen for the simple and convenient monitoring of the inverter

status and a range of internal variables. The display also includes three LEDs to show the inverter operating status. All this helps to simplify and facilitate maintenance tasks.

#### Software included

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its smartphone version iSun Monitor for monitoring and recording the inverter data over the internet. RS-485 communications are supplied as standard. In addition, users can download the latest version of the firmware from the Ingeteam website: www.ingeteam.com, and update it using a simple SD memory card.

Standard 5 year warranty, extendable for up to 25 years



# INGECON SUN 3Play

TL

#### Different versions to choose from

In order to satisfy its clients' needs, Ingeteam has created four different versions for the INGECON® SUN 3Play TL family:

- "S": Standard version
- "S+": Advanced Standard version
- "P": Premium version
- "P+": Advanced Premium version

All the versions are supplied with DC and AC varistors. The "S" version represents the most basic model of all. It features a single MPPT input with terminal blocks. The Advanced Standard version "S+" also features a DC switch.

On the other hand, the Premium version includes two options for DC connection: conventional terminal blocks or fused and monitored PV connectors.

Moreover, it also features DC fuses, the input current measuring kit and a DC switch. The Advanced Premium version "P+" is supplied with DC surge arresters, type 2.

#### MAIN FEATURES

- MPPT system.
- 98.5% maximum efficiency.
- Digital inputs.
- RS-485 communications supplied as standard.
- Inverter firmware updating by the user through a SD memory card.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD display.
- Easy maintenance.
- Display-configurable potential-free contact, to indicate insulation fault or grid connection.
- Plug & Play technology.
- Suitable for indoor and outdoor installations (IP65).
- High temperature performance.
- Different versions to satisfy every project needs.
- Compact design.
- Language, rated voltage and Country Code configurable by display.

#### PROTECTIONS

- Reverse polarity.
- Shortcircuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Insulation faults.


#### OPTIONAL ACCESORIES

- Inverter communication via Ethernet,
   Bluetooth, GSM / GPRS or Wi-Fi. A second
   RS-485 communication card is available.
- Self-consumption kit.

#### BENEFITS

- The best possible price.
- High efficiency rates.
- Easy maintenance.

	Standard	l version	Premium version		
	S	S+	Р	P+	
Terminal blocks	✓	✓	✓	✓	
PV connectors			✓	✓	
DC switch		✓	✓	✓	
DC surge arresters				✓	
DC fuses			✓	✓	
Current measuring kit			✓	✓	
DC and AC varistors	✓	✓	✓	✓	




	10TL	12.5TL	15TL	20TL	28TL	33TL
Input (DC)						
Recommended PV array power range <sup>(1)</sup>	10.3 - 13.4 kW	12.9 - 16.8 kW	15.5 - 20.1 kW	20.6 - 26.8 kW	28.9 - 37.5 kW	34 - 45 kW
Voltage range MPP	560 - 820 V	560 - 820 V	560 - 820 V	560 - 820 V	560 - 820 V	560 - 820 V
Min. voltage for Pnom at rated Vac	560 V	560 V	560 V	560 V	560 V	560 V
Maximum voltage(2)	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V
Maximum current(3)	19 A	24 A	28 A	37 A	52 A	61 A
Inputs for the S and S+ versions	1	1	1	1	1	1
Inputs for the P and P+ versions <sup>(4)</sup>	4	4	5	5	8	8
MPPT	1	1	1	1	1	1
Output (AC)						
Rated power	10 kW	12.5 kW	15 kW	20 kW	28 kW	33 kW
Max. temperature at rated power <sup>(5)</sup>	55 °C	55 °C	55 °C	55 °C	45 °C	45 °C
Maximum current	15 A	19 A	22 A	29 A	41 A	48 A
Rated voltage	400 V	400 V	400 V	400 V	400 V	400 V
Voltage range	277 - 528 V	277 - 528 V	277 - 528 V	277 - 528 V	277 - 528 V	277 - 528 V
Frecuency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=10 kVA	Yes. Smax=12.5 kVA	Yes. Smax=15 kVA	Yes. Smax=20 kVA	Yes. Smax=28 kVA	Yes. Smax=33 kVA
THD	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency						
Maximum efficiency	98.5%	98.5%	98.5%	98.5%	98.5%	98.5%
Euroefficiency	98.3%	98.3%	98.4%	98.3%	98.3%	98.3%
General Information						
Refrigeration system			Forced v	ventilation		
Air flow	200 m <sup>3</sup> /h	200 m³/h	200 m <sup>3</sup> /h	200 m <sup>3</sup> /h	400 m <sup>3</sup> /h	400 m <sup>3</sup> /h
Stand-by consumption <sup>(7)</sup>	10 W	10 W	10 W	10 W	10 W	10 W
Consumption at night	1 W	1 W	1 W	1 W	1 W	1 W
Ambient temperature	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Protection class	IP65	IP65	IP65	IP65	IP65	IP65
Marking			(	DE .		
EMC and security standards	EN 61000-6-1, EN 6	1000-6-2, EN 61000-6-3 EN 6				00-3-12, EN 62109-1,
Grid connection standards	EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100  RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-16 Ed. III, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2 <sup>III</sup> , P.O.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code					

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> The maximum current per PV connector is 11 A <sup>(4)</sup> Optionally, the DC inputs could be duplicated <sup>(5)</sup> For each °C of increase, the output power will be reduced at the rate of 1.8% <sup>(6)</sup> For Pout>25% of the rated power <sup>(7)</sup> Consumption from PV field <sup>(8)</sup> Related only to inverters up to 16 A.



Size and weight (mm)



10TL / 12.5TL / 15TL / 20TL 46.8 kg. 28TL / 33TL 51.5 kg.

#### INGECON SUN 3Play

TL M



#### 10TL M / 12.5TL M / 15TL M / 20TL M / 28TL M / 33TL M

Maximum efficiency with Multi-MPPT three-phase technology

A three-phase inverter family for domestic, industrial and large-scale PV plants.

# Maximum efficiency with two independent MPPT inputs

A single DC-to-AC power conversion stage with an advanced maximum power point tracking system (MPPT), making it possible to harness the maximum energy from the PV array at all times, including difficult situations such as scattered clouds and partial shading. Great flexibility for configuring the solar array, thanks to the two independent MPPT trackers with a wide input voltage range. Possibility of asymmetrical configurations.

#### Plug & Play technology

Extremely easy to install. The inverter connection is fast and simple. The country-specific configuration and language can be easily selected from the inverter screen.

#### Rugged design

Steel casing, especially designed for indoor and outdoor applications (IP65). Able to withstand extreme temperatures. The 3Play TL M inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to.

#### Ease of maintenance

Internal datalogger for up to 3 months data storage. Control either from a remote PC or on-site from the inverter front keypad. Status and alarm LED indicators. LCD screen.

#### Easy to operate

The INGECON® SUN 3Play TL M inverters feature a LCD screen for the simple and convenient monitoring of the inverter status and a range of internal variables. The display also includes three LEDs to show the inverter opera-

ting status. All this helps to simplify and facilitate maintenance tasks.

#### Software included

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its smartphone version iSun Monitor for monitoring and recording the inverter data over the internet. In addition, users can download the latest version of the firmware from the Ingeteam website **www.ingeteam.com**, and update it using a simple SD memory card. RS-485 communications are supplied as standard.

# Standard 5 year warranty, extendable for up to 25 years

#### Different versions to choose from

In order to satisfy its clients' needs, Ingeteam has created four different versions for the INGECON® SUN 3Play TL M family:

- "S": Standard version
- "S+": Advanced Standard version
- "P": Premium version
- "P+": Advanced Premium version

All the versions are supplied with DC and AC varistors. The "S" version represents the most basic model of all. It features a single MPPT input with terminal blocks. The Standard version "S+" also features DC switch.

On the other hand, the Premium version includes two options for DC connection: conventional terminal blocks or fused and monitored PV connectors.

Moreover, it also features DC fuses, the input current measuring kit and the DC. The Advanced Premium version "P+" is supplied with DC surge arresters, type 2.

#### MAIN FEATURES

- Double-MPPT system.
- 98.5% maximum efficiency.
- Digital inputs.
- RS-485 communications supplied as standard.
- Inverter firmware updating by the user through a SD memory card.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD display.
- Easy maintenance.
- Display-configurable potential-free contact, to indicate insulation fault or grid connection.
- Plug & Play technology.
- Suitable for indoor and outdoor installations (IP65).
- High temperature performance.
- Different versions to satisfy every project needs.
- Compact design.
- Language, rated voltage and Country Code, rated voltage configurable by display.

#### PROTECTIONS

- Reverse polarity.
- Shortcircuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Insulation faults.

#### OPTIONAL ACCESORIES

- Inverter communication via Ethernet,
   Bluetooth, GSM / GPRS or Wi-Fi. A second
   RS-485 communication card is available.
- Self-consumption kit.

#### BENEFITS

- Greater performance thanks to the double MPPT system.
- Easy maintenance.
- Higher inverter life expectance.

	Standard version		Premiun	n version
	S	S+	P	P+
Terminal blocks	✓	✓	✓	✓
PV connectors			✓	✓
DC switch		✓	✓	✓
DC surge arresters				✓
DC fuses			✓	✓
Current measuring kit			✓	✓
DC and AC varistors	✓	✓	✓	✓


#### 3Play TL M P+ version (20 kW) Inverter PV input MPPT1 11 1 -ilter 12 13 AC output for · 🗆 connection to the grid MPPT2 © 🔲 PV input Ν Optional Optional

	10TL M	12.5TL M	15TL M	20TL M
Input (DC)				
Recommended PV array power range <sup>(1)</sup>	10.3 - 13.4 kW	12.9 - 16.8 kW	15.5 - 20.1 kW	20.6 - 26.8 kW
Voltage range MPP1(2)	200 - 820 V	200 - 820 V	200 - 820 V	200 - 820 V
Voltage range MPP2 <sup>(2)</sup>	200 - 820 V	200 - 820 V	200 - 820 V	200 - 820 V
Min. voltage for Pnom with parallel inputs	260 V	325 V	310 V	415 V
Maximum voltage <sup>(3)</sup>	1,000 V	1,000 V	1,000 V	1,000 V
Maximum current <sup>(4)</sup> Input 1 / Input 2)	20 / 20 A	20 / 20 A	30 / 20 A	30 / 20 A
Inputs for the S and S+ versions (Input 1 / Input 2)	1/1	1/1	1/1	1/1
Inputs for the P and P+ versions (Input 1 / Input 2) <sup>(5)</sup>	2/2	2/2	3/2	3/2
MPPT	2	2	2	2
Output (AC)				
Rated power	10 kW	12,5 kW	15 kW	20 kW
Max. temperature at rated power <sup>(6)</sup>	55 °C	55 °C	55 °C	55 °C
Maximum current	15 A	19 A	22 A	29 A
Rated voltage	400 V	400 V	400 V	400 V
/oltage range	277 - 528 V	277 - 528 V	277 - 528 V	277 - 528 V
recuency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(7)</sup>	1	1	1	1
Phi Cosine adjustable	Yes. Smax=10 kVA	Yes. Smax=12.5 kVA	Yes. Smax=15 kVA	Yes. Smax=20 kVA
THD	<3%	<3%	<3%	<3%
Efficiency				
Maximum efficiency	98.5%	98.5%	98.5%	98.5%
Euroefficiency	98.3%	98.3%	98.3%	98.3%
General Information				
Refrigeration system		Forced ve		
Air flow	200 m³/h	200 m <sup>3</sup> /h	200 m <sup>3</sup> /h	200 m³/h
Stand-by consumption <sup>(8)</sup>	10 W	10 W	10 W	10 W
Consumption at night	1 W	1 W	1 W	1 W
Ambient temperature	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C	-25 °C to 65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Protection class	IP65	IP65	IP65	IP65
Marking		CE		
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100			
Grid connection standards	RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-16 Ed. III, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2 <sup>(9)</sup> , P.0.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romaniar Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code			

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> The output power will be conditioned by the voltage and current configuration selected at each input <sup>(3)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(4)</sup> The maximum current per PV connector is 11 A <sup>(5)</sup> Optionally, the DC inputs could be duplicated <sup>(6)</sup> For each °C of increase, the output power will be reduced at the rate of 1.8% <sup>(7)</sup> For  $P_{\text{out}} > 25\%$  of the rated power <sup>(8)</sup> Consumption from PV field <sup>(9)</sup> Related only to inverters up to 16 A.



Size and weight (mm)




**10TL M / 12.5TL M** 56.2 kg. **15TL M / 20TL M** 57.8 kg.

	28TL M	33TL M	
Input (DC)			
Recommended PV array power range(1)	28.9 - 37.5 kW	34 - 45 kW	
Voltage range MPP1(2)	200 - 820 V	200 - 820 V	
Voltage range MPP2 <sup>(2)</sup>	200 - 820 V	200 - 820 V	
Min. voltage for Pnom with parallel inputs	365 V	430 V	
Maximum voltage <sup>(3)</sup>	1,000 V	1,000 V	
Maximum current <sup>(4)</sup> (Input 1 / Input 2)	40 / 30 A	40 / 40 A	
Inputs for the S and S+ versions (Input 1 / Input 2)	1/1	1/1	
Inputs for the P and P+ versions (Input 1 / Input 2) <sup>(5)</sup>	5/5	5/5	
MPPT	2	2	
Output (AC)			
Rated power	28 kW	33 kW	
Max. temperature at rated power <sup>(6)</sup>	45 °C	45 °C	
Maximum current	41 A	48 A	
Rated voltage	400 V	400 V	
Voltage range	277 - 528 V	277 - 528 V	
Frecuency	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(7)</sup>	1	1	
Phi Cosine adjustable	Yes. Smax=28 kVA	Yes. Smax=33 kVA	
THD	<3%	<3%	
Efficiency			
Maximum efficiency	98.5%	98.5%	
Euroefficiency	98.3%	98.3%	
General Information			
Refrigeration system	Forced	ventilation	
Air flow	400 m³/h	400 m³/h	
Stand-by consumption <sup>(8)</sup>	10 W	10 W	
Consumption at night	1 W	1 W	
Ambient temperature	-20 °C to 65 °C	-20 °C to 65 °C	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	
Protection class	IP65	IP65	
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100		
Grid connection standards	RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-16 Ed. III, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2 <sup>®</sup> , P.O.12.3, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, DEWA (Dubai) Grid Code, Jordan Grid Code		

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> The output power will be conditioned by the voltage and current configuration selected at each input <sup>(3)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(4)</sup> The maximum current per PV connector is 11 A <sup>(5)</sup> Optionally, the DC inputs could be duplicated <sup>(6)</sup> For each °C of increase, the output power will be reduced at the rate of 1.8% <sup>(7)</sup> For  $P_{\text{out}} > 25\%$  of the rated power <sup>(8)</sup> Consumption from PV field <sup>(9)</sup> Related only to inverters up to 16 A.



Size and weight (mm)



**28TL M / 33TL M** 62.5 kg.

#### INGECON SUN 3Play

TL U M



#### 18TL U M480 / 24TL U M480 / 40TL U M480

Maximum efficiency with Multi-MPPT three-phase technology

A three-phase inverter family for residential, commercial and large-scale PV plants. It integrates an arc fault circuit interruption system (AFCI).

# Maximum efficiency with two independent MPPT inputs

A single DC-to-AC power conversion stage with an advanced maximum power point tracking system (MPPT), making it possible to harness the maximum energy from the PV array at all times, including difficult situations such as scattered clouds and partial shading. Great flexibility for configuring the solar array, thanks to the two independent MPPT trackers with a wide input voltage range. Possibility of asymmetrical configurations.

#### Plug & Play technology

Extremely easy to install. The inverter connection is fast and simple. The coun-

try-specific configuration and language can be easily selected from the inverter screen

#### Rugged design

Steel casing, especially designed for indoor and outdoor applications (NEMA 4). It with-stands extreme temperatures. The 3Play inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to.

#### Ease of maintenance

Internal datalogger for up to 3 months data storage. Control either from a remote PC or on-site from the inverter front keypad. Status and alarm LED indicators. LCD screen. Integrated DC arc-fault circuit interruption system.

#### Easy to operate


The INGECON® SUN 3Play TL U M inverters feature a LCD screen for the

simple and convenient monitoring of the inverter status and a range of internal variables. The display also includes three LEDs to show the inverter operating status. All this helps to simplify and facilitate maintenance tasks.

#### Software included

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its smartphone version iSun Monitor for monitoring and recording the inverter data over the internet. In addition, users can download the latest version of the firmware from the Ingeteam website **www.ingeteam.com**, and update it using a simple SD memory card. RS-485 communications are supplied as standard.

# Standard 10 year warranty, extendable for up to 20 years



### INGECON SUN 3Play

#### TL U M

#### A versatile equipment

The INGECON® SUN 3Play TL U M inverters integrate an arc-fault circuit interruption system.

The standard inverter features a double MPPT input with terminal blocks. Optionally, it can be supplied with DC and AC surge arresters, type 2.

#### Easy rooftop installation

Vertical or horizontal mounting, enabling the location of the inverter next to the PV modules and avoiding the installation of any additional rapid shutdown device.

#### MAIN FEATURES


- AFCI (Arc Fault Circuit Interrupt).
- Double-MPPT System.
- Easy rooftop installation.
- 98.5% maximum efficiency.
- Inverter firmware updating by the user through a SD memory card.
- Software INGECON® SUN Manager for PV plant access and data registration.
- Software INGECON® SUN Monitor for PV plant monitoring.
- LCD display.
- RS-485 communications supplied as standard
- Display-configurable potential-free contact, to indicate insulation fault or grid connection.
- Plug & Play technology.
- Suitable for indoor and outdoor installations (NEMA 4).
- High temperature performance. Rated power up to 131 °F (55 °C) for the 18 kW and 24 kW inverters.
- Language, rated voltage and Country Code configurable by display.

#### PROTECTIONS

- Reverse polarity.
- DC arc-fault circuit interruption.
- Shortcircuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Insulation faults.

#### OPTIONAL ACCESSORIES

- Inter-inverter communication via Ethernet, Bluetooth, GSM / GPRS or Wi-Fi.
- Combiner Box with DC fuses and DC switch.
- DC surge arresters, type 2.




#### **Combiner Box**

The Combiner Box is supplied with four or six inputs per MPPT with fuses on each pole and a DC switch. It can be located immediately under the PV inverter or in a different place.

#### COMBINER BOX MAIN FEATURES

- DC switch.
- 2 MPPTs (4 inputs / MPPT for the 18 kW and 24 kW models, and 6 inputs / MPPT for the 40 kW model).
- 4 fuses per pole for the 18 kW and 24 kW models and 6 fuses per pole for the 40 kW model.
- Maximum current per input: 12 A.






	18TL U M480	24TL U M480	40TL U M480
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	18.6 - 24.1 kW	24.7 - 32.2 kW	41.2 - 53.6 kW
Voltage range MPP1(2)	200 - 820 V	200 - 820 V	200 - 820 V
Voltage range MPP2(2)	200 - 820 V	200 - 820 V	200 - 820 V
Min. voltage for Pnom with parallel inputs	375 V	460 V	520 V
Maximum voltage <sup>(3)</sup>	1,000 V	1,000 V	1,000 V
Maximum current (Input 1 / Input 2)	30 / 20 A	27 / 27 A	40 / 40 A
Inputs (Input 1 / Input 2)	1/1	1/1	1/1
MPPT	2	2	2
Output (AC)			
Rated power	18 kW	24 kW	40 kW
Temperature at rated power <sup>(4)</sup>	131 °F	131 °F	113 °F
Maximum current	22 A	29 A	48 A
Rated voltage	480 V	480 V	480 V
Frequency	60 Hz	60 Hz	60 Hz
Phi Cosine <sup>(5)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=18 kVA	Yes. Smax=24 kVA	Yes. Smax=40 kVA
THD	<3%	<3%	<3%
Efficiency			
Maximum efficiency	98.5%	98.5%	98.5%
CEC - Weighted efficiency	98%	98%	98%
General Information			
Refrigeration system		Forced ventilation	
Air flow	200 m³/h	200 m³/h	400 m³/h
Stand-by consumption <sup>(6)</sup>	10 W	10 W	20 W
Consumption at night	1 W	1 W	1 W
Ambient temperature	-13 °F to 149 °F	-13 °F to 149 °F	-13 °F to 149 °F
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	NEMA 4	NEMA 4	NEMA 4
DC AFCI	✓	✓	✓
Marking		CE, ETL	
EMC and security standards		UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90	.2
Grid connection standards		EC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CO	DDE

**Notes:** <sup>(1)</sup> Depending on the type of installation and geographical location <sup>(2)</sup> The output power will be conditioned by the voltage and current configuration selected at each input <sup>(3)</sup> Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures <sup>(4)</sup> The output power will be reduced at the rate of 1% for each 1 °F of increase <sup>(5)</sup> For Pout>25% of the rated power <sup>(6)</sup> Consumption from PV field.



Size and weight (inches)



**18TL U M / 24TL U M / 40TL U M** 127.4 / 129 / 137.8 lbs

# INGECON SUN Power

With transformer



#### 50 / 60 / 70 / 80 / 90 / 100

Three phase inverter for medium and large power outputs on-roof applications and also for ground-based multi-megawatt applications

# Maximum efficiency at high temperatures

Advanced maximum power point tracker system (MPPT). Low voltage ride through capability, active power control and reactive power control. Suitable for medium voltage installations.

#### Easy to install

No additional items are required. Manual disconnection from the grid. Complete electrical protection equipment supplied as standard.

#### Easy to maintain

Internal datalogger for up to 3 months data storage. Control from either a remote PC or on-site from the inverter front key pad. Status and alarm LED indicators. LCD Screen. Useful life of more than 20 years.

#### Software included

Included at no extra cost are the INGE-CON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor smartphone version for monitoring and recording the inverter data over the internet.


# Standard 5 year warranty, extendable for up to 25 years

#### PROTECTIONS

- Galvanic isolation between the DC and AC side.
- Reverse polarity.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.
- DC switch.
- DC fuses.
- AC circuit breaker.
- DC and AC surge arresters type 2.


#### OPTIONAL ACCESSORIES


- Inter-inverter communication via RS-485, Ethernet or Bluetooth.
- GSM / GPRS remote communication.
- PV array string current monitoring. INGECON® SUN String Control.
- Grounding kit if required for the PV modules.



	50	60	70	80	90	100
Input (DC)						
Recommended PV array power range <sup>(1)</sup>	52 - 65 kWp	63 - 78 kWp	73 - 91 kWp	83 - 104 kWp	93 - 117 kWp	104 - 130 kWp
Voltage range MPP	405 - 750 V	405 - 750 V	405 - 750 V	405 - 750 V	405 - 750 V	405 - 750 V
Maximum voltage <sup>(2)</sup>	900 V	900 V	900 V	900 V	900 V	900 V
Maximum current	130 A	156 A	182 A	208 A	234 A	260 A
Inputs	4	4	4	4	4	4
MPPT	1	1	1	1	1	1
Output (AC)						
Rated power <sup>(3)</sup>	55 kW	66 kW	77 kW	88 kW	99 kW	110 kW
Maximum current	93 A	118 A	131 A	156 A	161 A	161 A
Rated voltage	400 V	400 V	400 V	400 V	400 V	400 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=55 kVA	Yes. Smax=66 kVA	Yes. Smax=77 kVA	Yes. Smax=88 kVA	Yes. Smax=99 kVA	Yes. Smax=110 kVA
THD <sup>(5)</sup>	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency						
Maximum efficiency	96.3%	96.4%	97.2%	97.5%	96.9%	96.8%
Euroefficiency	94.3%	94.7%	96.1%	96.2%	95.8%	95.7%
General Information						
Air cooling	2,600 m <sup>3</sup> /h	2,600 m³/h				
Stand-by consumption <sup>(6)</sup>	30 W	30 W	30 W	30 W	30 W	30 W
Consumption at night	1 W	1 W	1 W	1 W	1 W	1 W
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20	IP20	IP20	IP20	IP20	IP20
Marking			(	DE .		
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS3100					
Grid connection standards	IEC 62116, RD1699/2011, DIN V VDE V 0126-1-1, CEI 0-16 Ed. III, CEI 0-21, G59/2, VDE-AR-N 4105:2011-08, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code, Chilean Grid Code, Romanian Grid Code, IEEE929, Thailand MEA & PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code					

Notes: (1) Depending on the type of installation and geographical location (2) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (3) AC Power for 40 °C ambient temperature. For each °C of increase, the output power will be reduced at the rate of 1.8% (4) For Pout>25% of the rated power (5) For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 (6) Consumption from PV field.





# INGECON SUN Power

#### Transformerless



# 110TL B220 / 140TL B220 / 175TL B275 / 190TL B300 / 200TL B320 / 220TL B345 / 230TL B360 / 250TL B400

Three phase inverter for medium and large power outputs on-roof applications and also for ground-based multi-megawatt applications

# Maximum efficiency at high temperatures

Advanced maximum power point tracker system (MPPT). Low voltage ride through capability, active power control and reactive power control. Suitable for medium voltage installations.

#### Easy to install

No additional items are required. Manual disconnection from the grid. Complete electrical protection equipment supplied as standard.

#### Easy to maintain

Internal datalogger for up to 3 months data storage. Control from either a remote PC or on-site from the inverter front key pad. Status and alarm LED indicators. LCD Screen. Useful life of more than 20 years.

#### Software included

Included at no extra cost are the INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor smartphone version for monitoring and recording the inverter data over the internet.

# Standard 5 year warranty, extendable for up to 25 years

#### PROTECTIONS

- Reverse polarity.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.
- DC switch.
- DC fuses.
- AC circuit breaker.
- DC and AC surge arresters, type 2.

#### OPTIONAL ACCESSORIES

- Inter-inverter communication via RS-485, Ethernet or Bluetooth.
- GSM / GPRS remote communication.
- PV array string current monitoring. INGECON® SUN String Control.
- Grounding kit if required for the PV modules.
- Synchronization available with other inverters, to connect to the same MV transformer.




	110TL B220	140TL B220	175TL B275	190TL B300	200TL B320	220TL B345	230TL B360	250TL B400
Input (DC)								
Recommended PV array power range <sup>(1)</sup>	103 - 130 kWp	141 - 163 kWp	169 - 195 kWp	193 - 224 kWp	205 - 238 kWp	224 - 260 kWp	233 - 273 kWp	254 - 295 kWp
Voltage range MPP	405 - 820 V	405 - 820 V	420 - 820 V	437 - 820 V	468 - 820 V	502 - 820 V	524 - 820 V	578 - 820 V
Maximum voltage(2)	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V	1,000 V
Maximum current	400 A	400 A	400 A	400 A	400 A	400 A	400 A	450 A
Inputs	4	4	4	4	4	4	4	4
MPPT	1	1	1	1	1	1	1	1
Output (AC)								
Rated power <sup>(3)</sup>	110 kW	137.5 kW	173 kW	189.2 kW	201.3 kW	220 kW	229 kW	250 kW
Maximum current	368 A	368 A	368 A	368 A	368 A	368 A	368 A	368 A
Rated voltage	220 V IT System	220 V IT System	275 V IT System	300 V IT System	320 V IT System	345 V IT System	360 V IT System	400 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=110 kVA	Yes. Smax=137 kVA	Yes. Smax=173 kVA	Yes. Smax=189.2 kVA	Yes. Smax=201.3 kVA	Yes. Smax=220 kVA	Yes. Smax=229 kVA	Yes. Smax=250 kVA
THD <sup>(5)</sup>	<3%	<3%	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency								
Maximum efficiency	98.4%	98.1%	98.5%	98.6%	98.7%	98.8%	98.8%	98.9%
Euroefficiency	97.5%	97.7%	98.2%	98.3%	98.4%	98.5%	98.6%	98.6%
General Information								
Air cooling	2,600 m <sup>3</sup> /h	2,600 m <sup>3</sup> /h	2,600 m³/h	2,600 m³/h	2,600 m³/h	2,600 m <sup>3</sup> /h	2,600 m <sup>3</sup> /h	2,600 m³/h
Stand-by consumption <sup>(6)</sup>	30 W	30 W	30 W	30 W	30 W	30 W	30 W	30 W
Consumption at night	<5 W	<5 W	<5 W	<5 W	<5 W	<5 W	<5 W	<5 W
Ambient temperature	-20 °C to +65 °C	-20 ° C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Marking					CE			
EMC and security standards	EN 61000-6-	1, EN 61000-6-2, EN	1 61000-6-4, EN 610	000-3-11, EN 61000	-3-12, EN 62109-1, E	N 62109-2, IEC6210	3, EN 50178, FCC Pa	rt 15, AS3100
Grid connection standards	IEC 62116, RD1699/2011, DIN V VDE V 0126-1-1, CEI 0-16, G59/2, VDE-AR-N 4105:2011-08, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code, Chilean Grid Code, Romanian Grid Code, IEEE929, Thailand MEA & PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code							

Notes: (1) Depending on the type of installation and geographical location (2) Never exceed 1,000 V. Consider the voltage increase of the 'Voc' at low temperatures (3) AC Power for 40 °C ambient temperature. For each °C of increase, the output power will be reduced at the rate of 1.8% (4) For Pout>25% of the rated power (5) For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 (6) Consumption from PV field.

# Power TL PV input AC output for connection to a a private LV network AC output for connection to a a private LV network

1,761



110TL B220 / 140TL B220 / 175TL B275 / 190TL B300 200TL B320 / 220TL B345 / 230TL B360 / 250TL B400  $600\,\mathrm{kg}.$ 

# INGECON SUN Power

With transformer





#### 125 U 208 Outdoor / 125 U 480 Outdoor

The best performance at medium and large outdoor installations

Designed for ease of maintenance, capable of withstanding extreme temperatures, and featuring full electric protections as a standard supply, the INGECON® SUN Power 125 U Outdoor inverter is one of the latest Ingeteam's developments. It has been especially designed for medium and large outdoor installations.

#### Easy to install and maintain

The INGECON® SUN Power 125 U inverter has been manufactured with components which offer a useful life of more than 20 years. This inverter is equipped with an advanced maximum power point tracking system (MPPT) to obtain the maximum power from the PV

array. No additional items are required and it can be manually disconnected from the grid.

#### Software included

It includes, without any extra cost, RS-485 communications as well as the software INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor Smartphone version for monitoring, displaying and recording the data from the inverter through the Internet. Each inverter incorporates an internal datalogger for up to 3 months data storage, which can be accessed from either a remote PC or on-site from the inverter front panel, through a keypad.

# for up to 20 years


# Standard 5 year warranty, extendable

#### PROTECTIONS

- Reverse polarity.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.
- AC circuit breaker.
- DC switch.
- AC and DC surge arresters, type 2.
- Plus / minus grounding PV modules.
- Galvanic isolation between the DC and AC sides.

#### OPTIONAL ACCESSORIES


- Inter-inverter communication via Ethernet. For other communications, please check availability.
- DC fuses.
- Motorization of the AC breaker.
- Auxiliary services kit.
- Low voltage ride-through kit.
- -30 °C (-22 °F) operating kit.
- Night supply.
- INGECON® SUN String Control for PV array string current monitoring.




	125 U 208 Outdoor	125 U 480 Outdoor	
Input (DC)			
Recommended PV array power range(1)	128.5 - 167.1 kWp	129.2 - 168 kWp	
Voltage range MPP	330 - 820 V	330 - 820 V	
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V	
Maximum current	390 A	390 A	
Inputs	4	4	
MPPT	1	1	
Output (AC)			
Rated power <sup>(3)</sup>	125 kW	125 kW	
Maximum current	347 A	150 A	
Rated voltage	208 V	480 V	
Frequency	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(4)</sup>	1	1	
Phi Cosine adjustable	Yes. Smax=125 kVA	Yes. Smax=125 kVA	
THD <sup>(5)</sup>	<3%	<3%	
Efficiency			
Maximum efficiency	98.4%	97.3%	
CEC - Weighted efficiency	96.5%	96.5%	
General Information			
Air cooling	15.2 ft³/s	15.2 ft³/s	
Stand-by consumption <sup>(6)</sup>	30 W	30 W	
Consumption at night	1 W	1 W	
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	
Protection class	NEMA 3R	NEMA 3R	
Marking	C	E, ETL	
EMC and security standards	UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90.2		
Grid connection standards	IEC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CODE		

Notes: (1) Depending on the type of installation and geographical location (2) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (3) AC power for 122 °F (50 °C) ambient temperature. The output power will be reduced at the rate of 1% for each 1 °F (0.56 °C) of increase (4) For Powt>25% of the rated power (5) For Powt>25% of the rated power and voltage in accordance with IEEE 1547.1 (6) Consumption from PV field (7) Over 3,280 ft (1,000 m) temperature for rated power (122 °F / 50 °C) is reduced 2.42 °F each 1,000 ft.

#### Power U Outdoor







# INGECON SUN Power

#### **Transformerless**





# 125TL U 208 Outdoor / 165TL U 275 Outdoor / 200TL U 330 Outdoor / 220TL U 360 Outdoor

The best performance at medium and large outdoor installations

Designed for ease of maintenance, capable of withstanding extreme temperatures, and featuring full electric protections as a standard supply, the INGECON® SUN Power TL U Outdoor inverters are one of the latest Ingeteam's developments. They have been especially designed for medium and large outdoor installations.

#### Easy to install and maintain

The INGECON® SUN Power TL U Outdoor inverters have been manufactured with components which offer a useful life of more than 20 years. These inverters are equipped with an advanced maximum power point tracking system (MPPT) to obtain the maximum power from the PV array. No additional items

are required and they can be manually disconnected from the grid.

#### Software included

They include, without any extra cost, RS-485 communications as well as the software INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor Smartphone version for monitoring, displaying and recording the data from the inverter through the Internet. Each inverter incorporates an internal datalogger for up to 3 months data storage, which can be accessed from either a remote PC or on-site from the inverter front panel, through a keypad.


# Standard 5 year warranty, extendable for up to 20 years

#### PROTECTIONS

- Reverse polarity.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic disconnection.
- AC circuit breaker.
- DC switch.
- AC and DC surge arresters, type 2.
- Plus / minus grounding PV modules.

#### OPTIONAL ACCESSORIES


- Inter-inverter communication via Ethernet. For other communications, please check availability.
- DC fuses.
- Motorization of the AC breaker.
- Auxiliary services kit.
- Low voltage ride-through kit.
- -30 °C (-22 °F) operating kit.
- Night supply.
- INGECON® SUN String Control for PV array string current monitoring.
- Synchronization available with other inverters, to connect to the same MV transformer.




	125TL U 208 Outdoor	165TL U 275 Outdoor	200TL U 330 Outdoor	220TL U 360 Outdoor	
Input (DC)					
Recommended PV array power range(1)	128.5 - 167.1 kWp	168.6 - 219.2 kWp	203.9 - 265.1 kWp	223.9 - 291.1 kWp	
Voltage range MPP	330 - 820 V	440 - 820 V	525 - 820 V	570 - 820 V	
Maximum voltage(2)	1,000 V	1,000 V	1,000 V	1,000 V	
Maximum current	390 A	390 A	390 A	390 A	
Inputs	4	4	4	4	
MPPT	1	1	1	1	
Output (AC)					
Rated power <sup>(3)</sup>	125 kW	165 kW	200 kW	220 kW	
Maximum current	347 A	346 A	350 A	353 A	
Rated voltage	208 V IT System	275 V IT System	330 V IT System	360 V IT System	
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(4)</sup>	1	1	1	1	
Phi Cosine adjustable	Yes. Smax=125 kVA	Yes. Smax=165 kVA	Yes. Smax=200 kVA	Yes. Smax=220 kVA	
THD <sup>(5)</sup>	<3%	<3%	<3%	<3%	
Efficiency					
Maximum efficiency	98.4%	98.6%	98.7%	98.7%	
CEC	97.5%	98%	98.5%	98.5%	
General Information					
Air cooling	15.2 ft <sup>3</sup> /s	15.2 ft <sup>3</sup> /s	15.2 ft <sup>3</sup> /s	15.2 ft <sup>3</sup> /s	
Stand-by consumption <sup>(6)</sup>	30 W	30 W	30 W	30 W	
Consumption at night	1 W	1 W	1 W	1 W	
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)	9,842 ft (3,000 m)	9,842 ft (3,000 m)	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	
Protection class	NEMA 3R	NEMA 3R	NEMA 3R	NEMA 3R	
Marking		CE,	ETL		
EMC and security standards		UL1741, FCC Part 15, IEEE	E C37.90.1, IEEE C37.90.2		
Grid connection standards	IEC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CODE				

Notes: (1) Depending on the type of installation and geographical location (2) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (2) AC power for 122 °F (50 °C) ambient temperature. The output power will be reduced at the rate of 1% for each 1 °F (0.56 °C) of increase (4) For Pout>25% of the rated power (5) For Pout>25% of the rated power and voltage in accordance with IEEE 1547.1 (6) Consumption from PV field (7) Over 3,280 ft (1,000 m) temperature for rated power (122 °F / 50 °C) is reduced 2.42 °F each 1,000 ft.

#### Power TL U Outdoor



#### Size and weight (inches and lbs)



125TL U 208 Outdoor / 165TL U 275 Outdoor 200TL U 330 Outdoor / 220TL U 360 Outdoor

#### INGECON SUN PowerMax

#### Transformerless central inverters from 300 to 1164 kVA

The PV inverter family installed in the world's largest PV plants

The INGECON® SUN PowerMax central inverters are designed for multimegawatt plants with a direct connection to a medium voltage transformer. The economies of scale achieved with the development of installations of this type, make it possible to reduce and optimise the \$/Wp ratio.

#### **Enhanced performance**

The key strengths of the Ingeteam central inverters lie in their high maximum efficiency rating which can be as high as 99.1%.

Furthermore, the improved cooling system allows for a greater air flow through the inverter's most critical electronic

components, such as the IGBTs, ensuring that the rated power can be delivered up to an ambient temperature of 50 °C (122 °F).

#### **Grid support**

This family of central inverters performs grid support functions and complies with the grid connection requirements for countries throughout the world, contributing to the quality and stability of the electricity system.

The INGECON® SUN PowerMax family offers a low voltage ride-through capability, allowing for continuous operation through short periods of low grid voltage.

Working in combination with the INGE-CON® EMS Plant Controller, the inverters are able to control the active power delivered to the grid.

#### Model versatility

These central inverters can be supplied in a number of topologies, making them suitable for all kinds of projects. The inverters are available in three configurations: monoblock (B series), master-slave (X series) and multi-MPPT (M series).

Further options include indoor or outdoor models, and inverters with an integrated DC-AC cabinet or without the AC lines.



#### - B Series

Inverters with a single power block. This new inverter has been designed to be cost effective and to facilitate maintenance tasks.

Available in a range of power outputs from 830 to 1164 kVA.



#### X Series

Modular inverters with a masterslave configuration. The inverter has either two, three or four power blocks connected in parallel to the same PV array and to the same MV transformer.

Available in a wide range of power outputs from 300 to 1164 kVA.



#### - M Series

Modular inverters with a multi-MPPT configuration. The inverter can be supplied with either two, three or four independent power blocks, each with its own maximum power point tracking system (MPPT). It is possible to connect up to two 4-block inverters to the same medium voltage transformer winding.

Available from 300 to 1164 kVA.



#### INGECON SUN PowerMax

#### **B** Series



#### Transformerless central inverters with a single power block

# DC and AC supplies in the same cabinet

The input and output lines are integrated into the same cabinet, facilitating maintenance and repair work.

#### Maximum protection

These three phase inverters are equipped with a motorized DC switch to decouple the PV generator from the inverter. Optionally, these inverters can be supplied with an AC circuit breaker with door control, in addition to fuses, grounding kit and input current monitoring.

#### Maximum efficiency values

Through the use of innovative electronic conversion topologies, efficiency values of up to 99% can be achieved. Thanks to a sophisticated control algorithm, this equipment can guarantee maximum efficiency depending on the PV power available.

This maximizes the efficiency and service life of the equipment. In this way, in periods of low irradiance, it is able to increase performance by up to 1.8 points.

# A complete range of equipment for all types of projects

Versions available:

- Indoor inverters with integrated DCAC cabinet.
- Outdoor inverters with integrated DCAC cabinet.
- Symmetrical indoor inverters, with the connection cabinet on the opposite side, to make it possible to install two inverters facing each other, with a common power supply point.

#### **Enhanced functionality**

This new INGECON® SUN PowerMax range features a revamped, improved enclosure which, together with its innovative air cooling system, makes it possible to increase the ambient operating temperature to deliver its rated power up to 50 °C.

#### Long-lasting design

The inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to. Standard 5 year warranty, extendable for up to 25 years.

#### **Grid support**

The INGECON® SUN PowerMax B Series has been designed to comply with the grid connection requirements in different countries, contributing to the quality and stability of the electric system. These inverters therefore feature a low voltage ride-through capability, and can deliver reactive power and control the active power delivered to the grid.

#### Ease of maintenance

All the elements can be removed or replaced directly from the inverter's front side, thanks to its new design.

#### Easy to operate

The INGECON® SUN PowerMax inverters feature an LCD screen for the simple and convenient monitoring of the inverter status and a range of internal variables. The display also includes a number of LEDs to show the inverter operating status with warning lights to indicate any incidents. All this helps to simplify and facilitate maintenance tasks.

#### Monitoring and communication

Ethernet and RS-485 communications supplied as standard. The following applications are included at no extra cost: INGECON® SUN Manager, INGECON® SUN Monitor and its Smart-phone version iSun Monitor, available on the App Store. These applications are used for monitoring and recording the inverter's internal operating variables through the

Internet (alarms, real time production, etc.), in addition to the historical production data.

Two communication ports available (one for monitoring and one for plant controlling), allowing fast and simultaneous plant control.

#### PROTECTIONS

- DC Reverse polarity.
- Short-circuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Insulation failure DC.
- 15 pairs of fuse-holders.
- Lightning induced DC and AC surge arrestors, type 2.
- Motorized DC switch to automatically disconnect the inverter from the PV array.
- Low voltage ride-through capability.

#### OPTIONAL ACCESSORIES

- AC circuit breaker.
- Motorization kit for the AC circuit breaker.
- Insulation failure AC.
- Grounding kit.
- Heating kit, for operating at an ambient temperature of down to -30 °C.
- DC fuses
- Monitoring of the group currents at the DC input.
- Remote tripping of the AC protection.
- Wattmeter on the AC side.
- Lightning induced DC and AC surge arrestors, type 1.


#### ADVANTAGES OF THE MONOBLOCK VERSION

- Enhanced performance.
- Easier maintenance thanks to its new design and enclosure.
- Lightweight spares.
- It allows to ground the PV array.
- Components easily replaceable.


#### PowerMax B Series +15 +3 +2 -+1 -1 $\Box$ -2 Optional -3 -15 Optional

# Size and weight (mm) Indoor inverter 1,860 kg. Outdoor inverter 1,920 kg.

	830TL B300	1000TL B360	1070TL B385
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	845 - 1,081 kWp	1,013 - 1,297 kWp	1,084.3 - 1,387 kWp
Voltage Range MPP	440 - 820 V	524 - 820 V	560 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	2,000 A	2,000 A	2,000 A
N° inputs with fuse holders	15	15	15
Fuse dimensions		63 A / 1,000 V to 630 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Number of power blocks	1	1	1
MPPT	1	1	1
Max. current at each input		From 40 A to 410 A for positive and negative pole:	S
Inputs protection			
Overvoltage protections		Type 1-2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reverse	polarity / insulation failure monitoring / Anti-islanding	g protection
Output (AC)			
Power @30 °C / @50 °C(3)	831.4 kVA / 765 kVA	997.7 kVA / 918 kVA	1,066.9 kVA / 981.8 kVA
Current @30 °C / @50 °C	1,600 A / 1,472 A	1,600 A / 1,472 A	1,600 A / 1,472 A
Rated voltage	300 V IT System	360 V IT System	385 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=831.4 kVA	Yes. Smax=997.7 kVA	Yes. Smax=1,066.9 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 1-2 surge arresters	
AC breaker	Optiona	al AC circuit breaker with door control, remote trip or	motorized
Anti-islanding protection		Yes, with automatic disconnection	
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	98.8%	98.8%	98.8%
Euroefficiency	98.5%	98.5%	98.5%
Stand-by consumption <sup>(6)</sup>	90.5% 60 W	98.3% 60 W	98.3% 60 W
Consumption at night	60 W	60 W	60 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Air forced	d with temperature control (230 V phase + neutral po	ower supply)
Air flow	7,200 m <sup>3</sup> /h (fans: 2,500 VA)	7,200 m³/h (fans: 2,500 VA)	7,200 m³/h (fans: 2,500 VA)
Acoustic emission		<70 dB (A) at 1 m	
Marking		CE	
EMS and security standards		EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2.6), Chilean Grid Code, Ecuadorian Grid Code, Peruvian Grid code, Thailand PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid code, Jordan Grid Code		



	1110TL B400	1140TL B410	1165TL B420
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	1,124.2 - 1,441.1 kWp	1,151 - 1,476.8 kWp	1,179.3 - 1,513.2 kWp
Voltage Range MPP	580 - 820 V	595 - 820 V	610 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	2,000 A	2,000 A	2,000 A
N° inputs with fuse holders	15	15	15
- Fuse dimensions		63 A / 1,000 V to 630 A / 1,000 V fuses	
Type of connection		Connection to fuse-holder copper bars	
Number of power blocks	1	1	1
MPPT	1	1	1
Max. current at each input		From 40 A to 410 A for positive and negative pole	es
nputs protection			
Overvoltage protections		Type 1-2 surge arresters	
OC switch		Motorized DC switch	
Other protections	Reverse p	polarity, DC insulation monitor with alarm, emergence	y pushbutton
Output (AC)			
Power @30 °C / @50 °C(3)	1,108.5 kVA / 1,020 kVA	1,136.2 kVA / 1,045.5 kVA	1,163.9 kVA / 1,071 kVA
Current @30 °C / @50 °C	1,600 A / 1,472 A	1,600 A / 1,472 A	1,600 A / 1,472 A
Rated voltage	400 V IT System	410 V IT System	420 V IT System
requency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=1,108 kVA	Yes. Smax=1,136.2 kVA	Yes. Smax=1,163.9 kVA
THD (Total Harmonic Distortion)(5)	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 1-2 surge arresters	
AC breaker	Ontion	al AC circuit breaker with door control, remote trip or	r motorized
Anti-islanding protection	Option	Yes, with automatic disconnection	Milotofized
Other protections		AC short circuits and overloads	
		no short circuits and overloads	
Features			
Maximum efficiency	99%	99%	99%
uroefficiency	98.7%	98.7%	98.7%
Stand-by consumption <sup>(6)</sup>	60 W	60 W	60 W
Consumption at night	60 W	60 W	60 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Air force	d with temperature control (230 V phase + neutral p	ower supply)
hir flow	7,200 m³/h (fans: 2,500 VA)	7,200 m <sup>3</sup> /h (fans: 2,500 VA)	7,200 m³/h (fans: 2,500 VA)
Acoustic emission		<70 dB (A) at 1 m	
Marking		CE	
EMS and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4.	EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62	109-2, IEC62103, EN 50178, FCC Part 15. AS
Grid connection standards	IEC 62116, Arrêté 23-04-200 South African Grid code (ver 2.6), Chilean	8, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelsp n Grid Code, Ecuadorian Grid Code, Peruvian Grid c NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC Chi	pannungsrichtlinie:2011, P.O.12.3, ode, Thailand PEA requirements, IEC61727,



## INGECON SUN PowerMax

X Series
Indoor / Outdoor



#### Central inverters with a Master-Slave configuration and integrated DCAC cabinet

# DC and AC supplies in the same cabinet


The input and output lines are integrated into the same cabinet, facilitating maintenance and repair work.


# Available in indoor and outdoor versions

These Master-Slave central inverters feature an innovative ventilation system for the internal circulation of fresh air. Furthermore, the selection of casings makes these inverters suitable for indoor (IP20) and outdoor (IP54) installation.

#### **Maximum protection**

These three phase inverters are equipped with a motorized DC switch to decouple the PV generator from the inverter. Optionally, the inverters can be supplied with an AC circuit breaker with door control, in addition to fuses, grounding kit and input current monitoring.







#### Central inverters with a Master-Slave configuration and DC cabinet

#### Optimised space and investment


This model requires less space as the AC supply is not grouped together. This is a versatile solution, which is particularly advantageous for medium voltage transformer substations with two inverters and limited space. In this

way, investment is optimised by constructing enclosures housing a number of inverters.


#### Integrated protections

The Master-Slave INGECON® SUN PowerMax DC inverters are supplied

with DC fuse-holders as standard and, optionally, they can come with DC fuses and a grounding kit. In addition, they have a motorized DC switch to decouple the PV generator from the inverter.




	380TL X300	570TL X300	760TL X300
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	388.6 - 497.1 kWp	583 - 745.8 kWp	777.3 - 994.4 kWp
Voltage Range MPP	437 - 820 V	437 - 820 V	437 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1.050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions	<del>-</del>	63 A / 1,000 V to 630 A / 1,000 V	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
Max. current at each input	·	From 40 A to 410 A for positive and negative pol	
max. current at each input		110111 40 A to 410 A for positive and negative por	ics
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversibl	e polarity / insulation failure monitoring / Anti-island	ding protection
Outnut (AC)			
Output (AC)			
Power @30 °C / @45 °C(3)	415.7 kVA / 382.4 kVA	623.5 kVA / 573.7 kVA	831.4 kVA / 764.9 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	300 V IT System	300 V IT System	300 V IT System
requency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=415.7 kVA	Yes. Smax=623.5 kVA	Yes. Smax=831.4 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circu	uit breaker with door control, remote trip or motorize	ed (only DCAC models)
Anti-islanding protection		Yes, with automatic disconnection	
Other protections		AC short circuits and overloads	
Factures			
Features			
Maximum efficiency	98.9%	98.9%	98.9%
Euroefficiency	98.7%	98.7%	98.8%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Air force	d with temperature control (230 V phase + neutral	power supply)
Air flow	2,670 m <sup>3</sup> /h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		$<$ 67 dB (A) at 1 m with fans working at maximum $\mu$	oower
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4	, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62	2109-2, IEC62103, EN 50178, FCC Part 15, AS31
Grid connection standards	Chilean Grid Code, Romanian Grid Code, E	II, Terna A68, G59/2, BDEW-Mittelspannungsrichtlini icuadorian Grid Code, Peruvian Grid code, IEEE 929 NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC Chi	, Thailand MEA & PEA requirements, IEC61727




	400TL X320	605TL X320	800TL X320
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	413.7 - 530.3 kWp	620.6 - 795.5 kWp	827.5 - 1,060.7 kWp
Voltage Range MPP	468 - 820 V	468 - 820 V	468 - 820 V
Maximum voltage(2)	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions		63 A / 1,000 V to 630 A / 1,000 V	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
Max. current at each input	<u> </u>	From 40 A to 410 A for positive and negative pole:	s
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversible	polarity / insulation failure monitoring / Anti-islandin	ng protection
Output (AC)			
Power @30 °C / @45 °C(3)	443.4 kVA / 407.9 kVA	665.1 kVA / 611.9 kVA	886.8 kVA / 815.9 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	320 V IT System	320 V IT System	320 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=443.4 kVA	Yes. Smax=665.1 kVA	Yes. Smax=886.8 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circuit	breaker with door control, remote trip or motorized	(only DCAC models)
Anti-islanding protection		Yes, with automatic disconnection	
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	99%	99%	99%
Euroefficiency	98.8%	98.8%	98.9%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		with temperature control (230 V phase + neutral po	'
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		67 dB (A) at 1 m with fans working at maximum po	
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4.	EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	109-2, IEC62103, EN 50178, FCC Part 15. AS
Grid connection standards x	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III Chilean Grid Code, Romanian Grid Code, Ed	, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie: uadorian Grid Code, Peruvian Grid code, IEEE 929, IBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC Chin	:2011, P.O.12.3, South African Grid code (ve Thailand MEA & PEA requirements, IEC617


**Notes:**  $^{(1)}$  Depending on the type of installation and geographical location. Data for STC conditions  $^{(2)}$  Consider the voltage increase of the 'Voc' at low temperatures  $^{(3)}$  For each  $^{\circ}$ C of increase between 30  $^{\circ}$ C and 45  $^{\circ}$ C, the output power will be reduced at the rate of 0.4%. Over 45  $^{\circ}$ C, the output power will be reduced at the rate of 1.8% /  $^{\circ}$ C  $^{(4)}$ For  $P_{out}>25\%$  of the rated power  $^{(5)}$ For  $P_{out}>25\%$  of the rated power and voltage in accordance with IEC 61000-3-4  $^{(6)}$ C onsumption from PV field  $^{(7)}$ Over 1,000 m temperature for rated power is reduced at the rate of 4.5  $^{\circ}$ C for each 1,000 m.




	440TL X345	660TL X345	880TL X345
Input (DC)			
Recommended PV array power range(1)	445.8 - 571.7 kWp	668.7 - 857.6 kWp	891.6 - 1,143.5 kWp
Voltage Range MPP	502 - 820 V	502 - 820 V	502 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions	S	63 A / 1,000 V to 630 A / 1,000 V	12 (Oxtendable up to 10)
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
	1		
Max. current at each input		From 40 A to 410 A for positive and negative pole	es
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversibl	e polarity / insulation failure monitoring / Anti-island	ling protection
Output (AC)			
Power @30 °C / @45 °C(3)	478 kVA / 439.8 kVA	717.1 kVA / 659.7 kVA	956.1 kVA / 879.6 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	345 V IT System	345 V IT System	345 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=478 kVA	Yes. Smax=717.1 kVA	Yes. Smax=956.1 kVA
THD (Total Harmonic Distortion)(5)	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	· · · · · · · · · · · · · · · · · · ·		
Anti-islanding protection	Optional AC circuit breaker with door control, remote trip or motorized (only DCAC models)  Yes, with automatic disconnection		
Other protections		AC short circuits and overloads	
Other protections		AC SHORE CIrcuits and overloads	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.8%	98.9%	98.9%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		d with temperature control (230 V phase + neutral)	
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m <sup>3</sup> /h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		< 67 dB (A) at 1 m with fans working at maximum p	
Marking	g ,		
EMC and security standards	CE EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS310		
, , , , , , , , , , , , , , , , , , ,			
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2. Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IECG1727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		




	460TL X360	690TL X360	920TL X360
Input (DC)			
Recommended PV array power range(1)	464.7 - 596.6 kWp	697.1 - 894.9 kWp	928.9 - 1,193.1 kWp
/oltage Range MPP	524 - 820 V	524 - 820 V	524 - 820 V
Maximum voltage(2)	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
use dimensions		63 A / 1,000 V to 630 A / 1,000 V	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
Max. current at each input		From 40 A to 410 A for positive and negative poles	3
Input protections			
		Tuno 2 curro orrectore	
Overvoltage protections		Type 2 surge arresters	
DC switch	D	Yes, motorized DC switch	
Other protections	Reversible	e polarity / insulation failure monitoring / Anti-islandin	ng protection
Output (AC)			
Power @30 °C / @45 °C(3)	498.8 kVA / 458.9 kVA	748.2 kVA / 688.4 kVA	997.7 kVA / 917.8 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	360 V IT System	360 V IT System	360 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=498.8 kVA	Yes. Smax=748.2 kVA	Yes. Smax=997.7 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Ontional AC circuit	t breaker with door control, remote trip or motorized	(anly DCAC modals)
Anti-islanding protection	Optional Activeus	Yes, with automatic disconnection	(Unity DEAC Hodels)
Other protections		AC short circuits and overloads	
Other protections		AC SHORE CIrcuits and overloads	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.8%	98.9%	99%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		with temperature control (230 V phase + neutral po	
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		: 67 dB (A) at 1 m with fans working at maximum po	
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4,	EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	09-2, IEC62103, EN 50178, FCC Part 15, AS
Grid connection standards	IEC 62116, Arreté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid Code, Ver 2 Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727 UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		



	500TL X400	750TL X400	1000TL X400
Input (DC)			
Recommended PV array power range(1)	515.8 - 662.9 kWp	773.7 - 994.4 kWp	1,031.6 - 1,325.7 kWp
/oltage Range MPP	578 - 820 V	578 - 820 V	578 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
use dimensions	0	63 A / 1,000 V to 630 A / 1,000 V	12 (externable up to 10)
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
Max. current at each input	<u> </u>	From 40 A to 410 A for positive and negative poles	
wax. current at each input		Trom 40 A to 410 A for positive and negative poles	•
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversible	polarity / insulation failure monitoring / Anti-islandin	ng protection
Output (AC)			
Power @30 °C / @45 °C(3)	EE 4 2 IAVA / EOO O IAVA	831.4 kVA / 764.9 kVA	1 100 5 14/4 / 1 010 9 14/4
	554.3 kVA / 509.9 kVA		1,108.5 kVA / 1,019.8 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	400 V IT System	400 V IT System	400 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=554.3 kVA	Yes. Smax=831.4 kVA	Yes. Smax=1,108.5 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circui	t breaker with door control, remote trip or motorized	(only DCAC models)
Anti-islanding protection		Yes, with automatic disconnection	
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.8%	98.9%	99%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
	00.00 to .05.00	20.00 to 1.05.00	00.00 +05.00
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		with temperature control (230 V phase + neutral po	
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission	< 67 dB (A) at 1 m with fans working at maximum power		
Marking	EN 61000 6.1 EN 61000 6.2 EN 61000 6.4	CE EN 61000 3 11 EN 61000 3 12 EN 62100 1 EN 621	00 2 IEC62103 EN 50170 FOO Doct 15 AC
EMC and security standards		EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC617: UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan G		



	535TL X420	805TL X420	1070TL X420
Input (DC)			
Recommended PV array power range(1)	541.1 - 696 kWp	811.7 - 1,044 kWp	1,082.3 - 1,392 kWp
/oltage Range MPP	607 - 820 V	607 - 820 V	607 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
use dimensions		63 A / 1,000 V to 630 A / 1,000 V	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT	1	1	1
Max. current at each input	<u> </u>	From 40 A to 410 A for positive and negative poles	
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
	December	,	
Other protections	Reversible	polarity / insulation failure monitoring / Anti-islandin	ig protection
Output (AC)			
Power @30 °C / @45 °C(3)	582 kVA / 535.4 kVA	873 kVA / 803.1 kVA	1,163.9 kVA / 1,070.8 kVA
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	420 V IT System	420 V IT System	420 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=582 kVA	Yes. Smax=873 kVA	Yes. Smax=1,163.9 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Ontional AC circui	t breaker with door control, remote trip or motorized	(only DCAC models)
Anti-islanding protection	optional ric office.	Yes, with automatic disconnection	(city Device models)
Other protections		AC short circuits and overloads	
		, to one telledite and evenedab	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.8%	98.9%	98.9%
Stand-by consumption <sup>(6)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(7)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Air forced	with temperature control (230 V phase + neutral po	wer supply)
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission	<	67 dB (A) at 1 m with fans working at maximum por	wer
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4,	EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 6210	09-2, IEC62103, EN 50178, FCC Part 15, AS
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2 Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727 UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		



### INGECON SUN PowerMax

M Series
Indoor / Outdoor



#### Central multi-MPPT inverters with an integrated DCAC CABINET

# DC and AC supplies in the same cabinet

The input and output lines are integrated into the same cabinet, facilitating maintenance and repair work, whilst still maintaining the highest level of safety.


# Available in indoor and outdoor versions


These multi-string central inverters can be supplied with either an indoor (IP20) or outdoor (IP54) casing.

#### **Maximum protection**

These three phase inverters are equip-

ped with a manual DC switch and a DC automatic contactor for each power block, in order to decouple the PV generator from the inverter. Optionally, the inverters can be supplied with an AC circuit breaker with door control, in addition to fuses and current monitoring.







#### Central multi-MPPT inverters with a DC CABINET

#### Optimised space and investment


This model requires less space as the AC supply is not grouped together. This is a versatile solution, which is particularly advantageous for medium voltage transformer substations with two inverters and limited space. In this

way, investment is optimised by constructing enclosures housing a number of inverters.

#### Integrated protections

The INGECON® SUN PowerMax DC multi-string inverters are supplied with

manual DC switch and an automatic DC contactor for each power block, in order to decouple the PV generator from the inverter.




	380TL M300	570TL M300	760TL M300
Input (DC)			
Recommended PV array power range(1)	388.6 - 197.1 kWp	583 - 745.8 kWp	777.3 - 994.4 kWp
Voltage Range MPP	437 - 820 V	437 - 820 V	437 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	6
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversib	le polarity / insulation failure monitoring / Anti-islandin	ng protection
	Reversib	is polarity / modulator randre monitoring / / mit islandin	is protection
Output (AC)			
Power @30 °C / @45 °C(5)	415.7 kW / 382.4 kW	623.5 kW / 573.7 kW	831.4 kW / 764.9 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	300 V IT System	300 V IT System	300 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=415.7 kVA	Yes. Smax=623.5 kVA	Yes. Smax=831.4 kVA
THD (Total Harmonic Distortion) <sup>(7)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circuit breaker with door control, motorized or remote trip (only DCAC models)		
Anti-islanding protection		Yes, with automatic disconnection (for each power sta	age)
Other protections	AC short circuits and overloads		
Features			
Maximum efficiency	98.9%	98.9%	98.9%
Euroefficiency	98.5%	98.5%	98.5%
Stand-by consumption <sup>(8)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
		ed with temperature control (230 V phase + neutral po	
Cooling system  Air flow	2,670 m <sup>3</sup> /h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		< 67 dB (A) at 1 m with fans working at maximum po	
Marking		CE	WO.
EMC and security standards	EN 61000-6-1 EN 61000 6 2 EN 61000 6 4	GE I, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	09-2 JEC62103 EN 50179 ECC Part 15 AS210
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2.6 Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		

**Notes:**  $^{(1)}$  Depending on the type of installation and geographical location. Data for STC conditions  $^{(2)}$  Consider the voltage increase of the 'Voc' at low temperatures  $^{(3)}$  For other configurations, consult with Ingeteam  $^{(4)}$  The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration  $^{(3)}$  For each  $^{\circ}$ C of increase between 30  $^{\circ}$ C and 45  $^{\circ}$ C, the output power will be reduced at the rate of 0.4%. Over 45  $^{\circ}$ C, the output power will be reduced at the rate of 1.8%  $^{\circ}$ C  $^{(6)}$  For  $P_{out}>25\%$  of the rated power and voltage in accordance with IEC 61000-3-4  $^{(6)}$ C Consumption from PV field  $^{(9)}$ O Ver 1,000 m temperature for rated power is reduced at the rate of 4.5  $^{\circ}$ C for each 1,000 m.




	400TL M320	605TL M320	800TL M320
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	413.7 - 530.3 kWp	620.6- 795.5 kWp	827.5 - 1,060.7 kWp
Voltage Range MPP	468 - 820 V	468 - 820 V	468 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
use dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	5
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversible	polarity / insulation failure monitoring / Anti-islandin	ng protection
		polarity / modulation rainare monitoring / / with localitation	,s procession
Output (AC)		227 4 1111 124 2 1111	
Power @30 °C / @45 °C <sup>(5)</sup>	443.4 kW / 407.9 kW	665.1 kW / 611.9 kW	886.8 kW / 815.9 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	320 V IT System	320 V IT System	320 V IT System
requency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=443.4 kVA	Yes. Smax=665.1 kVA	Yes. Smax=886.8 kVA
THD (Total Harmonic Distortion) <sup>(7)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections	Type 2 surge arresters		
AC breaker	Optional AC circuit breaker with door control, motorized or remote trip (only DCAC models)		
Anti-islanding protection	Ye	es, with automatic disconnection (for each power sta	age)
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	99%	99%	99%
Euroefficiency	98.6%	98.6%	98.6%
Stand-by consumption(8)	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
	55	50	120
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Air forced	with temperature control (230 V phase + neutral po	wer supply)
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m <sup>3</sup> /h (fans: 1,300 VA)	5,340 m <sup>3</sup> /h (fans: 1,500 VA)
Acoustic emission	<	$67~\mathrm{dB}$ (A) at $1~\mathrm{m}$ with fans working at maximum po	wer
Marking		CE	
EMC and security standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-4,	EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	09-2, IEC62103, EN 50178, FCC Part 15, AS31
Grid connection standards	IEC 62116, Arrèté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2 Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727 UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		

Notes: <sup>(1)</sup> Depending on the type of installation and geographical location. Data for STC conditions <sup>(2)</sup> Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> For other configurations, consult with Ingeleam <sup>(4)</sup> The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration <sup>(3)</sup> For each °C of increase between 30 °C and 45 °C, the output power will be reduced at the rate of 0.4%. Over 45 °C, the output power will be reduced at the rate of 1.8% / °C <sup>(6)</sup> For Pout>25% of the rated power <sup>(7)</sup> For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(8)</sup> Consumption from PV field <sup>(9)</sup> Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.



	440TL M345	660TL M345	880TL M345
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	445.8 - 571.7 kWp	668.7 - 857.6 kWp	891.6 - 1,143.5 kWp
Voltage Range MPP	502 - 820 V	502 - 820 V	502 - 820 V
Maximum voltage(2)	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversib	le polarity / insulation failure monitoring / Anti-islandin	g protection
	Keversib	o polarity / modulator randre mornioring / / with islanding	g protection
Output (AC)			
Power @30 °C / @45 °C(5)	478 kW / 439.8 kW	717.1 kW / 659.7 kW	956.1 kW / 879.6 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	345 V IT System	345 V IT System	345 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=478 kVA	Yes. Smax=717.1 kVA	Yes. Smax=956.1 kVA
THD (Total Harmonic Distortion) <sup>(7)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circuit breaker with door control, motorized or remote trip (only DCAC models)		
Anti-islanding protection		Yes, with automatic disconnection (for each power sta	ge)
Other protections	AC short circuits and overloads		
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.7%	98.7%	98.7%
Stand-by consumption <sup>(8)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
	30 11	30 !!	120 11
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		d with temperature control (230 V phase + neutral po	11.3
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		< 67 dB (A) at 1 m with fans working at maximum pov	wer
Marking		CE	
EMC and security standards		, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 6210	
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2.6 Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		

Notes: <sup>(1)</sup> Depending on the type of installation and geographical location. Data for STC conditions <sup>(2)</sup> Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> For other configurations, consult with Ingeleam <sup>(4)</sup> The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration <sup>(3)</sup> For each °C of increase between 30 °C and 45 °C, the output power will be reduced at the rate of 0.4%. Over 45 °C, the output power will be reduced at the rate of 1.8% / °C <sup>(4)</sup> For Pout>25% of the rated power <sup>(7)</sup> For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(6)</sup> Consumption from PV field <sup>(6)</sup> Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.




	460TL M360	690TL M360	920TL M360
Input (DC)			
Recommended PV array power range(1)	464.7 - 596.6 kWp	697.1 - 894.9 kWp	929.4 - 1,193.1 kWp
/oltage Range MPP	524 - 820 V	524 - 820 V	524 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
use dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	, , ,
ype of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	
Input protections			
Overvoltage protections		Type 2 surge arresters	
OC switch		Yes, motorized DC switch	
Other protections	Reversible	e polarity / insulation failure monitoring / Anti-islanding	protection
	1/CVCI SIDIC	, polarity i modulatori randre monitoring i zinti Islanumg	S procession
Output (AC)			
Power @30 °C / @45 °C <sup>(5)</sup>	498.8 kW / 458.9 kW	748.2 kW / 688.4 kW	997.7 kW / 917.8 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	360 V IT System	360 V IT System	360 V IT System
requency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=498.8 kVA	Yes. Smax=748.2 kVA	Yes. Smax=997.7 kVA
THD (Total Harmonic Distortion) <sup>(7)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections	Type 2 surge arresters		
AC breaker	Optional AC circuit breaker with door control, motorized or remote trip (only DCAC models)		
Anti-islanding protection	Y	es, with automatic disconnection (for each power stage	ge)
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.7%	98.7%	98.7%
Stand-by consumption(8)	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
General Information			
	00.00 to	00.00 +05.00	20.00 to CE 00
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		I with temperature control (230 V phase + neutral pov	
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission	<	: 67 dB (A) at 1 m with fans working at maximum pow	/er
Marking	EN (1000 C.1 EN (1000 C.2 EN (1000 C.2	CE	0.0 15000100 51150170 500 5 145
EMC and security standards		EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 6210	
Grid connection standards	Chilean Grid Code, Romanian Grid Code, Ed	I, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2 cuadorian Grid Code, Peruvian Grid code, IEEE 929, Th NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China,	nailand MEA & PEA requirements, IEC6172

Notes: <sup>(1)</sup> Depending on the type of installation and geographical location. Data for STC conditions <sup>(2)</sup> Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> For other configurations, consult with Ingeleam <sup>(4)</sup> The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration <sup>(3)</sup> For each °C of increase between 30 °C and 45 °C, the output power will be reduced at the rate of 0.4%. Over 45 °C, the output power will be reduced at the rate of 1.8% / °C <sup>(6)</sup> For Pout>25% of the rated power <sup>(7)</sup> For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(8)</sup> Consumption from PV field <sup>(9)</sup> Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.




	500TL M400	750TL M400	1000TL M400
Input (DC)			
Recommended PV array power range(1)	515.8 - 662.9 kWp	773.7 - 994.4 kWp	1,031.6 - 1,325.7 kWp
Voltage Range MPP	578 - 820 V	578 - 820 V	578 - 820 V
Maximum voltage(2)	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	6
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Povorcible	e polarity / insulation failure monitoring / Anti-islandir	ag protection
	I/Cvel sibil	e polarity / insulation failure monitoring / Anti-islandii	ig protection
Output (AC)			
Power @30 °C / @45 °C(5)	554.3 kW / 509.9 kW	554.3 kW / 509.9 kW	1,108.5 kW / 1,019.8 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	400 V IT System	400 V IT System	400 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=554.3 kVA	Yes. Smax=554.3kVA	Yes. Smax=1,108.5 kVA
THD (Total Harmonic Distortion)(7)	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circuit breaker with door control, motorized or remote trip (only DCAC models)		
Anti-islanding protection	Y	es, with automatic disconnection (for each power sta	age)
Other protections	AC short circuits and overloads		
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.7%	98.7%	98.7%
Stand-by consumption <sup>(8)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
	55 <b></b>	30 11	120 11
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		d with temperature control (230 V phase + neutral po	ower supply)
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m <sup>3</sup> /h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		< 67 dB (A) at 1 m with fans working at maximum po	wer
Marking		CE	
EMC and security standards		EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	
Grid connection standards	IEC 62116, Arrêté 23-04-2008, CEI 0-16 Ed. III, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie:2011, P.O.12.3, South African Grid code (ver 2.6) Chilean Grid Code, Romanian Grid Code, Ecuadorian Grid Code, Peruvian Grid code, IEEE 929, Thailand MEA & PEA requirements, IEC61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China, DEWA (Dubai) Grid Code, Jordan Grid Code		

Notes: <sup>(1)</sup> Depending on the type of installation and geographical location. Data for STC conditions <sup>(2)</sup> Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> For other configurations, consult with Ingeleam <sup>(4)</sup> The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration <sup>(3)</sup> For each °C of increase between 30 °C and 45 °C, the output power will be reduced at the rate of 0.4%. Over 45 °C, the output power will be reduced at the rate of 1.8% / °C <sup>(4)</sup> For Pout>25% of the rated power <sup>(7)</sup> For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(6)</sup> Consumption from PV field <sup>(6)</sup> Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.



	535TL M420	805TL M420	1070TL M420
Input (DC)			
Recommended PV array power range(1)	541.1 - 696 kWp	811.7 - 1,044 kWp	1,028.3 - 1,392 kWp
Voltage Range MPP	607 - 820 V	607 - 820 V	607 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V	1,050 V	1,050 V
Maximum current	900 A	1,350 A	1,800 A
N° inputs with fuse holders	8	12 (extendable up to 16)	12 (extendable up to 16)
Fuse dimensions <sup>(3)</sup>		63 A / 1,000 V to 400 A / 1,000 V fuses	
Type of connection		Connection to copper bars	
Power blocks	2	3	4
MPPT <sup>(4)</sup>	2	3	4
Max. current at each input		From 40 A to 260 A for positive and negative poles	6
Input protections			
Overvoltage protections		Type 2 surge arresters	
DC switch		Yes, motorized DC switch	
Other protections	Reversibl	e polarity / insulation failure monitoring / Anti-islandin	ng protection
	Reversion	e polarity / modulion famore monitoring / / mil folaridin	is protection
Output (AC)			
Power @30 °C / @45 °C(5)	582 kW / 535.4 kW	582 kW / 803.1 kW	1,163.9 kW / 1,070.8 kW
Current @30 °C / @45 °C	800 A / 736 A	1,200 A / 1,104 A	1,600 A / 1,472 A
Rated voltage	420 V IT System	420 V IT System	420 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(6)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=582 kVA	Yes. Smax=582 kVA	Yes. Smax=1,163.9 kVA
THD (Total Harmonic Distortion) <sup>(7)</sup>	<3%	<3%	<3%
Output protections			
Overvoltage protections		Type 2 surge arresters	
AC breaker	Optional AC circu	uit breaker with door control, motorized or remote trip	(only DCAC models)
Anti-islanding protection	,	Yes, with automatic disconnection (for each power sta	age)
Other protections		AC short circuits and overloads	
Features			
Maximum efficiency	99.1%	99.1%	99.1%
Euroefficiency	98.6%	98.6%	98.6%
Stand-by consumption <sup>(8)</sup>	60 W	90 W	120 W
Consumption at night	60 W	90 W	120 W
	55	55	220 11
General Information	2000	2000 2500	00.00
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(9)</sup>	3,000 m	3,000 m	3,000 m
Cooling system		d with temperature control (230 V phase + neutral po	
Air flow	2,670 m³/h (fans: 1,000 VA)	4,640 m³/h (fans: 1,300 VA)	5,340 m³/h (fans: 1,500 VA)
Acoustic emission		< 67 dB (A) at 1 m with fans working at maximum por	wer
Marking		CE	
EMC and security standards		, EN 61000-3-11, EN 61000-3-12, EN 62109-1, EN 621	
Grid connection standards	Chilean Grid Code, Romanian Grid Code, E	II, Terna A68, G59/2, BDEW-Mittelspannungsrichtlinie: icuadorian Grid Code, Peruvian Grid code, IEEE 929, 1 NBR 16150, IEEE 1547, IEEE1547.1, GGC&CGC China	Thailand MEA & PEA requirements, IEC61727,

Notes: <sup>(1)</sup> Depending on the type of installation and geographical location. Data for STC conditions <sup>(2)</sup> Consider the voltage increase of the 'Voc' at low temperatures <sup>(3)</sup> For other configurations, consult with Ingeleam <sup>(4)</sup> The MPPT connected to the same transformer throught TL inverters must have the same voltage configuration <sup>(3)</sup> For each °C of increase between 30 °C and 45 °C, the output power will be reduced at the rate of 0.4%. Over 45 °C, the output power will be reduced at the rate of 1.8% / °C <sup>(6)</sup> For Pout>25% of the rated power <sup>(7)</sup> For Pout>25% of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(8)</sup> Consumption from PV field <sup>(9)</sup> Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.







## Transformerless central inverters with a Master-Slave configuration

The central inverter with a Master-Slave configuration, in any of its versions, is equipped with three to four power blocks, connected in parallel to the same PV generator and to the same medium voltage transformer

# DC and AC supplies in the same cabinet

The input and output lines are integrated into the same cabinet, facilitating maintenance and repair work.

#### Maximum efficiency values

Through the use of innovative electronic conversion topologies, efficiency values up to 98.6% can be easily achieved. Thanks to a sophisticated control algorithm, this equipment can guarantee maximum efficiency through the selective operation of its power blocks, based on the PV power available. This maximizes the efficiency and service life of the equipment. In this way, in periods of low irradiance, it is able to increase performance by up to 1.8 points.

#### **Enhanced functionality**

This new INGECON® SUN PowerMax U inverter range features a revamped, improved enclosure which, together with its innovative air cooling system, makes it possible to increase the ambient operating temperature to deliver its rated power up to 122 °F (50 °C).

# A complete range of equipment for all types of projects

The PowerMax U inverters are fully adaptable to all types of engineering projects. This is made possible thanks to their wide range of power outputs and to the variety of possible configurations.

#### Maximum protection

These three-phase inverters are equipped with a motorized DC switch to decouple the PV generator from the inverter. Optionally, the PowerMax U inverters can be supplied with DC fuses. Optional positive or negative grounding, or nongrounded.

#### Long-lasting design

The inverters have been designed to guarantee a service life of more than 20 years, as demonstrated by the stress tests they are subjected to. Standard 5 year warranty, extendable for up to 20 years.

#### **Grid support**

The INGECON® SUN PowerMax U family has been designed to comply with the grid connection requirements in different countries, contributing to the quality and stability of the electric system. These inverters therefore can deliver reactive power and control the active power delivered to the grid.

#### Ease of maintenance

Easily replaceable modular power blocks for shorter maintenance times.

#### Easy to operate

The INGECON® SUN PowerMax U inverters feature an LCD screen for the simple and convenient monitoring of the inverter status and a range of internal variables. The display also includes a number of LEDs to show the inverter operating status with warning lights to indicate any incident. All this helps to simplify and facilitate maintenance tasks.

#### Monitoring and communication

RS-485 communications supplied as standard for monitoring the internal operating variables (alarms, real time production, etc.) in addition to the historical production data. Ethernet, GSM / GPRS and Bluetooth are also available. The following applications are included at no extra cost: INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor Smartphone version for monitoring and recording the inverter data over the Internet



#### PROTECTIONS


- DC reverse polarity.
- Short-circuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Insulation failure.
- 4 DC fuse-holders per power block. Non-grounded inverters have both poles protected.
- DC and AC surge arresters, type 2.
- Motorized DC switch for the automatic disconnection of the inverter from the PV array.
- AC fuses.

#### OPTIONAL ACCESSORIES

- GSM / GPRS remote communication.
- Inter-inverter communication via Ethernet or Bluetooth.
- Kit for operating at an ambient temperature of -22  $^{\circ}\text{F}$  (-30  $^{\circ}\text{C}).$
- DC fuses.
- Monitoring of the input DC currents.
- Wattmeter on the AC side.
- Low voltage ride-through kit.
- Auxiliary services kit.
- AC breaker.


#### ADVANTAGES OF THE MASTER-SLAVE VERSION

- Enhanced performance.
- In the event of the failure of one of the blocks, the power is then distributed amongst the remaining blocks.
- Lightweight spares, for shorter delivery times
- It allows to ground the PV array, either the positive or the negative pole.



# Size and weight (inches and lbs) 660TL U X360 Outdoor 4,520 lbs 880TL U X360 Outdoor 5,950 lbs


	375TL U X208 Outdoor	500TL U X208 Outdoor	
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	382.1 - 502.1 kWp	509.5 - 669.5 kWp	
Voltage Range MPP	311 - 820 V	350 - 820 V	
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V	
Maximum current	1,170 A	1,560 A	
N° inputs with fuse holders	12 (24 for floating configuration)	16 (32 for floating configuration)	
Fuse dimensions	125 A / 1,000 V to 400 A / 1,000 V fuses, maximum curr	rent from 82 to 260 A for positive and negative poles	
Type of connection	Connection to copper bars		
Power blocks	3	4	
MPPT	1	1	
Current at each input	82 to 260 A	82 to 260 A	
Input protections			
Overvoltage protections	DC surge arrest	ters, type 2	
DC switch	Motorized DC		
Other protections	DC insulation monitor with alarm. Optionally, from 8 to 16 pa	irs of DC fuses (16 to 32 pairs for floating configuration)	
Output (AC)			
Rated power <sup>(3)</sup>	375 kW	500 kW	
Maximum current	1,050 A	1,400 A	
Rated voltage	208 V IT System	208 V IT System	
Frequency	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(4)</sup>	1	1	
Phi Cosine adjustable	Yes. Smax=375 kVA	Yes. Smax=500 kVA	
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	
Output protections			
Overvoltage protections	AC surge arrest	ters, type 2	
AC breaker	Yes		
Anti-islanding protection	Yes, with automatic disconnect	tion (for each power stage)	
Other protections	AC fuses, AC short circuits and ove		
Features			
Maximum efficiency	98.1%	98.1%	
CEC	97.5%	97.5%	
Stand-by consumption <sup>(6)</sup>	90 W	120 W	
Consumption at night	90 W	120 W	
General Information			
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	
Protection class	NEMA 3R	NEMA 3R	
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)	
Cooling system	Air forced with temperature control (23		
Air flow	37.96 ft <sup>3</sup> /s (fans: 1,300 VA)	45.56 ft³/s (fans:1,500 VA)	
Acoustic emission	< 55 dB (A) at 4 m and < 67 dB (A) at 1 m		
Marking	CE, ETL		
Marking  EMC and security standards	UL1741, FCC Part 15, IEEE C		




	500TL U X275 Outdoor	660TL U X275 Outdoor	
Input (DC)			
Recommended PV array power range(1)	508.4 - 669.5 kWp	671.1 - 897.1 kWp	
Voltage Range MPP	403 - 820 V	403 - 820 V	
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V	
Maximum current	1,170 A	1,560 A	
N° inputs with fuse holders	12 (24 for floating configuration)	16 (32 for floating configuration)	
Fuse dimensions	125 A / 1,000 V to 400 A / 1,000 V fuses, maximum cu	rrent from 82 to 260 A for positive and negative poles	
Type of connection	Connection to	copper bars	
Power blocks	3	4	
MPPT	1	1	
Current at each input	82 to 260 A	82 to 260 A	
Input protections			
Overvoltage protections	DC surge arres	sters, type 2	
DC switch	Motorized D	DC switch	
Other protections	DC insulation monitor with alarm. Optionally, from 8 to 16 p	pairs of DC fuses (16 to 32 pairs for floating configuration)	
Output (AC)			
Rated power <sup>(3)</sup>	500 kVA	660 kVA	
Maximum current	1,050 A	1,400 A	
Rated voltage	275 V IT System	275 V IT System	
Frequency	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(4)</sup>	1	1	
Phi Cosine adjustable	Yes. Smax=500 kVA	Yes. Smax=500 kVA	
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	
Output protections			
Overvoltage protections	AC surge arres	sters, type 2	
AC breaker	Yes	s	
Anti-islanding protection	Yes, with automatic disconnection	ction (for each power stage)	
Other protections	AC fuses, AC short circuits and or	verloads (for each power stage)	
Features			
Maximum efficiency	98.3%	98.3%	
CEC	98%	98%	
Stand-by consumption <sup>(6)</sup>	90 W	120 W	
Consumption at night	90 W	120 W	
General Information			
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	
Protection class	NEMA 3R	NEMA 3R	
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)	
Cooling system	Air forced with temperature control (2.	30 V phase + neutral power supply)	
Air flow	37.96 ft³/s (fans: 1,300 VA)	45.56 ft³/s (fans:1,500 VA)	
Acoustic emission	< 55 dB (A) at 4 m and < 67 dB (A) at 1 r	m with fans working at maximum power	
Marking	CE, E		
EMC and security standards	UL1741, FCC Part 15, IEEE		
Grid connection standards			
	IEC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CODE		




Voltage Range MPP 484 - 820 V  Maximum voltage <sup>®</sup> 1,000 V  Maximum current 1,170 A  N° inputs with fuse holders 12 (24 for floating configuration) 16 (32 for floating configuration) 15 (32 for floating configuration) 16 (32 for floating configuration) 17 (32 for floating configuration) 18 (33 f	4 1 82 to 260 A
Voltage Range MPP         484 - 820 V           Maximum vortage™         1,000 V           Maximum current         1,170 A           Nº inputs with fuse holders         12 (24 for floating configuration)         16 (32 ft fise dimensions)           Type of connection         Connection to corper bars           Type of Docks         3           MPPT         1           Current at each input         82 to 260 A           Input protections           Overvoltage protections         DC surge arresters, type 2           Octing protections         DC surge arresters, type 2           Output (AC)         Motorized DC switch           Other protections         DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p. optional protections)           Output (AC)         Output (AC)           Rated power®         600 kVA           Maximum current         1,050 A           Rated voltage         330 V IT System           Frequency         50 / 60 Hz           Phi Cosine adjustable         Yes. Smax=600 kVA           THD (Total Harmonic Distortion)®         <3%           Output protections         AC surge arresters, type 2           AC breaker         Yes           AC breaker         Yes	1,000 V 1,560 A or floating configuration) ositive and negative poles  4 1 82 to 260 A  airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Maximum voltage <sup>(2)</sup> Maximum current 1,170 A N° inputs with fuse holders 12 (24 for floating configuration) 16 (32 for floating configuration) 16 (32 for floating configuration) 16 (32 for floating configuration) 17 yee of connection 17 yee of connection 18 yee of connection to copper bars 19 yee of connection to copper bars 10 yeer of locks 3	1,000 V 1,560 A or floating configuration) ositive and negative poles  4 1 82 to 260 A  airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Maximum current  1,170 A  Nº inputs with fuse holders  12 (24 for floating configuration)  16 (32 fector)  Fuse dimensions  125 A / 1,000 V to 400 A / 1,000 V fuses, maximum current from 82 to 260 A for proper blocks  3  MPPT  1  Current at each input  Input protections  Overvoltage protections  DC surge arresters, type 2  DC switch  Motorized DC switch  Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p. 00 for p.	1,560 A for floating configuration) ositive and negative poles  4 1 82 to 260 A  airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
N° inputs with fuse holders         12 (24 for floating configuration)         16 (32 ft Fuse dimensions)           Type of connection         Connection to copper bars           Power blocks         3           MPPT         1           Current at each input         82 to 260 A           Input protections           Overvoltage protections         DC surge arresters, type 2           Dc switch         Motorized DC switch           Other protections         DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p.	or floating configuration) ositive and negative poles  4 1 82 to 260 A  airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Fuse dimensions         125 A / 1,000 V to 400 A / 1,000 V fuses, maximum current from 82 to 260 A for proper forms.           Type of connection         Connection to copper bars.           Power blocks         3           MPPT         1           Current at each input         82 to 260 A           Input protections         DC surge arresters, type 2           Oevroltage protections         DC surge arresters, type 2           DC switch         Motorized DC switch           Other protections         DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 pm.)           Output (AC)         Stated power <sup>50</sup> Rated power <sup>50</sup> 600 kVA           Maximum current         1,050 A           Rated voltage         330 V IT System           Frequency         50 / 60 Hz           Phi Cosine adjustable         Yes. Smax=600 kVA         Yes.           THD (Total Harmonic Distortion) <sup>(50)</sup> <3%	airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Type of connection to copper bars  Power blocks 3  MPPT 1  Current at each input 82 to 260 A  Input protections  Overvoltage protections  DC surge arresters, type 2  DC switch Motorized DC switch  Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p. d.	4 1 82 to 260 A  airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Power blocks 3 MPPT 1 Current at each input 82 to 260 A  Input protections  Overvoltage protections  DC surge arresters, type 2  DC switch Motorized DC switch Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p. 00	1 82 to 260 A airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
MPPT 1 1 82 to 260 A  Input protections  Overvoltage protections  DC surge arresters, type 2  DC switch Motorized DC switch Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p. 00 p. 0	1 82 to 260 A airs for floating configuration)  800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Input protections  Overvoltage protections  DC surge arresters, type 2  DC switch  Motorized DC switch  Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p.)  Output (AC)  Rated power <sup>co</sup> 600 kVA  Maximum current  1,050 A  Rated voltage  330 V IT System  Frequency  50 / 60 Hz  Phi Cosine <sup>co</sup> 1  Phi Cosine adjustable  Yes. Smax=600 kVA  AC surge arresters, type 2  AC breaker  Yes  Anti-islanding protection  AC fuses, AC short circuits and overloads (for each power stage)  Other protections  Maximum efficiency  98.5%  CEC  98%	82 to 260 A  airs for floating configuration)  800 kVA  1,400 A  330 V IT System  50 / 60 Hz
Input protections Overvoltage protections OC switch OC S	airs for floating configuration)  800 kVA  1,400 A  330 V IT System  50 / 60 Hz
DC surge arresters, type 2  DC switch  Motorized DC switch  Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p.  Output (AC)  Rated power <sup>(3)</sup> 600 kVA  Maximum current  1,050 A  Rated voltage  330 V IT System  Frequency  50 / 60 Hz  Phi Cosine <sup>(6)</sup> 1  Phi Cosine adjustable  Yes. Smax=600 kVA  Yes  Output protections  Overvoltage protections  AC surge arresters, type 2  AC breaker  Yes  Anti-islanding protection  Yes, with automatic disconnection (for each power stage)  Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency  98.5%  CEC  98%	800 kVA 1,400 A 330 V IT System 50 / 60 Hz
DC switch Other protections DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p  Output (AC)  Rated power <sup>(3)</sup> 600 kVA Maximum current 1,050 A Rated voltage 330 V IT System  Frequency 50 / 60 Hz Phi Cosine <sup>(4)</sup> 1 Phi Cosine adjustable Yes. Smax=600 kVA  Output protections Overvoltage protections AC surge arresters, type 2  AC breaker Yes Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5% CEC  98%	800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Other protections  DC insulation monitor with alarm. Optionally, from 8 to 16 pairs of DC fuses (16 to 32 p.  Output (AC)  Rated power <sup>(3)</sup> 600 kVA Maximum current 1,050 A Rated voltage 330 V IT System Frequency 50 / 60 Hz Phi Cosine dijustable Yes. Smax=600 kVA THD (Total Harmonic Distortion) <sup>(5)</sup> Output protections Overvoltage protections AC surge arresters, type 2 AC breaker Yes Anti-islanding protection AC fuses, AC short circuits and overloads (for each power stage) Other protections  Maximum efficiency 98.5% CEC  Output (16 to 32 p.  DU fuses (16 to 32 p.  DU fuses (16 to 32 p.  DE f	800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Output (AC)       Rated power <sup>(3)</sup> 600 kVA       Maximum current     1,050 A       Rated voltage     330 V IT System       Frequency     50 / 60 Hz       Phi Cosine adjustable     Yes. Smax=600 kVA       THD (Total Harmonic Distortion) <sup>(5)</sup> <3%	800 kVA 1,400 A 330 V IT System 50 / 60 Hz
Rated power <sup>(3)</sup> Maximum current  1,050 A  Rated voltage  330 V IT System  Frequency  50 / 60 Hz  Phi Cosine <sup>(4)</sup> 1  Phi Cosine adjustable  Yes. Smax=600 kVA  THD (Total Harmonic Distortion) <sup>(5)</sup> Output protections  Overvoltage protections  AC surge arresters, type 2  AC breaker  Act breaker  Act surge arresters, type 2  Act	1,400 A 330 V IT System 50 / 60 Hz
Maximum current  Rated voltage  330 V IT System  Frequency  50 / 60 Hz  Phi Cosine dijustable  Yes. Smax=600 kVA  THD (Total Harmonic Distortion) (5)  Output protections  Overvoltage protections  AC surge arresters, type 2  AC breaker  Anti-islanding protection  Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Other protections  Ac fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency  98.5%  CEC  98%	1,400 A 330 V IT System 50 / 60 Hz
Rated voltage 330 V IT System  Frequency 50 / 60 Hz  Phi Cosine (6) 1  Phi Cosine adjustable Yes. Smax=600 kVA Yes  THD (Total Harmonic Distortion) (5) <3%  Output protections  Overvoltage protections  AC surge arresters, type 2  AC breaker Yes  Anti-islanding protection Yes, with automatic disconnection (for each power stage)  Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5%  CEC 98%	330 V IT System 50 / 60 Hz
Frequency 50 / 60 Hz  Phi Cosine (40)  Phi Cosine adjustable Yes. Smax=600 kVA Yes. THD (Total Harmonic Distortion) (5)  Output protections  Overvoltage protections  AC surge arresters, type 2  AC breaker Yes  Anti-islanding protection  Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Other protections  Maximum efficiency 98.5%  CEC 98%	50 / 60 Hz
Phi Cosine (4) Phi Cosine adjustable Phi Cosine adjustable Yes. Smax=600 kVA Yes. THD (Total Harmonic Distortion)(5)  Output protections Overvoltage protections AC surge arresters, type 2  AC breaker Yes Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5% CEC 98%	
Phi Cosine (40) Phi Cosine adjustable Phi Cosine adjustable Yes. Smax=600 kVA Yes. THD (Total Harmonic Distortion)(5)  Output protections Overvoltage protections AC surge arresters, type 2 AC breaker Yes Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5% CEC 98%	1
Output protections Overvoltage protections Overvoltage protections AC surge arresters, type 2 AC breaker Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections AC fuses, AC short circuits and overloads (for each power stage) Features  Maximum efficiency 98.5% CEC 98%	1
Output protections Overvoltage protections Overvoltage protections AC surge arresters, type 2 AC breaker Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections AC fuses, AC short circuits and overloads (for each power stage) Features  Maximum efficiency 98.5% CEC 98%	es. Smax=800 kVA
Overvoltage protections AC surge arresters, type 2 AC breaker Anti-islanding protection Yes, with automatic disconnection (for each power stage) Other protections AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5% CEC 98%	<3%
AC breaker  Anti-islanding protection  Yes, with automatic disconnection (for each power stage) Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency  98.5% CEC  98%	
Anti-islanding protection  Yes, with automatic disconnection (for each power stage)  Other protections  AC fuses, AC short circuits and overloads (for each power stage)  Features  Maximum efficiency 98.5%  CEC 98%	
Other protections AC fuses, AC short circuits and overloads (for each power statements)  Features  Maximum efficiency 98.5% CEC 98%	
Features  Maximum efficiency 98.5% CEC 98%	
Maximum efficiency         98.5%           CEC         98%	ge)
CEC 98%	
	98.5%
	98%
Stand-by consumption <sup>(6)</sup> 90 W	120 W
Consumption at night 90 W	120 W
General Information	
Ambient temperature -4 °F to 149 °F (-20 °C to 65 °C) -4 °F to	149 °F (-20 °C to 65 °C)
Relative humidity (non-condensing) 0 - 95%	0 - 95%
Protection class NEMA 3R	NEMA 3R
Max. altitude <sup>(7)</sup> 9,842 ft (3,000 m) 9	,842 ft (3,000 m)
Cooling system Air forced with temperature control (230 V phase + neutral power	supply)
Air flow 37.96 ft³/s (fans: 1,300 VA) 45.50	6 ft <sup>3</sup> /s (fans:1,500 VA)
Acoustic emission < 55 dB (A) at 4 m and < 67 dB (A) at 1 m with fans working at maxim	
Marking CE, ETL	
EMC and security standards  UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90.2	
Grid connection standards IEC 62116, UL1741, IEEE1547, IEEE1547.1, NEC CODE	




	660TL U X360 Outdoor	880TL U X360 Outdoor
Input (DC)		
Recommended PV array power range(1)	670 - 884 kWpV	892.6 - 1,178.3 kWp
Voltage Range MPP	528 - 820 V	528 - 820 V
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V
Maximum current	1,170 A	1,560 A
Nº inputs with fuse holders	12 (24 for floating configuration)	16 (32 for floating configuration)
- use dimensions	125 A / 1,000 V to 400 A / 1,000 V fuses, maximum cur	rrent from 82 to 260 A for positive and negative poles
Type of connection	Connection to	copper bars
Power blocks	3	4
MPPT	1	1
Current at each input	82 to 260 A	82 to 260 A
Input protections		
Overvoltage protections	DC surge arres	sters, type 2
OC switch	Motorized D	OC switch
Other protections	DC insulation monitor with alarm. Optionally, from 8 to 16 p.	airs of DC fuses (16 to 32 pairs for floating configuration)
Output (AC)		
Rated power <sup>(3)</sup>	660 kVA	880 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	360 V IT System	360 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(4)</sup>	1	1
Phi Cosine adjustable	Yes. Smax=660 kVA	Yes. Smax=880 kVA
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%
Output protections		
Overvoltage protections	AC surge arres	sters, type 2
AC breaker	Yes	6
Anti-islanding protection	Yes, with automatic disconnec	ction (for each power stage)
Other protections	AC fuses, AC short circuits and ov	verloads (for each power stage)
Features		
Maximum efficiency	98.5%	98.6%
CEC	98.5%	98.5%
Stand-by consumption <sup>(6)</sup>	90 W	120 W
Consumption at night	90 W	120 W
General Information		
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)
Relative humidity (non-condensing)	0 - 95%	0 - 95%
Protection class	NEMA 3R	NEMA 3R
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)
Cooling system	Air forced with temperature control (23	
	37.96 ft <sup>3</sup> /s (fans: 1,300 VA)	45.56 ft³/s (fans:1,500 VA)
Air flow	37.30 It /3 (Idils. 1,300 VA)	
	< 55 dB (A) at 4 m and < 67 dB (A) at 1 n	n with fans working at maximum power
Acoustic emission	< 55 dB (A) at 4 m and < 67 dB (A) at 1 n	
Air flow  Acoustic emission  Marking  EMC and security standards		TL



	750TL U X400 Outdoor	1000TL U X400 Outdoor		
Input (DC)				
Recommended PV array power range <sup>(1)</sup>	670 - 884 kWp	892.6 - 1,178.3 kWp		
Voltage Range MPP	581 - 820 V	581 - 820 V		
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V		
Maximum current	1,350 A	1,800 A		
N° inputs with fuse holders	12 (24 for floating configuration)	16 (32 for floating configuration)		
Fuse dimensions	125 A / 1,000 V to 400 A / 1,000 V fuses, maximum curre	nt from 82 to 260 A for positive and negative poles		
Type of connection	Connection to co	pper bars		
Power blocks	3	4		
MPPT	1	1		
Current at each input	82 to 260 A	82 to 260 A		
Input protections				
Overvoltage protections	DC surge arreste	rs, type 2		
DC switch	Motorized DC	switch		
Other protections	DC insulation monitor with alarm. Optionally, from 8 to 16 pair	s of DC fuses (16 to 32 pairs for floating configuration)		
Output (AC)				
Rated power <sup>(3)</sup>	765 kVA	1,020 kVA		
Maximum current	1,104 A	1,472 A		
Rated voltage	400 V IT System	400 V IT System		
Frequency	50 / 60 Hz	50 / 60 Hz		
Phi Cosine <sup>(4)</sup>	1	1		
Phi Cosine adjustable	Yes. Smax=765 kVA	Yes. Smax=1,020 kVA		
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%		
Output protections				
Overvoltage protections	AC surge arreste	rs, type 2		
AC breaker	Yes			
Anti-islanding protection	Yes, with automatic disconnection	on (for each power stage)		
Other protections	AC fuses, AC short circuits and over			
Features				
Maximum efficiency	98.5%	98.6%		
CEC	98.5%	98.5%		
Stand-by consumption <sup>(6)</sup>	90 W	120 W		
Consumption at night	90 W	120 W		
General Information				
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)		
Relative humidity (non-condensing)	0 - 95%	0 - 95%		
Protection class	NEMA 3R	NEMA 3R		
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)		
Cooling system	Air forced with temperature control (230			
Air flow	37.96 ft³/s (fans: 1,300 VA)	45.56 ft³/s (fans:1,500 VA)		
Acoustic emission	< 55 dB (A) at 4 m and < 67 dB (A) at 1 m v			
Marking				
	CE, ETL			
EMC and security standards	III 17/11 FCC Part 15 IEEE C3	UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90.2		



	805TL U X420 Outdoor	1070TL U X420 Outdoor	
Input (DC)			
Recommended PV array power range <sup>(1)</sup>	818.9 - 1,044 kWp	1,091.5 - 1,392 kWp	
Voltage Range MPP	611 - 820 V	611 - 820 V	
Maximum voltage <sup>(2)</sup>	1,000 V	1,000 V	
Maximum current	1,350 A	1,800 A	
N° inputs with fuse holders	12 (24 for floating configuration)	16 (32 for floating configuration)	
Fuse dimensions	125 A / 1,000 V to 400 A / 1,000 V fuses, maximum curre	ent from 82 to 260 A for positive and negative poles	
Type of connection	Connection to co	ppper bars	
Power blocks	3	4	
MPPT	1	1	
Current at each input	82 to 260 A	82 to 260 A	
Input protections			
Overvoltage protections	DC surge arreste	ers, type 2	
DC switch	Motorized DC	switch	
Other protections	DC insulation monitor with alarm. Optionally, from 8 to 16 pai	rs of DC fuses (16 to 32 pairs for floating configuration)	
Output (AC)			
Rated power <sup>(3)</sup>	803.1 kVA	1,070.8 kVA	
Maximum current	1,104 A	1,472 A	
Rated voltage	420 V IT System	420 V IT System	
Frequency	50 / 60 Hz	50 / 60 Hz	
Phi Cosine <sup>(4)</sup>	1	1	
Phi Cosine adjustable	Yes. Smax=803.1 kVA	Yes. Smax= 1,070.8 kVA	
THD (Total Harmonic Distortion) <sup>(5)</sup>	<3%	<3%	
Output protections			
Overvoltage protections	AC surge arreste	ers, type 2	
AC breaker	Yes		
Anti-islanding protection	Yes, with automatic disconnecti	on (for each power stage)	
Other protections	AC fuses, AC short circuits and ove	rloads (for each power stage)	
Features			
Maximum efficiency	98.5%	98.6%	
CEC	98.5%	98.5%	
Stand-by consumption <sup>(6)</sup>	90 W	120 W	
Consumption at night	90 W	120 W	
General Information			
Ambient temperature	-4 °F to 149 °F (-20 °C to 65 °C)	-4 °F to 149 °F (-20 °C to 65 °C)	
Relative humidity (non-condensing)	0 - 95%	0 - 95%	
Protection class	NEMA 3R	NEMA 3R	
Max. altitude <sup>(7)</sup>	9,842 ft (3,000 m)	9,842 ft (3,000 m)	
Cooling system	Air forced with temperature control (230	) V phase + neutral power supply)	
Air flow	37.96 ft³/s (fans: 1,300 VA)	45.56 ft <sup>3</sup> /s (fans:1,500 VA)	
Acoustic emission	< 55 dB (A) at 4 m and < 67 dB (A) at 1 m		
	CE, ETI		
Marking	UL1741, FCC Part 15, IEEE C37.90.1, IEEE C37.90.2		
Marking  EMC and security standards		37.90.1, IEEE C37.90.2	



# INGECON SUN PowerStation



## From 750 to 2140 kVA

Fully integrated turnkey solution, customized up to 2.14 MVA

All the devices required for a multimegawatt system are incorporated into a single structure.

# Maximize your investment with minimal effort

INGECON® SUN PowerStation U is a compact, customizable and flexible solution that can be configured to suit each customer's requirements. It features PV central inverters for outdoor installation, so there is no need of any kind of housing. Maximum efficiency thanks to the selective work of its power stages depending on the available PV power.

#### Plug & Play technology

This Medium Voltage turnkey solution integrates power conversion equipment —up to 2140 kVA-, step up transformer, switchgear, low voltage distribution panels and monitoring equipment. It is delivered fully furnished for Plug & Play integration at the site.

#### Software included

It includes, without any extra cost, the software INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor Smartphone version for monitoring, displaying and recording the data from the inverter through Internet.

#### SYSTEM FEATURES

- 2 IS PowerMax TL U Outdoor inverters with an output power AC up to 2140 kVA.
- Liquid filled MV Pad Mounted transformer up to 35 kV with integrated switch disconnect, customized for each particular project.
- Electrical gear: low voltage distribution panels, auxiliary transformers.
- Complete integration of all electrical components for faster installation at project site.

#### CONSTRUCTION

- Steel Channel base-frame.
- Skid platform grounded or pier mounted.

#### Size and weight

(ft and lbs)
Dimensions aprox.
20' to 26' L x 11' W x 9' 11" H
Weight aprox.
30000 to 38000 lbs

#### Complete accessibility

Thanks to the lack of housing, the inverters can have immediate access. Furthermore, the INGECON® SUN Power-Max Outdoor inverters feature a modular system that distributes the load between the various power stages, facilitates the maintenance, and controls the voltage dips, the active power and the reactive power.

# Protections and communications included

Active power control, reactive power control and voltage dips. RS-485 communications by default for inverter control and monitorization (alarms, real time production, etc.).

#### OPTIONS

- Medium Voltage switchgear.
- Metering equipment.
- Reduced loss transformer.
- Remote communications.
- SCADA for system supervision.
- Start-up at the system site.




Front view



Back view

## Configuration with PowerMax TL U Outdoor inverters

Example 2 x 1070 kVA



# **INGECON SUN** PowerStation Concrete



## From 300 to 2330 kVA

The comprehensive turnkey solution

#### **Equipped with everything necessary**

Ingeteam has developed a comprehensive turnkey Medium Voltage solution that integrates all the energy conversion equipment up to 2140 kW, PV inverters, LV/MV transformer, Low Voltage parallel cabinet, auxiliary services panel and monitoring equipment that can be customized according to each specific user.

It is supplied totally equipped with a complete integration of the enclosure, the inverters, the controls and the transformer in a single unit or platform, for its Plug & Play installation on-site.

#### Perfect refrigeration

This Medium Voltage solution, concrete made for a perfect isolation and durability, features an advanced air forced cooling system that, together with the inverters' internal fans, guarantees the correct operation of all the equipment inside the cabin. Moreover, the Power-Station fans also feature some filters that avoid the entrance of water and particles.

#### CONSTRUCTION

- Steel basement in U shape with walls and ceiling in galvanized aluminium panels.
- The platform is fixed to the ground or mounted over the foundations.

## SYSTEM FEATURES

- 2 INGECON® SUN inverters with a combined output AC power from 300 to 2.140 kVA.
- Oil transformer up to 36 kV with an integrated breaker.
- Electric switching: Low Voltage parallel cabinet, auxiliary transformers.
- Complete integration of all the electrical elements for a quick on-site installation.
- Heat dissipation system for an optimal inverter performance.
- Illumination system.

#### OPTIONAL

- Medium Voltage equipment.
- Air conditioning system.
- Measuring equipment.
- Reduced losses transformer.
- Remote communication.
- SCADA for system supervision.
- On-site start up.

#### Weight and dimensions of the housing

(Without inverters)


Dimensions

8,300 mm L x 2,500 mm H x 2,170 mm W

Weight 19,000 kg



# Scheme with two inverters with Multi-MPPT configuration (also available with Master-Slave or Monoblock configuration) $2 \times 1,070 \text{ kVA}$



# INGECON SUN MV Box



## From 300 to 4660 kVA / 6 to 36 kVA

Medium voltage transformer box designed for outdoor installation, ideal for large multi-megawatt plants

#### Simplifies the PV installation procedure

Equipped with everything required to complete the connection of the INGECON® SUN PowerMax outdoor inverters to the utility company's MV grid, including the LV / MV transformer, the MV switchgear and the LV auxiliary services switchgear. A range of accessories are available to configure the INGECON® SUN MV Box to suit the requirements of each specific customer.

#### Ease of maintenance

A low-maintenance structure with a useful life of more than 20 years. In the event of a failure, the doors ensure ease of access to the internal components, shortening repair times and lowering maintenance costs.

#### Designed for outdoor installation

Suitable for direct outdoor installation thanks to its compact, weatherproof enclosure. Simple mounting on a cement base, telescopic guides for the access conduits to the cable protection. The varnish used guarantees maximum protection against adverse weather conditions.



#### MAIN FEATURES


- Suitable for outdoor installation and IP54 / NEMA 3R protection degree for use in any climatic conditions.
- Available with LV / MV transformer up to 4660 kVA and 36 kV output voltage.
- Compatible with cast resin and oil immersed LV / MV transformers.
- Forced Air ventilation system for transformer compartment with temperature probes and central thermometric control.
- Complete accessibility for ease of maintenance.
- Ease of access to the LV / MV transformer to connect the cables running from the PV array.
- Hot galvanised structure for a useful life of more than 20 years.
- Built-in Low Voltage auxiliary services switchgear with everything required to complete the PV installation.
- Extensive range of Medium Voltage switchgears for chain or ring connection.
- Lower installation and connections costs.


- Standard opto-isolated RS-485 communication infrastructure for direct connection to INGECON® SUN PowerMax outdoor inverters and INGECON® SUN String Control string combiner boxes.
- Complete internal lighting system with emergency lights from 60 minutes onwards
- Compliance with the principal medium and high voltage directives and regulations.
- Medium Voltage safety kit: Class 3 gloves and 30 kV insulating footboard.
- Fire safety kit: portable 5 kg CO<sub>2</sub> fire extinguisher.
- Manufacturer's 2 year warranty, extendible up to 25 years on request.

#### OPTIONAL EQUIPMENT

- LV / LV transformer for the power supply to the auxiliary services panel.
- UPS for auxiliary services.
- Energy meter with GSM / GPRS system for remote metering.
- Metering of the AC energy produced by means of approved TV voltage sensors and TA current sensors.
- Meteo station.
- INGECON® SUN String Control 16 / 32 string combiner boxes.
- High-speed Ethernet / Fiber Optic communication infrastructure for Plug & Play connection to PV Plant Controller and SCADA systems.
- SCADA supervision, control and data acquisition system.
- PV Plant Controller compliant with the most widely international Grid Codes.
- Gateway for monitoring and control of the PV Plant by the Grid Operator using standard protocols (like IEC 61850, IEC 60870-5-101/104, DNP 3.0, etc.).

#### MV Box





# INGECON SUN PowerStation

SHE 22



## From 300 to 2330 kVA

The complete turnkey solution, customized & fully equipped up to 2.8 MWp, 22 ft. shelter with Forced Air cooling system

The very latest technological development by Ingeteam. All the devices required for a multi-megawatt system incorporated into a single shelter with three separate compartments and different cooling systems, easily transportable by road thanks to its small dimensions and low weight.

# Maximize your investment with minimal effort

INGECON® SUN PowerStation SHE 22 is a compact, customisable and flexible solution that can be configured to suit each customer's requirement. Thanks to its panel-based structure, the internal layout can be customised to incorporate various INGECON® SUN inverters. Ideal for low environmental impact applications.

#### Extremely robust and long-lasting

The shelter can be easily transported by road, thanks to its small dimensions and low overall weight. The hot galvanised steel structure is designed to guarantee maximum mechanical strength and durability. The walls and roof contain a 50 mm rigid fire-proof polyurethane foam filling, to guarantee perfect water resistance and correct thermal insulation.

#### **Equipped with everything necessary**

High efficiency inverters, auxiliary services switchgear, Medium Voltage cubicle and LV / MV transformer. Available with High-speed Ethernet / Fiber Optic communication infrastructure for Plug & Play connection to PV Plant Controller, monitoring and SCADA systems.

#### Maximum stability

All the devices are anchored to the base, to guarantee the maximum stability of the structure. The varnish used guarantees maximum protection against adverse weather conditions.

#### Complete accessibility

Thanks to its innovative design, all devices are readily accessible, thereby making it easier to inspect, maintain and repair the INGECON® SUN PowerStation SHE 22. The MV transformer compartment door is equipped with AREL safety lock with a blocking code.

#### Innovative ventilation system

The internal temperature of inverter compartment is controlled by high efficiency hot air extraction plenums and centrifugal fan systems. A number of internal and external probes guarantee a constant ambient temperature. The incoming air is filtered through special grids mounted on the bottom of the walls.



SHE 22 TUNNEL FA / NA



SHE 22 TUNNEL FA / FA



SHE 22 WING FA / NA



SHE 22 WING FA / FA

#### MAIN FEATURES

- Output power up to 2330 kVA.
- Available up to 36 kV output voltage.
- Available with cast resin or oil immersed hermetically sealed LV / MV transformers.
- Protection degree: IP54 / NEMA 3R for inverter compartment.
- Extremely compact design.
- Plug & Play solution.
- Maximum reliability, higher safety and reduced maintenance thanks to flexible copper busbars for Low Voltage power distribution.
- Fully customizable.
- Operating Temperature Range: from -20 °C to +60 °C. (1)
- Relative Humidity: 0 95%.
- Installation Altitude: 3000 m above sea level. (1)
  - (1) Refer to Technical Characteristics table for further details.

#### ELECTRICAL PROTECTIONS

- Reverse polarity.
- Output short-circuits and overloads.
- DC fuses.
- DC switch with door control.
- AC circuit breaker with door control.
- DC and AC overvoltage suppressors.
- Anti-islanding monitoring system with automatic disconnection.
- Insulation monitoring system.
- Automatic disconnection system in case of LV / MV transformer overheat.
- Emergency disconnection button, accessible from outside.

#### STANDARD EQUIPMENT


- Internal lighting system.
- Emergency lighting system.
- Auxiliary power outlet.
- Fire detection system with automatic disconnection (both DC and AC sides).
- Safety interlocks for MV transformer compartment door.
- Fire safety kit.
- Medium Voltage safety kit.
- First aid kit and safety signals.


#### OPTIONAL EQUIPMENT

In addition to the standard equipment, the INGECON® SUN PowerStation can be supplied with the following options:

- LV / MV transformer for the power supply to the auxiliary services panel.
- UPS for auxiliary services.
- INGECON® SUN String Control 16 / 32 string combiner boxes.
- Energy meter with GSM / GPRS system for remote metering.
- Meteo station.
- High-speed Ethernet / Fiber Optic communication infrastructure for Plug & Play connection to PV Plant Controller and SCADA systems.
- SCADA supervision, control and data acquisition system.
- PV Plant Controller compliant with the most widely international Grid Codes.
- Gateway for monitoring and control of the PV Plant by the Grid Operator using standard protocols (like IEC 61850, IEC 60870-5-101/104, DNP 3.0, etc.).
- HV surge arresters.
- Anti-rodent system.
- Human intrusion detection system.
- External lighting system.

# INGECON SUN PowerStation






	SHE 22 - FA / FA SHE 22				
General Information					
	Cooling system	Forced air with tempera	ature control		
In a star O and a star and	Air extraction / Air intake	Overpressure dampers with anti-rain co	Overpressure dampers with anti-rain covers / Filtered sand trap grids		
Inverter Compartment	Max. power consumption	400 W			
	Protection degree	IP54 / NEMA	3R		
	Cooling system	Forced air with temperature control	Natural air ventilation		
Tranformer Compartment	Air extraction / Air intake	Overpressure dampers with anti-rain covers / Filtered sand trap grids	Protective metal grids		
	Max. power consumption	2,720 W	0 W		
	Protection degree	IP54 / NEMA 3R	IP21		
	Cooling system	Forced air with tempera	ature control		
M/O 1: 1	Air extraction / Air intake	Filtered anti-rain	grids		
MV Cubicle compartment (2)	Max. power consumption	130 W			
	Protection degree	IP55 / NEMA	3R		
Operating temperature range (3)		from -30 °C to +	0° 00		
Relative humidity		0 - 95%			
Installation altitude (4)		3,000 m above se	ea level		
Equipment					
Inverter version		X series (Master-Slave), M series (Multi-MPPT), B series (Monoblock)			
BT-AUX switchgear		BASE version (FULL version and high-speed co	mmunication infrastructure optional;		
LV / MV Transformer		Dry type cast resin or Oil immers	ed hermetically sealed		
MV Switchgear		1P-1L or 1P-2L prote	ction cells		
Mechanical Information					
Structure Material		Steel			
Insulation		Sandwich panels containing a 50 mm rigid f	ire-proof polyurethane foam filling		

Notes: (1) Equipped with oil immersed hermetically sealed LV / MV transformers (2) Including instrumentation, auxiliary services switchgear, monitoring systems (3) INGECON® SUN PowerMax, "M" and "X" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 45 °C operating temperature. Derating above 45 °C of 1.8% for each °C of increase until 60 °C operating temperature. -30 °C with optional kit (3) INGECON® SUN PowerMax, "B" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 50 °C operating temperature. Derating above 50 °C of 1.8% for each °C of increase until 60 °C operating temperature. -30 °C with optional kit (4) Please contact Ingeteam for altitudes higher than 1,000 m.

	Length	Width	Height
Size (mm)			
Body dimensions	6,750	2,450	3,050
Overall dimensions with doors open (Tunnel)	8,760	3,950	3,050
Overall dimensions with doors open (Wing)	8,560	6,750	3,050
Foundation dimensions	9,000	5,000	300



# INGECON SUN PowerStation

**CON 40** 



## From 300 to 3500 kVA

The complete turnkey solution, customized up to 4.2 MWp, 40 ft. container with innovative forced air or air conditioned cooling systems for adverse environmental conditions

Thanks to its CSC approval for overseas shipment, The INGECON® SUN Power-Station CON 40 can be marketed and installed everywhere in the world. It is a fully equipped container with three separate compartments and different cooling systems (up to 2330 kVA) or two separate compartments with different cooling systems and outdoor mounted LV / MV transformer (up to 3500 kVA).

#### Robust and long-lasting design

The INGECON® SUN PowerStation CON 40 is a standard solution specifically designed for dusty areas with innovative cooling systems to ensure the nominal output power up to 60 °C. Moreover, this solution avoid any problem regarding the corrosion generated from sandstorms. To ensure the maximum protection against weather conditions, external sides are coated with a galvanized layer and painted with polyurethane lacquer. The loadbearing structure is single-block made of welded steel, to ensure top resistance and durability over time. Rooftop and walls are coated with insulated sandwich panels. The sandwich panels are made of galvanized painted steel, filled with a 50 mm layer of rigid fireproof polyurethane foam, ensuring perfect waterproofness over time and efficient thermal insulation.

#### Equipped with everything necessary

High efficiency inverters, auxiliary services switchgear, Medium Voltage cubicle and LV / MV transformer. Available with High-speed Ethernet / Fiber Optic communication infrastructure for Plug & Play connection to PV Plant Controller, monitoring and SCADA systems.

#### Complete accessibility

Thanks to its innovative design, all devices are readily accessible, thereby making it easier to inspect, maintain and repair the INGECON® SUN Power-Station CON 40. The transformer compartment door is equipped with AREL safety lock with a blocking code.

#### Ideal for adverse environments

The INGECON® SUN PowerStation CON 40 is a standard solution able to withstand adverse environmental conditions without any loss of performance. Thanks to its recirculation air conditioning system, the "RC" version can provide its rated power up to 60 °C (ambient temperature) without derating and IP65 / NEMA 4 protection degree.

#### Innovative cooling system

**FA type**: the internal temperature of inverters compartment is controlled by high efficiency hot air extraction plenums and centrifugal fan systems. A number of internal and external probes

guarantee a constant ambient temperature. The incoming air is filtered through special sand trap grids mounted on the bottom of the walls.

**AC type**: the container is equipped with an internal cooling system featuring a Free Cooling function for inverters compartment. The air conditioning units, sized for each of the inverters, feature the following operating modes:

- Pure Free Cooling: Compressor in OFF mode. The outdoor air temperature is low and the conditioner operates like a ventilation system, with an air inflow and outflow.
- Assisted Free Cooling: Compressor operates in ON-OFF mode. The outdoor air temperature is relatively low to allow operation in Free Cooling mode. However, it is not low enough to maintain the desired interior temperature.
- Cooling Compressor in ON mode: The system operates like a normal air conditioner.

**RC type**: the container is equipped with an internal Recirculation Air Conditioning system for inverters compartment, to maintain the correct internal temperature over the entire operating temperature range.



CON 40 RT FA / NA



CON 40 RT AC-RC / NA

#### MAIN FEATURES

- Output power up to 3500 kVA.
- Available up to 36 kV output voltage.
- Available with cast resin or oil immersed hermetically sealed LV / MV transformer (up to 2330 kVA).
- Available with outdoor mounted hermetically sealed LV / MV transformer (up to 3500 kVA).
- Up to IP65 / NEMA 4 protection degree for inverter compartment.<sup>(1)</sup>
- Rated power up 60 °C ambient temperature. (1)
- Protected against solar and sand corrosion.
- CSC certification for container shipping.
- Plug & Play solution.
- Maximum reliability, higher safety and reduced maintenance thanks to solid aluminium and flexible copper busbars for Low Voltage power distribution.
- Different cooling systems for inverter compartment<sup>(1)</sup>:

Type FA: Forced Air ventilation, operating temperature range from -20 °C to +60 °C.

Type AC: Free Cooling Air Conditioning system, operating temperature range from -20 °C to +55 °C without derating.

Type RC: Recirculation Air Conditioning system, operating temperature range from -20 °C to +60 °C without derating.

- Relative Humidity: 0 95%.
- Installation Altitude: 3000 m above sea level. (1)

#### ELECTRICAL PROTECTIONS

- Reverse polarity.
- Output short-circuits and overloads.
- DC fuses.
- DC switch with door control.
- AC circuit breaker with door control.
- DC and AC overvoltage suppressors.
- Anti-islanding monitoring system with automatic disconnection.
- Insulation monitoring system.
- Automatic disconnection system in case of LV / MV transformer overheat.
- Emergency disconnection button, accessible from outside.

#### STANDARD EQUIPMENT

- Internal lighting system.
- Emergency lighting system.
- Auxiliary power outlet.
- Fire detection system with automatic disconnection (both DC and AC sides).
- Safety interlocks for MV transformer compartment door.
- Fire safety kit.
- Medium Voltage safety kit.
- First aid kit and safety signals.





#### CON 40 RT AC-RC / FA


#### OPTIONAL EQUIPMENT


In addition to the standard equipment, the INGECON® SUN PowerStation CON 40 can be supplied with the following options:

- LV / LV transformer for the power supply to the auxiliary services panel.
- UPS for auxiliary services.
- INGECON® SUN String Control 16 / 32 inputs string combiner boxes.
- Meteo station.
- Energy meter with GSM / GPRS system for remote metering.
- High-speed Ethernet / Fiber Optic communication infrastructure for Plug & Play connection to PV Plant Controller and SCADA systems.
- SCADA supervision, control and data acquisition system.
- PV Plant Controller compliant with the most widely international Grid Codes.
- Gateway for monitoring and control of the PV Plant by the Grid Operator using standard protocols (like IEC 61850, IEC 60870-5-101/104, DNP 3.0, etc.).
- HV surge arresters.
- Anti-rodent system.
- Human intrusion detection system.
- External lighting system.

<sup>(1)</sup> Refer to Technical Characteristics tables for further details.

# INGECON SUN PowerStation







<sup>\*</sup> Illustrative image. It might not correspond with the basic configuration.

		CON 40 RT - FA / xx	CON 40 RT - AC / xx	CON 40 RT - RC / xx
General Information				
	Cooling system	Forced air ventilation	Air conditioning with Free Cooling function	Recirculation air conditioning
Inverter Compartment (1)	Air extraction / Air intake	Overpressure Dampers with anti- rain covers / Filtered sand trap grids	Overpressure Dampers / Filte	ered grids with anti-rain covers
	Max. power consumption	420 W	5,400 / 18,000 W (2)	18,000 W
	Protection degree	IP54 / NEMA 3R	IP54 / NEMA 3R	IP65 / NEMA 4
	Cooling system	Forced air with temperature control		
LV / MV Transformer compartment	Air extraction / Air intake	Overpressure dampers with anti-rain covers / Filtered sand trap grids		
CON 40 RT - xx / FA	Max. power consumption	2,720 W		
	Protection degree		IP54 / NEMA 3R	
	Cooling system		Natural air ventilation	
LV / MV Transformer compartment (3)	Air extraction / Air intake		Protective metal grids	
CON 40 RT - xx / NA	Max. power consumption		0 W	
	Protection degree		IP21	
	Cooling system		Forced air with temperature control	
	Air extraction / Air intake		Filtered anti-rain grids	
MV Cubicle compartment	Max. power consumption		65 W	
	Protection degree		IP55 / NEMA 3R	
Operating temperature range (5)		from -20 °C to +60 °C (4)	from -20 °C to +55 °C	from -20 °C to +60 °C
Relative humidity			0 - 95%	
Installation altitude (6)			3,000 m above sea level	
Equipment				
Inverter version		X series (Master-	Slave), M series (Multi-MPPT), B se	ries (Monoblock)
BT-AUX switchgear		BASE version (FULL vers	sion and high-speed communicatio	n infrastructure optional)
LV / MV Transformer		Dry type o	ast resin or Oil immersed hermetic	ally sealed
MV Switchgear			1P-1L or 1P-2L protection cells	
Mechanical Information				
Structure Material			Steel	
Insulation		Sandwich panels con	taining a 50 mm rigid fire-proof pol	yurethane foam filling

Notes: (1) Including inverters, instrumentation, auxiliary services switchgear, monitoring systems (2) Pure Free Cooling function / Cooling function (3) Equipped with oil immersed hermetically sealed LV / MV transformers (4) For INGECON® SUN PowerMax, "M" and "X" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 45 °C operating temperature. Derating above 45 °C of 1.8% for each °C of increase until 60 °C operating temperature (4) For INGECON® SUN PowerMax, "B" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 50 °C operating temperature. Derating above 50 °C of 1.8% for each °C of increase until 60 °C operating temperature (5) -30 °C with optional kit (6) Please contact Ingeteam for altitudes higher than 1,000 m.

	Length	Width	Height
Size (mm)			
Body dimensions	12,192	2,438	2,896
Overall dimensions with all doors open	14,400	3,700	2,896
Foundation dimensions	14,142	5,000	300






<sup>\*</sup> Illustrative image. It might not correspond with the basic configuration.

Cooling system  Air extraction / Air intake  Max. power consumption  Protection degree  Cooling system  Air extraction / Air intake  Max. power consumption	Forced air ventilation  Overpressure dampers with anti-rain covers / Filtered sand trap grids  630 W  IP54 / NEMA 3R	Air conditioning with Free Cooling function Overpressure Dampers / Filtered grids with anti-rain covers 7,200 / 24,000 W <sup>(2)</sup> IP54 / NEMA 3R Forced air with temperature control	Recirculation air conditioning Overpressure Dampers / Standard grids with anti-rain covers 24,000 W IP65 / NEMA 4	
Air extraction / Air intake  Max. power consumption  Protection degree  Cooling system  Air extraction / Air intake  Max. power consumption	Overpressure dampers with anti-rain covers / Filtered sand trap grids 630 W IP54 / NEMA 3R	Free Cooling function  Overpressure Dampers / Filtered grids with anti-rain covers  7,200 / 24,000 W (2)  IP54 / NEMA 3R	Overpressure Dampers / Standard grids with anti-rain covers 24,000 W IP65 / NEMA 4	
Max. power consumption Protection degree Cooling system Air extraction / Air intake Max. power consumption	covers / Filtered sand trap grids 630 W IP54 / NEMA 3R	grids with anti-rain covers 7,200 / 24,000 W <sup>(2)</sup> IP54 / NEMA 3R	grids with anti-rain covers 24,000 W IP65 / NEMA 4	
Protection degree  Cooling system  Air extraction / Air intake  Max. power consumption	IP54 / NEMA 3R	IP54 / NEMA 3R	IP65 / NEMA 4	
Cooling system  Air extraction / Air intake  Max. power consumption				
Air extraction / Air intake  Max. power consumption		Forced air with temperature control		
Max. power consumption				
		Filtered anti-rain grids		
	65 W			
Protection degree		IP55 / NEMA 3R		
Mounting type	Outdoor m	nounting with protective perimeter m	netal fence	
Cooling system		Natural air ventilation		
	from -20 °C to +60 °C (3)	from -20 °C to +55 °C	from -20 °C to +60 °C	
		0 - 95%		
		3,000 m above sea level		
	M se	ries (Multi-MPPT), B series (Monob	llock)	
	BASE version (FULL version and high-speed communication infrastructure optional)		n infrastructure optional)	
		Oil immersed hermetically sealed		
		1P-1L or 1P-2L protection cells		
		Steel		
	Sandwich panels cor	ntaining a 50 mm rigid fire-proof poly	yurethane foam filling	
	Mounting type	Mounting type  Cooling system  from -20 °C to +60 °C (3)  M se  BASE version (FULL ver	Mounting type  Cooling system  Natural air ventilation  from -20 °C to +60 °C (3)  from -20 °C to +55 °C  0 - 95%  3,000 m above sea level  M series (Multi-MPPT), B series (Monoble BASE version (FULL version and high-speed communication Oil immersed hermetically sealed 1P-1L or 1P-2L protection cells	

Notes: (1) Including inverters, instrumentation, auxiliary services switchgear, monitoring systems (2) Pure Free Cooling function / Cooling function (3) For INGECON® SUN PowerMax, "M" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 45 °C operating temperature. Derating above 45 °C of 1.8% for each °C of increase until 60 °C operating temperature (3) For INGECON® SUN PowerMax, "B" series: rated output power indicated in the Technical Characteristics tables is guaranteed up to 50 °C operating temperature. Derating above 50 °C of 1.8% for each °C of increase until 60 °C operating temperature (4) -30 °C with optional kit (5) Please contact Ingeteam for altitudes higher than 1,000 m.

	Length	Width	Height
Size (mm)			
CON 40 dimensions	12,192	2,438	2,896
CON 40 overall dimensions with doors open	14,400	3,700	2,896
LV / MV transformer indicative dimensions	2,600	1,400	2,700
Foundation dimensions	14,142	7,500	300





# INGECON SUN PowerStation


Different installation configurations


## Configuration


This system is very flexible and offers different configuration possibilities. A single component can control all the elements, reducing production times, facilitating the maintenance and making repairing processes more efficient.















INGECON SUN STORAGE

**BATTERY INVERTERS** 

# The AC-Link Concept



# Smart solutions for stand-alone systems

A large number of remote villages all over the world are still forced to resort to alternative energy generation solutions to supply their needs. Due to economic factors, pollution and, of course, dependence, the power generation systems based solely on fossil fuels, no longer appear to be the best option.

Ingeteam has applied all its experience in the electrical engineering sector in order to develop solutions for these alternative energy generation systems.

As a result, Ingeteam is proud to offer a wide range of products capable of meeting all types of needs and requirements.

Based on the premise of making an uninterrupted energy supply available, Ingeteam has designed some robust, easy-to-install equipment, with priority given to the generation of electricity through renewable energy sources.


The sun and the wind are resources that are as old as they are plentiful in our environment and, as such, they form the base that supports our systems.

We are referring to converters capable of generating energy by means of these resources, and supported by a system of batteries in order to ensure that power is delivered to the mini-grid whenever the photovoltaic and wind power systems are unable to power the loads.

Within our range of products for off-grid systems we include single-phase and three-phase solutions being able to fit in all type of load demands.

#### The AC-Link Concept

The AC-Link Concept consists of an off-grid AC network to which the loads and the renewable energy sources are coupled. This AC grid is generated by a battery inverter that acts as a grid manager by establishing the voltage's amplitude and frequency.



The INGECON® SUN STORAGE battery inverter controls the energy coming from the sources and the energy flows inside the AC grid, by modifying the frequency of the grid voltage. As a result, it guarantees the correct balance between generation, consumption and the storage system.

Apart from that, the battery inverter manages the batteries' state of charge and the operation of an optional auxiliary AC source (a genset or the public grid).


When the renewable sources are available the energy generated feeds the loads, while the excess is stored in the batteries. But if the loads demand more

energy than the one available, the batteries will provide the amount of energy needed.

Regarding the operation of an auxiliary genset, it will only be connected when the batteries' state of charge is lower than a certain programmable threshold.

#### ADVANTAGES

- 100% Renewable energy.
- The AC-Link Concept allows to use standard grid-connected INGECON® SUN PV inverters.
- Thanks to the management system that controls the power generated, no communication is required between the PV and the battery inverters.
- This enables to locate the energy generation sources in a distributed manner, e.g., rooftop installations in an island, where there is not much land available.
- The AC-Link concept allows connecting in parallel battery inverters rather than power generation inverters, thus adjusting the system's total power to every specific case.
   If the energy demand increases in the future, the storage capacity could be also enlarged, as well as the installed renewable power.
- If the public grid reaches the installation, the micro-grid could be coupled to it. In that case, the energy coming from renewable sources will be prioritised to satisfy the demand of the loads.



# NGECON SUN STORAGE 1Play

With transformer



# 3/6

Single-phase battery inverter with transformer

The INGECON® SUN STORAGE 1Play TL battery inverter is a single-phase, two-way unit that can either be used in off-grid systems or connected to the general supply network.

#### **Battery management**

The INGECON® SUN STORAGE 1Play inverters feature cutting-edge technology to control the charging and discharging of the storage system in order to maximise the battery service life. The battery temperature could be controlled at all times, ensuring correct battery operation and durability. The inverter incorporates a pre-charge system to avoid battery inrush currents.

#### Back-up genset

The INGECON® SUN STORAGE 1Play permits the connection of a back-up genset, should this be necessary. Furthermore, the inverter can be started-up using this generator, in order to charge the batteries when these are completely discharged.

#### PV input

Optionally, the new INGECON® SUN STORAGE 1Play inverters can incorporate a PV input. Thanks to this input, the PV array can be connected directly to the inverter.

## Maximum compatibility

This inverter is fully compatible with the INGECON® SUN and INGECON®  $\mu WIND$  inverters. Furthermore, the scale of the system created and managed by the INGECON® SUN STORAGE 1Play can be increased through the parallel connection of a number of grid-connected converters to the AC grid. It is also possible to to create three phase grids with three single-phase inverters.

# 3 year warranty, extendible up to 25 years.

### PROTECTIONS

- Galvanic isolation between the DC and AC sides.
- AC overvoltages.
- Insulation faults.
- Output shortcircuits and overloads.

## OPTIONAL ACCESORIES

- Inverter communication via RS-485 and Ethernet.
- PV input.
- DC switch for the PV field.
- AC pre-charge system.
- INGECON® SUN STORAGE Box.

#### ACCESSORIES SUPPLIED AS STANDARD

- CAN communication for smart batteries.
- Configurable potential free input.
- Configurable potential-free outputs, some for the connection and disconnection of the back-up genset.
- DC pre-charge system.
- Battery temperature measurement circuit built-in. PT100 (3-wire) needed.

#### Operating modes:

#### - Stand-alone

The INGECON® SUN STORAGE 1Play inverter generates a stand-alone AC grid and acts as a grid manager, guaranteeing the correct balance between generation, consumption and the storage system. To do so, it controls the energy flow between the grid and the batteries, based on the status at any given time.

The INGECON® SUN STORAGE 1Play inverter makes it possible to integrate a solar energy source into the grid, through the use of INGECON® SUN inverters. An advanced control system, requiring no communications, manages the power generated by the PV inverters, based on consumption data and the battery charge status. The back-up power source (a genset or the public grid) only connects when the battery state of charge is below a certain programmable threshold.

Optionally, this unit can incorporate a PV input. As a special operating case within the stand-alone mode, it is possible to implement the **Direct Panel Mode.** 

In this mode, there is no storage system and the system only operates when the solar resource is available, always providing the energy directly from the PV panel.

#### - Back-up mode

This operating mode has been designed for grid-connected systems, where grid outages are long and frequent, meaning that a back-up power source is required. The INGECON® SUN STORAGE 1Play inverter operates through a connection to the AC grid. In order to guarantee a power source, the inverter maintains the batteries charged. During a grid outage, the battery inverter generates the AC network and the energy stored in the batteries is used to power the loads. If any renewable energy sources are connected to the grid and the energy generated is greater than the one demanded, then the surplus could be injected into the grid. Furthermore, this mode also makes it possible to implement peak shaving strategies in order to shave consumption peaks and reduce the contracted power.


#### - Self-consumption mode

This operating mode is conceived for grid-connected systems with renewable energy sources, in order to minimise grid consumption. If the energy generated is greater than the one demanded, any surplus energy could charge the batteries or, if they are fully charged, the energy could be injected into the grid. If the loads demand more energy than the one produced by the renewable sources, then the batteries would cover this demand, increasing the self-consumption ratio. In this mode, it is also possible to implement peak shaving strategies in order to shave consumption peaks and lower the electricity bill.


#### - Grid support

In combination with the INGECON® EMS Manager, the INGECON® SUN STORAGE 1Play inverter is able to adapt the output power from the PV plant to a pre-established value, in order to maintain a constant power output or to control the ramp rate.

# Schema for the Stand-alone mode Single-phase



#### Three-phase



<sup>\*</sup> It must be a single battery bank.

# **INGECON SUN STORAGE 1Play**

Transformerless



## 3TL / 6TL

Single-phase transformerless battery inverter

The INGECON® SUN STORAGE 1Play TL battery inverter is a single-phase, two-way unit that can either be used in off-grid systems or connected to the general supply network.

#### **Battery management**

The INGECON® SUN STORAGE 1Play TL inverters feature cutting-edge technology to control the charging and discharging of the storage system in order to maximise the battery service life. The battery temperature could be controlled at all times, ensuring correct battery operation and durability. The inverter incorporates a pre-charge system to avoid battery inrush currents.

#### Back-up genset

The INGECON® SUN STORAGE 1Play TL permits the connection of a back-up genset, should this be necessary. Furthermore, the inverter can be started-up using this generator, in order to charge the batteries when these are completely discharged.

#### PV input

Optionally, the new INGECON® SUN STORAGE 1Play TL inverters can incorporate a PV input. Thanks to this input, the PV array can be connected directly to the inverter.

#### Maximum compatibility

This inverter is fully compatible with the INGECON® SUN and INGECON® µWIND inverters. Furthermore, the scale of the system created and managed by the INGECON® SUN STORAGE 1Play TL can be increased through the parallel connection of a number of grid-connected converters to the AC grid.

# 3 year warranty, extendible up to 25 years.

#### PROTECTIONS

- AC overvoltages.
- Insulation faults.
- Output shortcircuits and overloads.

#### OPTIONAL ACCESORIES

- Inverter communication via RS-485 and Ethernet.
- PV input.
- DC switch for the PV field.
- AC pre-charge system.
- INGECON® SUN STORAGE Box.

#### ACCESSORIES SUPPLIED AS STANDARD

- CAN communication for smart batteries.
- Configurable potential free input.
- 2 configurable potential-free outputs, some for the connection and disconnection of the back-up genset.
- DC pre-charge system.
- Battery temperature measurement circuit built-in. PT100 (3-wire) needed.

#### Operating modes:

#### - Stand-alone mode

The INGECON® SUN STORAGE 1Play TL inverter generates a stand-alone AC grid and acts as a grid manager, gua-ranteeing the correct balance between generation, consumption and the storage system. To do so, it controls the energy flow between the grid and the batteries, based on the status at any given time.

The INGECON® SUN STORAGE 1Play TL inverter makes it possible to integrated solar energy source into the grid, through the use of INGECON® SUN inverters. An advanced control system, requiring no communications, manages the power generated by the PV inverters, based on consumption data and the battery charge status. The back-up power source (a genset or the public grid) only connects when the battery state of charge is below a certain programmable threshold.

Optionally, this unit can incorporate a PV input. As a special operating case within the stand-alone mode, it is possible to implement the **Direct Panel Mode.** 

In this mode, there is no storage system and the system only operates when the solar resource is available, always providing the energy directly from the PV panel.

#### - Back-up mode

This operating mode has been designed for grid-connected systems, where grid outages are long and frequent, meaning that a back-up power source is required. The INGECON® SUN STORAGE 1Play TL inverter operates through a connection to the AC grid. In order to guarantee a power source, the inverter maintains the batteries charged. During a grid outage, the battery inverter generates the AC network and the energy stored in the batteries is used to power the loads. If any renewable energy sources are connected to the grid and the energy generated is greater than that demanded, then the surplus could be injected into the grid. Furthermore, this mode also makes it possible to implement peak shaving strategies in order to shave consumption peaks and reduce the contracted power.


#### - Self-consumption mode

This operating mode is conceived for grid-connected systems with renewable energy sources, in order to minimise grid consumption. If the energy generated is greater than the one demanded, any surplus energy could charge the batteries or, if they are fully charged, the energy could be injected into the grid. If the loads demand more energy than the one produced by the renewable sources, then the batteries would cover this demand, increasing the self-consumption ratio. In this mode, it is also possible to implement peak shaving strategies in order to shave consumption peaks and lower the electricity bill.

#### - Grid support

In combination with the INGECON® EMS Manager, the INGECON® SUN STORAGE 1Play TL inverter is able to adapt the output power from the PV plant to a pre-established value, in order to maintain a constant power output or to control the ramp rate.

#### Schema for the Stand-alone mode




<sup>\*</sup> Each inverter will have its own battery bank.

	3	6
PV Input (DC)		
PV array max. power	6.5 kWp	10 kWp
Voltage range MPP	300 - 450 V	300 - 450 V
Voltage range <sup>(1)</sup>	300 - 550 V	300 - 550 V
Maximum current	20 A	30 A
Inputs	2	2
MPPT	1	1
Battery Input (DC)		
Rated Battery voltage <sup>(2)</sup>	48 - 300 V	96 - 300 V
Extended battery voltage(3)	48 - 420 V	96 - 420 V
Minimum operation voltage <sup>(2)</sup>	40 V	40 V
Maximum charge / discharge current	50 A	50 A
Battery type	Lead, Ni-Cd, Li-ion	Lead, Ni-Cd, Li-ion
Generator / Grid Input (AC)		
Rated voltage	230 V	230 V
Voltage range	172 - 264 V	172 - 264 V
Rated frequency	50 / 60 Hz	50 / 60 Hz
Frequency range	40 - 70 Hz	40 - 70 Hz
Charge current range	0 - 13 A	0 - 26 A
Generator or grid maximum power	11.500 W	11.500 W
Output (AC)		
Rated power <sup>(4)</sup>	3 kW	6 kW
Power (25 °C) 30 min, 2 min, 3 s <sup>(5)</sup>	3.500 / 3.900 / 5.080 W	6.400 / 6.900 / 7.900 W
Current	13 A	26 A
Rated voltage <sup>(6)</sup>	220 - 240 V	220 - 240 V
Rated frequency <sup>(6)</sup>	50 / 60 Hz	50 / 60 Hz
Efficiency		
Maximum efficiency	95,5%	96%
General Information		
Stand-by consumption	<10 W	<10 W
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%
Protection class	IP65	IP65

Compliance with standards: EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-12, EN 61000-3-11, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS 3100, RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2<sup>(7)</sup>, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, IEEE 929, Thailand MEA & PEA requirements

Notes: (1) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (2) The inverter's maximum power will be the battery voltage multiplied by the maximum discharge current (50 A) (3) Only possible if PV energy is not present (4) AC power up to 40 °C ambient temperature (5) This power is only available if the battery voltage multiplied by the maximum discharge current reaches these values (6) This parameter is configurable through the display (7) Related only to inverters up to 16 A.





Transformer

	3TL	6TL
PV Input (DC)		
PV array max. power	6.5 kWp	10 kWp
Voltage range MPP	300 - 450 V	300 - 450 V
Voltage range <sup>(1)</sup>	300 - 550 V	300 - 550 V
Maximum current	20 A	30 A
Inputs	2	2
MPPT	1	1
Battery Input (DC)		
Rated Battery voltage <sup>(2)</sup>	48 - 300 V	96 - 300 V
Extended battery voltage <sup>(3)</sup>	48 - 420 V	96 - 420 V
Minimum operation voltage <sup>(2)</sup>	40 V	40 V
Maximum charge / discharge current	50 A	50 A
Battery type	Lead, Ni-Cd, Li-ion	Lead, Ni-Cd, Li-ion
Generator / Grid Input (AC)		
Rated voltage	230 V	230 V
Voltage range	172 - 264 V	172 - 264 V
Rated frequency	50 / 60 Hz	50 / 60 Hz
Frequency range	40 - 70 Hz	40 - 70 Hz
Charge current range	0 - 13 A	0 - 26 A
Generator or grid maximum power	11,500 W	11,500 W
Output (AC)		
Rated power <sup>(4)</sup>	3 kW	6 kW
Power (25 °C) 30 min, 2 min, 3 s <sup>(5)</sup>	3,500 / 3,900 / 5,080 W	6,400 / 6,900 / 7,900 W
Current	13 A	26 A
Rated voltage <sup>(6)</sup>	220 - 240 V	220 - 240 V
Rated frequency <sup>(6)</sup>	50 / 60 Hz	50 / 60 Hz
Efficiency		
Maximum efficiency	95.5%	96%
General Information		
Stand-by consumption	<10 W	<10 W
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%
Protection class	IP65	IP65

Compliance with standards: EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-3, EN 61000-3-12, EN 61000-3-11, EN 62109-1, EN 62109-2, IEC62103, EN 50178, FCC Part 15, AS 3100, RD1699/2011, DIN V VDE V 0126-1-1, EN 50438, CEI 0-21, VDE-AR-N 4105:2011-08, G59/2, G83/2<sup>(7)</sup>, AS4777.2, AS4777.3, IEC 62116, IEC 61727, UNE 206007-1, ABNT NBR 16149, ABNT NBR 16150, South African Grid code, IEEE 929, Thailand MEA & PEA requirements

Notes: (1) Must not be exceeded under any circumstances. Consider the voltage increase of the 'Voc' at low temperatures (2) The inverter's maximum power will be the battery voltage multiplied by the maximum discharge current (50 A) (3) Only possible if PV energy is not present (4) AC power up to 40 °C ambient temperature (5) This power is only available if the battery voltage multiplied by the maximum discharge current reaches these values (6) This parameter is configurable through the display (7) Related only to inverters up to 16 A.





### NGECON SUN STORAGE PowerMax



### Power management at large PV plants with an energy storage system

Smart solutions for seamless integration into the electricity grid

Ingeteam has developed the INGECON® SUN STORAGE PowerMax (EMS: *Energy Management Solutions*) family of inverters, designed to integrate energy storage systems into PV plants.

### Integration of batteries into PV plants

The use of energy storage systems at PV plants helps to improve the integration of solar energy into the electricity grid, particularly in the case of a weak grid or one with a high solar energy penetration.

The INGECON® SUN STORAGE Power-Max inverters are compatible with the range of battery technologies currently available, such as Lead, Ni-Cd, Redox and Lithium, ensuring that the most suitable technology can be used for each specific application.


The use of energy storage systems makes it possible to implement different plant operating strategies, such as the control of the plant power output variability or the generation of a constant power output.

### Control of the power output variability


The variation in irradiance caused by passing clouds produces power output variations that can be as great as 80% of the rated power of the plant per minute, depending on the size of the plant and the weather conditions at the site.

The use of INGECON® SUN STORAGE PowerMax inverters, together with their corresponding batteries, makes it possible to reduce the dynamics of these variations and to adapt to the requirements imposed by grid operators, improving the quality of supply and ensuring the high integration of solar energy into the electricity system.


An energy storage system makes it possible to control the plant power output ramps, based on pre-established values. Whenever a cloud passes over, with the subsequent loss of irradiance, the storage system provides the energy required to offset the energy shortfall, whilst the power output is progressively reduced until it is equal to the PV power. Once the cloud has gone, the available power increases sharply and this is used to charge the batteries whilst smoothly increasing the power output.



Example of the system performance in the face of an 80%/min fluctuation in irradiance (up and down), in accordance with the 10%/min output power variation requirement.



Output power at an actual 1 MW PV plant on a day with scattered clouds, th and without energy storage systems, implementing output power regulation.



Output power on a day with scattered clouds, with and without energy storage systems, implementing constant power control.

## Constant power control. Shifting the power curve

With the INGECON® SUN STORAGE PowerMax inverters, it is also possible to control the plant output power to ensure that this remains at a constant, pre-determined value. This value can be calculated on the basis of grid operator requirements or weather forecasts. Furthermore, the power curve can be shifted if required by the grid operator.

## High penetration for diesel-PV hybrid plants

The INGECON® SUN STORAGE Power-Max inverters can be used to support diesel-PV hybrid systems, to achieve high PV penetration levels. In this way, the PV production variations caused by passing clouds are offset with the power supplied from the storage systems, thereby allowing greater response time

to either vary the diesel load balance system or to start up new generators.

### DC and AC supplies together

The input and output supplies are integrated into the same cabinet, facilitating maintenance and repair works.

#### Solutions available

- Indoor inverters with an integrated DCAC cabinet.
- Indoor inverters with a DC cabinet.
- Outdoor inverters with an integrated DCAC cabinet.

This system is based on conventional grid-connected inverters for PV generation and dedicated inverters to connect the batteries to the electricity grid. This option can be installed in PV plants that are already operating. It also offers the possibility of providing reactive energy with the battery inverters, thereby avoiding the need to over-size the PV inverters should there be strict reactive power delivery requirements. For this topology, a plant controller manages the energy flow between the grid and the batteries, adjusting the plant generation to a pre-established pattern.

### NGECON SUN STORAGE Power

With transformer



### 60 / 80 / 100 / 125 / 150 / 200 / 250

Three-phase battery inverter with transformer

The INGECON® SUN STORAGE Power battery inverter is a three-phase, two-way unit that can either be used in off-grid systems or connected to the general supply network. This inverter offers a high power density in a single power block, providing a choice of configurable operating modes.

### **Battery management**

The INGECON® SUN STORAGE Power features high-tech battery management in order to maximise the useful life of the storage system. The battery temperature can be monitored at all times, guaranteeing a correct operation.

### Back-up genset

Furthermore, the INGECON® SUN STORAGE Power permits the connection of a back-up generator, should this be necessary. It is possible to start-up the inverter by using the genset, in order to charge the batteries.

### Maximum compatibility

This inverter is 100% compatible with the INGECON® SUN inverters, making it possible to integrate a solar energy source into the AC grid. To do so, additional PV inverters are required.


### Software included

The INGECON® SUN Manager software is included at no extra charge. This can be used to monitor and record the inverter data over the Internet. The RS-485 communications are supplied as standard.

The INGECON® SUN STORAGE Power three-phase inverter complies with the most demanding international standards and regulations.

Standard 3 year warranty, extendable for up to 25 years

Size (mm)





### NGECON SUN STORAGE Power

### With transformer

### Operating modes:

#### Stand-alone mode

The INGECON® SUN STORAGE Power generates a stand-alone AC grid and acts as a grid manager, guaranteeing the correct balance between generation, consumption and the storage system. To achieve this, the INGECON® SUN STORAGE Power is able to control the energy flows between the grid and the batteries, based on the status at any given time. The INGECON® SUN STORAGE Power inverter allows a solar energy source to be integrated into the grid, through the use of IN-GECON® SUN inverters.

An advanced control system, requiring no communications, manages the power generated by the INGECON® SUN inverters, based on consumption data and the battery state of charge status. The back-up power source (a genset or the public grid) only connects when the battery state of charge is below a certain programmable threshold.

- Galvanic isolation between the DC and AC sides.
- Short-circuits and overloads at the output.
- Insulation faults

PROTECTIONS

- DC switch.
- AC circuit breaker.

## Back-up mode

This operating mode has been designed for grid-connected systems, where grid outages are long and frequent, meaning that a back-up power source is required. The INGE-CON® SUN STORAGE Power inverter operates through a connection to the AC grid. In order to guarantee a power source, the inverter maintains the batteries charged. During a grid outage, the battery inverter generates the AC network and the energy stored in the batteries is used to power the loads. If any renewable energy sources are connected to the grid and the energy generated is greater than that demanded, then the surplus could be injected into the grid. Furthermore, this mode also makes it possible to implement peak shaving strategies, in order to shave consumption peaks and reduce the contracted power.

#### Self-consumption mode

This operating mode is conceived for grid-connected systems with renewable energy sources, in order to minimise grid consumption. If the energy generated is greater than demand, then any any surplus energy could charge the batteries or, if they are fully charged, the energy could be injected into the grid. If the loads demand more energy than that produced by the renewable sources, then the batteries would cover this demand, increasing the self-consumption ratio. This mode also allows for the implementation of *peak shaving* strategies in order to shave consumption peaks and lower the electricity bill.

### - Grid support

In combination with the INGECON® EMS Plant Controller, the INGECON® SUN STORAGE Power inverter is able to adapt the output power from the PV plant to a pre-established value, in order to maintain a constant power output or to control the ramp rate.


#### OPTIONAL ACCESSORIES

- Inverter communication via Ethernet.
- DC fuses.
- Type 2, DC surge arresters.
- AC pre-charge system.
- AC wattmeter and switch for the auxiliary AC input.

#### ACCESSORIES SUPPLIED AS STANDARD

- RS-485 communication.
- CAN communication for smart batteries.
- Configurable potential free inputs.
- Configurable potential-free outputs, some for the connection and disconnection of a back-up genset.
- DC pre-charge system.
- Type 2, AC surge arresters.

### Schema for the Stand-alone mode




Bidirectional only when grid is connected.

	60	80	100	125	150	200	250
Batteries (DC)							
Nominal Power	≥ 62 kW	≥ 82 kW	≥ 103 kW	≥ 129	≥ 155 kW	≥ 206 kW	≥ 258 kW
Voltage range	330 - 820 V	347 - 820 V	462 - 820 V	578 - 820 V			
Maximum voltage <sup>(1)</sup>	1,000 V	1,000 V					
Maximum current	191 A	255 A	318 A	398 A	450 A	450 A	450 A
Inputs	4	4	4	4	4	4	4
Type of battery	Lead, Ni-Cd, Li-ion	Lead, Ni-Cd, Li-ion					
Input (AC)							
Rated voltage	400 V	400 V					
Voltage range	320 - 480 V	320 - 480 V					
Frecuency	50 / 60 Hz	50 / 60 Hz					
Frecuency Range	40 - 70 Hz	40 - 70 Hz					
Charging curent range	0 - 96 A	0 - 128 A	0 - 160 A	0 - 200 A	0 - 241 A	0 - 321 A	0 - 368 A
Maximum power	250 kW	250 kW					
Output (AC)							
Rated power <sup>(2)</sup>	60 kW	80 kW	100 kW	125 kW	150 kW	200 kW	250 kW
Maximum current	96 A	128 A	160 A	200 A	241 A	321 A	368 A
Rated voltage	400 V	400 V					
Frequency	50 / 60 Hz	50 / 60 Hz					
Efficiency							
Maximum efficiency	96.4%	96.6%	96.8%	96.9%	97.3%	97.4%	97.5%
General Information							
Galvanic isolation	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Air cooling	2,600 m <sup>3</sup> /h	2,600 m³/h					
Stand-by consumption	30 W	30 W					
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C					
Relative Humidity (Non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Maximum altitude <sup>(3)</sup>	3,000	3,000	3,000	3,000	3,000	3,000	3,000
Protection Class	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Weight	900 kg	1,026 kg	1,162 kg	1,162 kg	1,325 kg	1,400 kg	1,500 kg

Compliance with standards: EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, EN 61000-3-12, EN 61000-3-11, EN 62109-1, EN 62109-2, IEC 62103, EN 50178, FCC Part 15, EN 50438, IEC 62116, IEC 61727, VDE 0126-1-1

Notes: (1) Above 820 V, the maximum current decreases gradually (2) AC Power for 40 °C ambient temperature (3) Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1,000 m.



### NGECON SUN STORAGE PowerMax

### **B** Series



### 1000TL B400 DCAC Indoor

Three-phase transformerless battery inverter

The INGECON® SUN STORAGE Power-Max is a three-phase bidirectional battery inverter that can be used in both, grid-connected or stand-alone systems. This inverter offers a high-power density in a single power block, providing different configurable operating modes.

### Easy maintenance

String inverter philosophy has been applied in the design of this central inverter, facilitating the inverter usage. Moreover, the input and output lines are

integrated into the same cabinet, in order to make maintenance work easier.

#### **Battery management**

The INGECON® SUN STORAGE Power-Max features a highly advanced battery control technology, ensuring the maximum life of the storage system. The battery temperature could be controlled at all times ensuring an enhanced lifespan of the accumulator. This inverter is 100% compatible with the INGECON® SUN inverters.

### Software included

Included at no extra cost the software INGECON® SUN Manager for monitoring and recording the inverter data over the Internet. Ethernet communications are supplied as standard.

The INGECON® SUN STORAGE Power-Max three-phase inverter complies with the most demanding international standards.

Standard 3 year warranty, extendable for up to 25 years



### INGECON SUN STORAGE PowerMax

### **B** Series

#### Operating modes:

#### - Stand-alone mode

The INGECON® SUN STORAGE Power-Max inverter generates an off-grid AC network and acts as a grid manager, guaranteeing the correct balance between generation, consumption and the storage system. To do so, the INGECON® SUN STORAGE Power-Max can control the energy flow between the grid and the batteries, based on the situation at any given time. The INGECON® SUN STORAGE Power-Max allows the integration of a solar energy source into the grid using INGECON® SUN PV inverters.

An advanced control system, requiring no communications, manages the power generated by the INGECON® SUN inverters, based on consumption and the battery state of charge. The auxiliary source (a genset or the public grid) is only connected when the batteries' state of charge is lower than a certain programmable threshold.

#### - Back-up mode

This operation mode is conceived for grid-connected systems where grid outages are long and frequent, and an auxiliary energy source is required. The INGECON® SUN STORAGE Power-Max inverter works connected to the AC grid. In order to guarantee an energy source the inverter keeps the batteries charged. During grid outages, the INGECON® SUN STORAGE Power-Max generates an AC grid and the energy stored in the batteries is used to feed the loads.

If renewable energy sources are connected to the grid and the energy generated is bigger than the one demanded, the surplus could be injected into the grid.

### Self-consumption mode

This operating mode is conceived for grid-connected systems with renewable energy sources in order to minimise the consumption from the grid. If the energy generated is bigger than the one demanded, the surplus could be used to charge the batteries or to inject into the grid if the batteries are fully charged. If the loads demand more energy than the one produced by the renewable sources, the batteries would satisfy the demand, increasing the self-consumption ratio.

### - Grid support

In combination with the INGECON® EMS Plant Controller, the INGECON® SUN STORAGE PowerMax inverter can adapt the output power of a PV plant to a pre-established requirement, such as power ramp control or constant output power.

#### PROTECTIONS

- Output short-circuits and overloads.
- Insulation failures.
- DC switch.
- IP64 protection class for the electronics.


#### INTEGRATED ACCESSORIES

- Ethernet communication.
- CAN communication for smart batteries.
- Configurable potential-free inputs.
- Configurable potential-free outputs, some of them for connection and disconnection of the back-up generators.
- DC pre-charge system.
- AC surge arresters, type 2.

#### OPTIONAL ACCESSORIES

- DC fuses.
- DC surge arresters, type 2.
- AC pre-charge system.
- Heating kit, for operating at an ambient temperature of -40 °C (-40 °F).
- AC circuit breaker.

#### Schema for the Stand-alone mode





	1000TL B400 DCAC Indoor
Batteries (DC)	
Nominal Power	≥ 1,030 kW
Voltage range for stand-alone mode	578 - 820 V
Voltage range for grid-connected modes <sup>(1)</sup>	636 - 820 V
Maximum voltage <sup>(2)</sup>	1,050 V
Maximum current	2,000 A
Inputs	8
Type of battery	Lead, Ni-Cd, Li-ion
Output (AC)	
Rated power (@ 50 °C)	1,000 kVA
Maximum power (@ 30 °C)	1,108 kVA
Maximum current	1,600 A
Rated voltage	400 V
Frequency	50 / 60 Hz
Efficiency	
Maximum efficiency	98.9%
General Information	
Galvanic isolation	No
Air cooling	8,000 m³/h
Stand-by consumption	60 W
Ambient temperature	-20 °C to +65 °C
Relative Humidity (Non-condensing)	0 - 95%
Maximum altitude <sup>(3)</sup>	3,000
Protection Class	IP20
Electronics' protection class	IP64
Weight	1,860 kg

Compliance with standards: EN 61000-6-1, EN 61000-6-2, EN 61000-6-4, EN 61000-3-12, EN 61000-3-11, EN 62109-1, EN 62109-2, IEC 62103, EN 50178, FCC Part 15, EN 50438, IEC 62116, IEC 61727

Notes: (1) Grid-connected modes include Back-up, Self consumption and Grid Support. Minimum voltage DC ( $V_{DC, min}$ ) for  $V_{grid,max} = 1.1$  p.u. If  $V_{grid,max}$  is higher than this value, minimum voltage should be corrected as  $V_{DC, min} * V_{grid,max} / 1.1$  (2) Above 820V, the maximum current decreases gradually (3) Over 1,000 m temperature for rated power is reduced at the rate of 4.5 °C for each 1000 m.

### SUN STORAGE PowerMax





### NGECON SUN STORAGE PowerMax

X Series
Indoor / Outdoor





### Battery inverters with a DCAC cabinet

The INGECON® SUN STORAGE Power-Max battery inverter family operates in a wide range of output voltages: 220, 275, 300, 320, 345, 360 and 400 Vac. For any of the operating voltages, these inverters have from two to four independent power blocks.

### **Battery management**

This battery inverter contemplates a power converter dedicated to each ESS. This converter delivers direct current to


the batteries for charging purposes whilst it feeds alternating current into the grid when it discharges the ESS. The battery inverter either delivers or absorbs the power required to ensure that the overall plant power is controlled. The equipment can change from charging to discharging the batteries in a matter of seconds.


#### Performance qualities

For this topology, a plant controller man-

ages the energy flow between the grid and the batteries, adjusting the plant generation to a pre-established pattern. Therefore, the plant controller is responsible for adding up the power outputs from the PV inverters and for calculating the power received by the battery inverters as a set point.

Standard 5 year warranty, extendible up to 25 years







### Battery inverters with a DC cabinet

#### Available in a DC version

This model has no AC cabinet and therefore takes up less space. This is a flexible solution, particularly suited to medium voltage transformer substations with two inverters. The construction of enclosures to house a number of inverters, maximises the investment made.

### System highlights

This battery inverter can be installed in PV plants that are already operating. It


is also possible to provide reactive energy with the battery inverters, thereby avoiding the need to over-size the PV inverters should there be strict reactive power delivery requirements.


### Software included

The INGECON® SUN Manager and INGECON® SUN Monitor applications for monitoring and recording the inverter data over the internet, are included at no extra cost.

## Protections and communications included


The INGECON® SUN STORAGE Power-Max family has a low-voltage ride through capability and is equipped with an active and reactive power control system. RS-485 communications supplied as standard for inter-inverter communications, and inverter monitoring (alarms, real time production, etc.). Featuring status and alarm LED indicators and the possibility of remote control from a PC or local control from the inverter display.





### INGECON SUN STORAGE PowerMax

# X Series Indoor / Outdoor



This option is based on conventional grid-connected inverters for the PV generation and dedicated inverters to connect the batteries to the electricity grid. This option can be installed in PV plants that are already operating. It offers the possibility of providing reactive


energy with the battery inverters, thereby avoiding the need to over-size the PV inverters should there be strict reactive power delivery requirements. For this topology, a plant controller manages the energy flow between the grid and the batteries, adjusting the plant generation to a pre-established pattern.

### PROTECTIONS

- Short-circuits and overloads at the output.
- Anti-islanding with automatic disconnection.
- Isolation monitor.
- DC load break switch.
- Lightning induced DC and AC surge arresters, type 2.


#### OPTIONAL ACCESSORIES

- Inter-inverter communications via Ethernet, Bluetooth or GSM / GPRS.
- Remote tripping of the AC protection.
- AC circuit breaker with door control (only in DCAC units).




### SUN STORAGE PowerMax x Series 300 Vac

	380TL X300	570TL X300	760TL X300
Input (DC) (Battery)			
Battery voltage range	480 - 820 V	480 - 820 V	480 - 820 V
Maximum current	900 A	1,350 A	1,800 A
Type of battery		Li-ion, lead, Ni-Cd	
Connection type	Connection to fuse holder copper bars,	cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm
Input protections			
Overvoltage protections	T	rpe 2 DC surge arresters (for each power stage	
DC switch	,	Motorized DC switch with door control	•1
Other protections	Up to 16 pairs of DO	C fuses, DC insulation monitor with alarm, eme	rgency nushbutton
Output (AC)	Op to 10 pails of BC	rases, po insulation monitor war alarm, eme	ingency pastibation
Rated power <sup>(1)</sup>	378 kW	568 kW	757 kW
Maximum current	736 A	1,104 A	1,472 A
Rated voltage	300 V IT System	300 V IT System	300 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=378 kVA	Yes. Smax=568 kVA	Yes. Smax=757 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%	<3%
		cable entry from the bottom through D40 cable	
	Confilection to ruse notice copper bars,	cable entry from the bottom through b40 cabi	e giarius (max. cable diameter. 40 mm
Connection type			
Output protections		Type 2 AC surge arresters	
Output protections Overvoltage protections	Optional AC circuit breaker w	Type 2 AC surge arresters ith door control, motorized or remote trip (only	v available for DCAC models)
Output protections Overvoltage protections AC breaker Anti-islanding protection			
Output protections Overvoltage protections AC breaker Anti-islanding protection	Yes, w	ith door control, motorized or remote trip (only	stage)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	Yes, w	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s	stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features	Yes, w	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s	stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency	Yes, w AC fuses,	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s AC short circuits and overloads (for each pow	stage) er stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency	Yes, w AC fuses, 98.6%	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s AC short circuits and overloads (for each pow 98.6%	stage) er stage) 98.6%
Output protections  Overvoltage protections  AC breaker	Yes, w AC fuses, 98.6% 98.4%	ith door control, motorized or remote trip (only ith automatic disconnection (for each power start and overloads (for each power start and overloads) (for each	stage) ver stage) 98.6% 98.4%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup>	Yes, w AC fuses, 98.6% 98.4% 97.9%	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s AC short circuits and overloads (for each pow 98.6% 98.4% 97.9%	98.6% 98.4% 97.9%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information	Yes, w AC fuses, 98.6% 98.4% 97.9%	ith door control, motorized or remote trip (only ith automatic disconnection (for each power s AC short circuits and overloads (for each pow 98.6% 98.4% 97.9%	98.6% 98.4% 97.9%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature	Yes, w AC fuses, 98.6% 98.4% 97.9% 120 W	ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each pow 98.6% 98.4% 97.9% 120 W	98.6% 98.4% 97.9% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing)	Yes, w AC fuses, 98.6% 98.4% 97.9% 120 W -20 °C to +65 °C	ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W	98.6% 98.4% 97.9% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class	Yes, w AC fuses, 98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95%	ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W	98.6% 98.4% 97.9% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup>	Yes, w AC fuses,  98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	ith door control, motorized or remote trip (only rith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W	98.6% 98.4% 97.9% 120 W -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Euroefficiency  CEC	Yes, w AC fuses,  98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	ith door control, motorized or remote trip (only rith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	98.6% 98.4% 97.9% 120 W -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system	Yes, w AC fuses,  98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air with 2,670 m³/h (fans: 1,230 W)	ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m at temperature control (230 V phase + neutral part of the control (23	98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  power supply) 5,340 m³/h (fans: 2,460 W)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	Yes, w AC fuses,  98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air with 2,670 m³/h (fans: 1,230 W)	ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each power's 98.6% 98.4% 97.9% 120 W -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m at temperature control (230 V phase + neutral 14,640 m³/h (fans: 2,050 W)	98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  power supply) 5,340 m³/h (fans: 2,460 W)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume	Yes, w AC fuses,  98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air with 2,670 m³/h (fans: 1,230 W)  <55 dB(A) at 4 r	ith door control, motorized or remote trip (only ith door control, motorized or remote trip (only ith automatic disconnection (for each power's AC short circuits and overloads (for each power's AC short circuits and overloads (for each power's 98.6% 98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m 1 temperature control (230 V phase + neutral page 14,640 m³/h (fans: 2,050 W) 1 and <67 dB(A) at 1 m with fans working at remove the supplementation of the supple	98.6% 98.4% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m bower supply) 5,340 m³/h (fans: 2,460 W) naximum power




	400TL X320	605TL X320	800TL X320
Input (DC) (Battery)			
Battery voltage range	515 - 820 V	515 - 820 V	515 - 820 V
Maximum current	900 A	1,350 A	1,800 A
Type of battery		Li-ion, lead, Ni-Cd	
Connection type	Connection to fuse holder copper bars	, cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm
Input protections			
Overvoltage protections	7	ype 2 DC surge arresters (for each power stage	
DC switch		Motorized DC switch with door control	-,
Other protections	Up to 16 pairs of D	C fuses, DC insulation monitor with alarm, eme	ergency nushbutton
	Op to 10 pairs of D	o lases, bo insulation monitor with diarm, eme	rigericy pashbatton
Output (AC)	404 1111		000.000
Rated power <sup>(1)</sup>	401 kW	605 kW	803 kW
Maximum current	736 A	1,104 A	1,472 A
Rated voltage	320 V IT System	320 V IT System	320 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=401 kVA	Yes. Smax=605 kVA	Yes. Smax=803 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%	<3%
Connection type	Connection to fuse holder copper bars	, cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm
Connection type			
Output protections		Type 2 AC surge arresters	
Output protections  Overvoltage protections		Type 2 AC surge arresters with door control, motorized or remote trip (only	y available for DCAC models)
Output protections Overvoltage protections AC breaker	Optional AC circuit breaker v		
Output protections Overvoltage protections AC breaker Anti-islanding protection	Optional AC circuit breaker v	with door control, motorized or remote trip (only	stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections	Optional AC circuit breaker v	with door control, motorized or remote trip (only with automatic disconnection (for each power s	stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features	Optional AC circuit breaker v Yes, · AC fuses	with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow	stage) ver stage)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency	Optional AC circuit breaker v Yes, AC fuses 98.7%	with door control, motorized or remote trip (only with automatic disconnection (for each power s, AC short circuits and overloads (for each pow	stage) ver stage) 98.7%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5%	with door control, motorized or remote trip (only with automatic disconnection (for each powers, AC short circuits and overloads (for each powers) 98.7% 98.5%	stage) ver stage) 98.7% 98.5%
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Euroefficiency  CEC	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5% 97.9%	with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.7% 98.5% 97.9%	98.7% 98.5% 97.9%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup>	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5%	with door control, motorized or remote trip (only with automatic disconnection (for each powers, AC short circuits and overloads (for each powers) 98.7% 98.5%	stage) ver stage) 98.7% 98.5%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup>	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5% 97.9%	with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.7% 98.5% 97.9%	98.7% 98.5% 97.9%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5% 97.9%	with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.7% 98.5% 97.9%	98.7% 98.5% 97.9%
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Euroefficiency  CEC  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature	Optional AC circuit breaker v Yes, AC fuses 98.7% 98.5% 97.9% 120 W	with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.7% 98.5% 97.9% 120 W	98.7% 98.5% 97.9%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing)	Optional AC circuit breaker ves, AC fuses  98.7% 98.5% 97.9% 120 W	with door control, motorized or remote trip (only with automatic disconnection (for each power s., AC short circuits and overloads (for each power s.)  98.7%  98.5%  97.9%  120 W	98.7% 98.5% 97.9% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95%	with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each power see, AC short circuits and Cartiforn circuits and	98.7% 98.5% 97.9% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup>	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each power see, AC short circuits and Carlos circuits and	98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Ccoling system	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads) (for each power see, AC short circuits and overloads)	98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air wit 2,670 m³/h (fans: 1,230 W)	with door control, motorized or remote trip (only with automatic disconnection (for each power s., AC short circuits and overloads (for each power s., AC short circuits and overloads (for each power s., AC short circuits and overloads (for each power s., AC short circuits and overloads (for each power s., AC short circuits and overloads (for each power s.)  98.7%  98.5%  97.9%  120 W  -20 °C to +65 °C  0 - 95%  IP20 / IP54  3,000 m  h temperature control (230 V phase + neutral processes)	98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  power supply) 5,340 m³/h (fans: 2,460 W)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air wit 2,670 m³/h (fans: 1,230 W)	with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each power's , AC short circuits and o	98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  power supply) 5,340 m³/h (fans: 2,460 W)
Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission Marking EMC & Security standards	Optional AC circuit breaker v Yes, AC fuses  98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m Forced air wit 2,670 m³/h (fans: 1,230 W) <55 dB(A) at 4	with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each power's , AC short circuits and overloads (for each power's , AC short circuits and overloads (for each power's , AC short circuits and overloads (for each power's , AC short circuits and overloads (for each power's , AC short circuits and very season of the short circuits and very season overloads (for each power's , AC short circuits and very season overloads) and very season overloads (for each power's , AC short circuits and very season overloads) and very season overloads (for each power's , AC short circuits and very season overloads) and very season overloads (for each power's , AC short circuits and overloads (for each power's , AC short cir	98.7% 98.5% 97.9% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m power supply) 5,340 m³/h (fans: 2,460 W) maximum power




### SUN STORAGE PowerMax x Series 345 Vac

	440TL X345	660TL X345	880TL X345
Input (DC) (Battery)			
Battery voltage range	552 - 820 V	552 - 820 V	552 - 820 V
Maximum current	900 A	1,350 A	1,800 A
Type of battery		Li-ion, lead, Ni-Cd	
Connection type	Connection to fuse holder copper bars,	cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm)
Input protections			
Overvoltage protections	Ту	pe 2 DC surge arresters (for each power stage	e)
DC switch		Motorized DC switch with door control	
Other protections	Up to 16 pairs of DC	C fuses, DC insulation monitor with alarm, eme	rgency pushbutton
Output (AC)			
Rated power <sup>(1)</sup>	440 kW	660 kW	880 kW
Maximum current	736 A	1,104 A	1,472 A
Rated voltage	345 V IT System	345 V IT System	345 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=440 kVA	Yes. Smax=660 kVA	Yes. Smax=880 kVA
THD (Total Harmonic Distortion) <sup>(3)</sup>	<3%	<3%	<3%
Connection type	Connection to fuse holder copper bars,	cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm)
Output protections			
Overvoltage protections		Type 2 AC surge arresters	
AC breaker	Optional AC circuit breaker w	ith door control, motorized or remote trip (only	available for DCAC models)
Anti-islanding protection	Yes, w	vith automatic disconnection (for each power s	stage)
Other protections	AC fuses,	AC short circuits and overloads (for each pow	er stage)
Features			
Maximum efficiency	98.8%	98.8%	98.8%
Euroefficiency	98.6%	98.6%	98.6%
CEC	98%	98%	98%
Stand-by consumption <sup>(4)</sup>	120 W	120 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(5)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Forced air with	n temperature control (230 V phase + neutral	power supply)
Air volume	2,670 m³/h (fans: 1,230 W)	4,640 m³/h (fans: 2,050 W)	5,340 m³/h (fans: 2,460 W)
Noise emission	<55 dB(A) at 4 n	n and <67 dB(A) at 1 m with fans working at r	naximum power
Marking		CE	
EMC & Security standards	EN 50	0178, IEC 61000-6-2, IEC 61000-6-4, FCC Pa	rt 15
Grid connection standards	BDEW MT, RD 661/2007, P.O.12.3	8, CEI 11-20, CEI 0-16, Allegato 70 TERNA, Arrêt	é 23-04-2008, IEEE 1547, G59/2




	460TL X360	690TL X360	920TL X360
Input (DC) (Battery)			
Battery voltage range	576 - 820 V	576 - 820 V	576 - 820 V
Maximum current	900 A	1,350 A	1,800 A
Type of battery		Li-ion, lead, Ni-Cd	
Connection type	Connection to fuse holder copper bars	, cable entry from the bottom through D40 cable	e glands (max. cable diameter: 40 mm
Input protections			
Overvoltage protections	Т	ype 2 DC surge arresters (for each power stage	.)
DC switch		Motorized DC switch with door control	
Other protections	Up to 16 pairs of D	C fuses, DC insulation monitor with alarm, eme	rgency pushbutton
Output (AC)			
Rated power <sup>(1)</sup>	458 kW	688 kW	917 kW
Maximum current	736 A	1,104 A	1,472 A
		360 V IT System	
Rated voltage Frequency	360 V IT System 50 / 60 Hz	50 / 60 Hz	360 V IT System 50 / 60 Hz
Phi Cosine <sup>(2)</sup>	50 / 60 HZ	50 / 60 HZ	1 507 60 HZ
Phi Cosine adjustable	Yes. Smax=458 kVA	Yes. Smax=688 kVA	Yes, Smax=917 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%	<3%
TTID (Total Flatfillottic Distortion)			
Connection type	Connection to fuse holder copper bars	, cable entry from the bottom through D40 cable	giarius (max. cable diameter. 40 mm
, ·	Connection to fuse holder copper bars	, cable entry from the bottom through D40 cable	e gianus (max. cable diameter: 40 mm
Output protections	Connection to fuse holder copper bars		; giantus (max. cable diameter. 40 mii
Output protections Overvoltage protections		Type 2 AC surge arresters	
Output protections  Overvoltage protections  AC breaker	Optional AC circuit breaker v	Type 2 AC surge arresters with door control, motorized or remote trip (only	available for DCAC models)
Output protections Overvoltage protections AC breaker Anti-islanding protection	Optional AC circuit breaker v Yes, v	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s	available for DCAC models)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	Optional AC circuit breaker v Yes, v	Type 2 AC surge arresters with door control, motorized or remote trip (only	available for DCAC models)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	Optional AC circuit breaker v Yes, v	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s	available for DCAC models)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features	Optional AC circuit breaker v Yes, v	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s	available for DCAC models)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency	Optional AC circuit breaker v Yes, v AC fuses	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow	available for DCAC models) tage) er stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency	Optional AC circuit breaker v Yes, AC fuses 98.8%	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow	available for DCAC models) tage) er stage) 98.8%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Euroefficiency CEC	Optional AC circuit breaker v Yes, AC fuses 98.8% 98.6%	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7%	available for DCAC models) tage) er stage) 98.8% 98.7%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup>	Optional AC circuit breaker v Yes, AC fuses 98.8% 98.6% 98.1%	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1%	available for DCAC models) tage) er stage) 98.8% 98.7% 98.1%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information	Optional AC circuit breaker v Yes, AC fuses 98.8% 98.6% 98.1%	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1%	available for DCAC models) tage) er stage) 98.8% 98.7% 98.1%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature	Optional AC circuit breaker v Yes, AC fuses 98.8% 98.6% 98.1% 120 W	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W	available for DCAC models) tage) er stage)  98.8% 98.7% 98.1% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Euroefficiency CEC Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing)	Optional AC circuit breaker v Yes, AC fuses 98.8% 98.6% 98.1% 120 W	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W	98.8% 98.7% 98.1% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class	98.8% 98.6% 98.1% 120 W	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W -20 °C to +65 °C 0 - 95%	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95%
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup>	Optional AC circuit breaker v Yes, AC fuses  98.8% 98.6% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system	Optional AC circuit breaker v Yes, AC fuses  98.8% 98.6% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power's , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume	Optional AC circuit breaker v Yes, v AC fuses  98.8% 98.6% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air wit 2,670 m³/h (fans: 1,230 W)	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m h temperature control (230 V phase + neutral p	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  bower supply) 5,340 m³/h (fans: 2,460 W)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	Optional AC circuit breaker v Yes, v AC fuses  98.8% 98.6% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  Forced air wit 2,670 m³/h (fans: 1,230 W)	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each pow 98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m h temperature control (230 V phase + neutral p	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m  bower supply) 5,340 m³/h (fans: 2,460 W)
Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Euroefficiency CEC Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission Marking EMC & Security standards	Optional AC circuit breaker v Yes, AC fuses  98.8% 98.6% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m Forced air wit 2,670 m³/h (fans: 1,230 W) <55 dB(A) at 4	Type 2 AC surge arresters with door control, motorized or remote trip (only with automatic disconnection (for each power s , AC short circuits and overloads (for each power 98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m h temperature control (230 V phase + neutral p 4,640 m³/h (fans: 2,050 W) m and <67 dB(A) at 1 m with fans working at m	98.8% 98.7% 98.1% 120 W  -20 °C to +65 °C 0 - 95% IP20 / IP54 3,000 m bower supply) 5,340 m³/h (fans: 2,460 W) naximum power




### SUN STORAGE PowerMax x Series 400 Vac

	500TL X400	750TL X400	1000TL X400
Input (DC) (Battery)			
Battery voltage range	636 - 820 V	636 - 820 V	636 - 820 V
Maximum current	900 A	1,350 A	1,800 A
Type of battery		Li-ion, lead, Ni-Cd	
Connection type	Connection to fuse holder copper bars, c	able entry from the bottom through D40 cabl	e glands (max. cable diameter: 40 mm)
Input protections			
Overvoltage protections	Тур	e 2 DC surge arresters (for each power stage	 e)
DC switch		Motorized DC switch with door control	
Other protections	Up to 16 pairs of DC	uses, DC insulation monitor with alarm, eme	ergency pushbutton
Output (AC)			
Rated power <sup>(1)</sup>	510 kW	764 kW	1,019 kW
Maximum current	736 A	1,104 A	1,472 A
Rated voltage	400 V IT System	400 V IT System	400 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1	1
Phi Cosine adjustable	Yes. Smax=510 kVA	Yes. Smax=764 kVA	Yes. Smax=1,019 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%	<3%
Connection type	Connection to fuse holder copper bars, c	able entry from the bottom through D40 cabl	e glands (max. cable diameter: 40 mm)
Output protections			
Overvoltage protections		Type 2 AC surge arresters	
AC breaker	Optional AC circuit breaker wit	h door control, motorized or remote trip (onl	y available for DCAC models)
Anti-islanding protection	Yes, wit	h automatic disconnection (for each power s	stage)
Other protections	AC fuses, A	C short circuits and overloads (for each pow	ver stage)
Features			
Maximum efficiency	98.8%	98.8%	98.8%
Euroefficiency	98.6%	98.6%	98.6%
CEC	98.1%	98.1%	98.1%
Stand-by consumption <sup>(4)</sup>	120 W	120 W	120 W
General Information			
Ambient temperature	-20 °C to +65 °C	-20 °C to +65 °C	-20 °C to +65 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP20 / IP54	IP20 / IP54	IP20 / IP54
Max. altitude <sup>(5)</sup>	3,000 m	3,000 m	3,000 m
Cooling system	Forced air with	emperature control (230 V phase + neutral	power supply)
Air volume	2,670 m³/h (fans: 1,230 W)	4,640 m³/h (fans: 2,050 W)	5,340 m³/h (fans: 2,460 W)
Noise emission	<55 dB(A) at 4 m	and <67 dB(A) at 1 m with fans working at r	maximum power
Marking		CE	
EMC & Security standards	EN 501	78, IEC 61000-6-2, IEC 61000-6-4, FCC Pa	art 15
EMC & Security standards  Grid connection standards		78, IEC 61000-6-2, IEC 61000-6-4, FCC Pa	



	375TL U X208 Outdoor	500TL U X208 Outdoor
Input (DC) (Battery)		
Battery voltage range	340 - 864 V	340 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion, I	ead, Ni-Cd
Connection type	Cable entry from the bottom through D40	) cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC surge arrest	ers (for each power stage)
DC switch		tch with door control
Other protections	DC insulation monitor with alarm.	. Door control. DC fuses are optional
Output (AC)		
Rated power <sup>(1)</sup>	375 kVA	500 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	208 V IT System	208 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
ricquericy	1	1
Phi Cosine <sup>(2)</sup>	*	Yes. Smax=500 kVA
	Vac Smay-375 kVA	
Phi Cosine adjustable	Yes. Smax=375 kVA	
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup>	<3%	<3%
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type	<3%	
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections	<3%  Connection to fuse holder copper bars, cable entry from the l	<3% bottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections	<3%  Connection to fuse holder copper bars, cable entry from the l	<3% bottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit break	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit breaks  Yes, with automatic discons	<3% bottom through D40 cable glands (max. cable diameter: 40 mn surge arresters er with door control nection (for each power stage)
Phi Cosine <sup>(2)</sup> Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection Other protections	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit breaks  Yes, with automatic discons	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit breaks  Yes, with automatic discons	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit breaks  Yes, with automatic discons	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency	<3%  Connection to fuse holder copper bars, cable entry from the I  Type 2 AC s  AC circuit break  Yes, with automatic discont	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)	<3% Connection to fuse holder copper bars, cable entry from the I Type 2 AC s AC circuit break Yes, with automatic discondance AC fuses, AC short circuits and 98.1%	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information	<3% Connection to fuse holder copper bars, cable entry from the I Type 2 AC s AC circuit break Yes, with automatic discondance AC fuses, AC short circuits and 98.1%	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature	<3% Connection to fuse holder copper bars, cable entry from the I Type 2 AC s AC circuit break Yes, with automatic discondance AC fuses, AC short circuits and 98.1% 90 W	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing)	<3% Connection to fuse holder copper bars, cable entry from the last of the last	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing) Protection class	<3% Connection to fuse holder copper bars, cable entry from the last of the last	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5)	<3% Connection to fuse holder copper bars, cable entry from the I Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.1% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system	<3% Connection to fuse holder copper bars, cable entry from the I Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.1% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume	Connection to fuse holder copper bars, cable entry from the last connection to fuse holder copper bars, cable entry from the last capture of th	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)  (230 V phase + neutral power supply)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume Noise emission	Connection to fuse holder copper bars, cable entry from the last connection to fuse holder copper bars, cable entry from the last capture of th	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)  (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA)
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection	Connection to fuse holder copper bars, cable entry from the last connection to fuse holder copper bars, cable entry from the last capture of th	<3% bottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage) d overloads (for each power stage)  98.1% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)  (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA) m with fans working at maximum power


**Notes:** <sup>(1)</sup> AC power for 122 °F (50 °C) ambient temperature. The output will be reduced at the rate of 1% for each 1 °F (0.56 °C) of increase. <sup>(2)</sup> For  $P_{out} > 25\%$  of the rated power <sup>(3)</sup> For  $P_{out} > 25\%$  of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(4)</sup> Consumption from the battery <sup>(5)</sup> Over 3,300 ft temperature for rated power 122 °F (50 °C) is reduced 2.42 °F for each 1,000 ft.



### SUN STORAGE PowerMax U x Series 275 Vac


	500TL U X275 Outdoor	660TL U X275 Outdoor
Input (DC) (Battery)		
Battery voltage range	442 - 864 V	442 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion, le	ead, Ni-Cd
Connection type	Cable entry from the bottom through D40	cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC curgo arrests	ers (for each power stage)
DC switch		ch with door control
Other protections		Door control. DC fuses are optional
	De insulation monitor with alarm.	Door control. De luses are optional
Output (AC)		
Rated power <sup>(1)</sup>	500 kVA	660 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	275 V IT System	275 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1
i ili Gosilic	Yes. Smax=500 kVA	Yes. Smax=660 kVA
	163. SIIIdA=300 KVA	
Phi Cosine adjustable THD (Total Harmonic Distortion)(3)	<3%	<3%
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup>	<3%	<3% oottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type	<3%	
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections	<3%  Connection to fuse holder copper bars, cable entry from the b	
Phi Cosine adjustable	<3%  Connection to fuse holder copper bars, cable entry from the b	oottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake	oottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconnections	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconnections	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature	<3% Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.3%  90 W	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)  98.3% 120 W
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency	Connection to fuse holder copper bars, cable entry from the bary from	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.3%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%	oottom through D40 cable glands (max. cable diameter: 40 mm  urge arresters er with door control section (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing)	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.3%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5)	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.3%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)	oottom through D40 cable glands (max. cable diameter: 40 mm  urge arresters er with door control section (for each power stage)  overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system	Connection to fuse holder copper bars, cable entry from the bary from	ottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control section (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume	<3%  Connection to fuse holder copper bars, cable entry from the b  Type 2 AC s  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.3%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control  37.96 ft³/s (fans: 1,300 VA)  <55 dB(A) at 4 m and <67 dB(A) at 1	oottom through D40 cable glands (max. cable diameter: 40 mm urge arresters er with door control nection (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)  (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume Noise emission	Connection to fuse holder copper bars, cable entry from the bary for the following forms and for the following forms and for the following for the foll	ottom through D40 cable glands (max. cable diameter: 40 mm  urge arresters er with door control ection (for each power stage) overloads (for each power stage)  98.3% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA) m with fans working at maximum power

Notas: <sup>(1)</sup> Potencia AC hasta 122 °F (50 °C) de temperatura ambiente. La potencia de salida se reducirá un 1% por cada 1 °F (0,56 °C) de incremento <sup>(2)</sup> Para Pac>25% de la potencia nominal <sup>(3)</sup> Para Pac>25% de la potencia nominal y tensión según IEC 61000-3-4 <sup>(4)</sup> Consumo desde baterías <sup>(5)</sup> Por encima de 3.300 ft, la temperatura para potencia nominal 122 °F (50 °C) se reduce a razón de 2,42 °F por cada 1.000 m adicionales.



	600TL U X330 Outdoor	800TL U X330 Outdoor
Input (DC) (Battery)		
Battery voltage range	526 - 864 V	526 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion, le	ead, Ni-Cd
Connection type	Cable entry from the bottom through D40	cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC surge arreste	ers (for each power stage)
DC switch	Motorized DC swit	tch with door control
Other protections	DC insulation monitor with alarm.	Door control. DC fuses are optional
Output (AC)		
Rated power <sup>(1)</sup>	600 kVA	800 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	330 V IT System	330 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
	307 60 HZ	1
Phi Cosine <sup>(2)</sup>		1
	Voc Smay=600 kV/A	Voc Smay-800 IVA
Phi Cosine adjustable	Yes. Smax=600 kVA	Yes. Smax=800 kVA
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup>	<3%	<3%
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type	<3%	
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections	<3%	<3%
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections	<3%  Connection to fuse holder copper bars, cable entry from the bars.	<3% oottom through D40 cable glands (max. cable diameter: 40 mm
Phi Cosine adjustable THD (Total Harmonic Distortion)(5) Connection type  Output protections  Overvoltage protections  AC breaker	<3%  Connection to fuse holder copper bars, cable entry from the to the following state of	<3%  oottom through D40 cable glands (max. cable diameter: 40 mm  ourge arresters  er with door control
Phi Cosine adjustable THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection	<3%  Connection to fuse holder copper bars, cable entry from the bars and the second s	<3%  cottom through D40 cable glands (max. cable diameter: 40 mm  curge arresters  er with door control  nection (for each power stage)
Phi Cosine (2) Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	<3%  Connection to fuse holder copper bars, cable entry from the bars and the second s	<3%  oottom through D40 cable glands (max. cable diameter: 40 mm  ourge arresters  er with door control
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection	<3%  Connection to fuse holder copper bars, cable entry from the bars and the second s	<3%  oottom through D40 cable glands (max. cable diameter: 40 mm  ourge arresters  er with door control hection (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features	<3%  Connection to fuse holder copper bars, cable entry from the bars and the second s	<3%  oottom through D40 cable glands (max. cable diameter: 40 mm  ourge arresters  er with door control hection (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	<3%  Connection to fuse holder copper bars, cable entry from the bars and the second s	<3%  cottom through D40 cable glands (max. cable diameter: 40 mm  curge arresters  er with door control nection (for each power stage)  overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection Other protections  Features  Maximum efficiency  Stand-by consumption(4)	<3% Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.5%	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm surge arresters  er with door control nection (for each power stage)  overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information	<3% Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.5%	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm surge arresters  er with door control nection (for each power stage)  overloads (for each power stage)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature	<3% Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.5% 90 W	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm surge arresters  er with door control nection (for each power stage)  overloads (for each power stage)  98.5%  120 W
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing)	Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discont AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C)	<3%  cottom through D40 cable glands (max. cable diameter: 40 mm  curge arresters er with door control election (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature  Relative humidity (non-condensing) Protection class	<3% Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%	<3%  cottom through D40 cable glands (max. cable diameter: 40 mm  curge arresters er with door control nection (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 -95%
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency	<3%  Connection to fuse holder copper bars, cable entry from the bars of the competition of the second seco	<3%  cottom through D40 cable glands (max. cable diameter: 40 mm  curge arresters er with door control nection (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4) General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system	<3%  Connection to fuse holder copper bars, cable entry from the bars of the competition of the second seco	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm surge arresters  er with door control section (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing) Protection class  Max. altitude(5) Cooling system Air volume	Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discont AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature control 37.96 ft³/s (fans: 1,300 VA)	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm surge arresters er with door control nection (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  (230 V phase + neutral power supply)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5)	Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic disconst AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature control 37.96 ft³/s (fans: 1,300 VA) <55 dB(A) at 4 m and <67 dB(A) at 1	<3%  pottom through D40 cable glands (max. cable diameter: 40 mm cable diameter: 40 mm cable arresters  per with door control flection (for each power stage)  overloads (for each power stage)  98.5%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 -95%  NEMA 3R  9,842 ft (3,000 m)  (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA)
Phi Cosine adjustable THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information  Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume Noise emission	Connection to fuse holder copper bars, cable entry from the bars. Type 2 AC s AC circuit breake Yes, with automatic discons AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature control 37.96 ft³/s (fans: 1,300 VA) <55 dB(A) at 4 m and <67 dB(A) at 1 CE	c3% cottom through D40 cable glands (max. cable diameter: 40 mm curge arresters er with door control nection (for each power stage) overloads (for each power stage) 98.5% 120 W -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9.842 ft (3,000 m) (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA) m with fans working at maximum power


**Notes:** <sup>(1)</sup> AC power for 122 °F (50 °C) ambient temperature. The output will be reduced at the rate of 1% for each 1 °F (0.56 °C) of increase. <sup>(2)</sup> For  $P_{out} > 25\%$  of the rated power <sup>(3)</sup> For  $P_{out} > 25\%$  of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(4)</sup> Consumption from the battery <sup>(5)</sup> Over 3,300 ft temperature for rated power 122 °F (50 °C) is reduced 2.42 °F for each 1,000 ft.



### SUN STORAGE PowerMax U x Series 360 Vac


	660TL U X360 Outdoor	880TL U X360 Outdoor
Input (DC) (Battery)		
Battery voltage range	572 - 864 V	572 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion, le	ad, Ni-Cd
Connection type	Cable entry from the bottom through D40	cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC surge arreste	rs (for each power stage)
DC switch		ch with door control
Other protections	DC insulation monitor with alarm.	Door control. DC fuses are optional
Output (AC)		
Rated power <sup>(1)</sup>	660 kVA	880 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	360 V IT System	360 V IT System
Frequency	50 / 60 Hz	50 / F1 System 50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1
505116	Yes. Smax=660 kVA	Yes. Smax=880 kVA
Phi Cosine adjustable	ics. Silidx=UUU KVA	
Phi Cosine adjustable  THD (Total Harmonic Dietortion)(3)	~3°/	
THD (Total Harmonic Distortion)(3)	<3%	<3%
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type		<3% ottom through D40 cable glands (max. cable diameter: 40 mm)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type		
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections	Connection to fuse holder copper bars, cable entry from the b	
	Connection to fuse holder copper bars, cable entry from the b	ottom through D40 cable glands (max. cable diameter: 40 mm)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC so  AC circuit breake	ottom through D40 cable glands (max. cable diameter: 40 mm
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC so  AC circuit breake  Yes, with automatic disconn	ottom through D40 cable glands (max. cable diameter: 40 mm urge arresters r with door control
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC so  AC circuit breake  Yes, with automatic disconn	ottom through D40 cable glands (max. cable diameter: 40 mm.  urge arresters r with door control ection (for each power stage)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC so  AC circuit breake  Yes, with automatic disconn	ottom through D40 cable glands (max. cable diameter: 40 mm.  urge arresters r with door control ection (for each power stage)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC st  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	ottom through D40 cable glands (max. cable diameter: 40 mm)  urge arresters  r with door control  ection (for each power stage)  overloads (for each power stage)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup>	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC si  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	ottom through D40 cable glands (max. cable diameter: 40 mm) urge arresters r with door control ection (for each power stage) overloads (for each power stage)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC si  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and	ottom through D40 cable glands (max. cable diameter: 40 mm) urge arresters r with door control ection (for each power stage) overloads (for each power stage)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC si  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W	ottom through D40 cable glands (max. cable diameter: 40 mm)  urge arresters  r with door control ection (for each power stage)  overloads (for each power stage)  98.6%  120 W
THD (Total Harmonic Distortion)(a) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC st  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)	ottom through D40 cable glands (max. cable diameter: 40 mm, urge arresters r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)	Connection to fuse holder copper bars, cable entry from the b  Type 2 AC st  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%	ottom through D40 cable glands (max. cable diameter: 40 mm, urge arresters r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup>	Type 2 AC so AC circuit breake Yes, with automatic disconn AC fuses, AC short circuits and  98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)	ottom through D40 cable glands (max. cable diameter: 40 mm, urge arresters r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system	Type 2 AC so AC circuit breake Yes, with automatic disconn AC fuses, AC short circuits and  98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)	ottom through D40 cable glands (max. cable diameter: 40 mm)  urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class	Type 2 AC st  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control of 37.96 ft³/s (fans: 1,300 VA)	ottom through D40 cable glands (max. cable diameter: 40 mm,  urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
THD (Total Harmonic Distortion) <sup>(3)</sup> Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	Type 2 AC si  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control of 37.96 ft ³/s (fans: 1,300 VA)  <55 dB(A) at 4 m and <67 dB(A) at 1	ottom through D40 cable glands (max. cable diameter: 40 mm, urge arresters r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA)
THD (Total Harmonic Distortion)(3) Connection type  Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume	Type 2 AC si  AC circuit breake  Yes, with automatic disconn  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control is 37.96 ft²/s (fans: 1,300 VA)  <55 dB(A) at 4 m and <67 dB(A) at 1  CE,	ottom through D40 cable glands (max. cable diameter: 40 mm,  urge arresters  r with door control ection (for each power stage)  overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%  NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA)  m with fans working at maximum power

**Notas:** <sup>(1)</sup> Potencia AC hasta 122 °F (50 °C) de temperatura ambiente. La potencia de salida se reducirá un 1% por cada 1 °F (0,56 °C) de incremento <sup>(2)</sup> Para PAc>25% de la potencia nominal <sup>(3)</sup> Para PAc>25% de la potencia nominal y tensión según IEC 61000-3-4 <sup>(4)</sup> Consumo desde baterías <sup>(5)</sup> Por encima de 3.300 ft, la temperatura para potencia nominal 122 °F (50 °C) se reduce a razón de 2,42 °F por cada 1.000 m adicionales.



	750TL U X400 Outdoor	1000TL U X400 Outdoor
Input (DC) (Battery)		
Battery voltage range	635 - 864 V	635 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion,	lead, Ni-Cd
Connection type	Cable entry from the bottom through D40	Cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC surge arrest	ters (for each power stage)
DC switch	Motorized DC sw	itch with door control
Other protections	DC insulation monitor with alarm	. Door control. DC fuses are optional
Output (AC)		
Rated power <sup>(1)</sup>	765 kVA	1,020 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	400 V IT System	400 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1
Phi Cosine adjustable	Yes. Smax=765 kVA	Yes. Smax=1,020 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%
Connection type		bottom through D40 cable glands (max. cable diameter: 40 mm
Output protections		
	Type 2 AC	surge arresters
Overvoltage protections		surge arresters er with door control
Overvoltage protections AC breaker	AC circuit break	
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	AC circuit break Yes, with automatic discon	er with door control
Overvoltage protections AC breaker Anti-islanding protection	AC circuit break Yes, with automatic discon	er with door control nection (for each power stage)
Overvoltage protections AC breaker Anti-islanding protection Other protections Features	AC circuit break Yes, with automatic discon	er with door control nection (for each power stage)
Overvoltage protections AC breaker Anti-islanding protection Other protections	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and	er with door control nection (for each power stage) d overloads (for each power stage)
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup>	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5%	er with door control nection (for each power stage) d overloads (for each power stage) 98.6%
Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5%	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C)
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%
Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature Relative humidity (non-condensing) Protection class	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)  Protection class  Max. altitude <sup>(5)</sup>	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)  Protection class  Max. altitude <sup>(5)</sup> Cooling system	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature contro	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)  Protection class  Max. altitude <sup>(5)</sup> Cooling system  Air volume	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature contro 37.96 ft³/s (fans: 1,300 VA)	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) I (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA)
Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature contro 37.96 ft³/s (fans: 1,300 VA) <55 dB(A) at 4 m and <67 dB(A) at 1	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) I (230 V phase + neutral power supply) 45.56 ft ³/s (fans: 1,500 VA) I m with fans working at maximum power
Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency  Stand-by consumption <sup>(4)</sup> General Information  Ambient temperature  Relative humidity (non-condensing)  Protection class  Max. altitude <sup>(5)</sup>	AC circuit break Yes, with automatic discon AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature contro 37.96 ft³/s (fans: 1,300 VA) <55 dB(A) at 4 m and <67 dB(A) at 1	er with door control nection (for each power stage) d overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) I (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA)


**Notes:** <sup>(1)</sup> AC power for 122 °F (50 °C) ambient temperature. The output will be reduced at the rate of 1% for each 1 °F (0.56 °C) of increase. <sup>(2)</sup> For  $P_{out} > 25\%$  of the rated power <sup>(3)</sup> For  $P_{out} > 25\%$  of the rated power and voltage in accordance with IEC 61000-3-4 <sup>(4)</sup> Consumption from the battery <sup>(5)</sup> Over 3,300 ft temperature for rated power 122 °F (50 °C) is reduced 2.42 °F for each 1,000 ft.



### SUN STORAGE PowerMax U x Series 420 Vac

	805TL U X420 Outdoor	
Input (DC) (Battery)		
Battery voltage range	666 - 864 V	666 - 864 V
Maximum current	1,170 A	1,560 A
Type of battery	Li-ion, le	ad, Ni-Cd
Connection type	Cable entry from the bottom through D40 (	cable glands (max. cable diameter: 40 mm)
Power Blocks	3	4
Input protections		
Overvoltage protections	Type 2 DC surge arreste	ers (for each power stage)
DC switch	Motorized DC switch	ch with door control
Other protections	DC insulation monitor with alarm.	Door control. DC fuses are optional
Output (AC)		
Rated power <sup>(1)</sup>	803 kVA	1,070 kVA
Maximum current	1,050 A	1,400 A
Rated voltage	420 V IT System	420 V IT System
Frequency	50 / 60 Hz	50 / 60 Hz
Phi Cosine <sup>(2)</sup>	1	1
Phi Cosine adjustable	Yes. Smax=803 kVA	Yes. Smax=1,070 kVA
THD (Total Harmonic Distortion)(3)	<3%	<3%
	Connection to fuse holder copper bars, cable entry from the be	ottom through DAO cable glands (may, cable diameter, AO mm)
Connection type	connection to tase holder copper bars, cable entry from the bi	ottom through b40 cable glands (max. cable diameter. 40 mm)
	Connection to tase holder copper sais, cause cities more the sa	ottom umough b40 cable glands (max. cable diameter. 40 mm)
Output protections		
Output protections Overvoltage protections	Type 2 AC su	urge arresters
Output protections Overvoltage protections AC breaker Anti-islanding protection	Type 2 AC st AC circuit breaker	urge arresters r with door control
Output protections Overvoltage protections AC breaker Anti-islanding protection	Type 2 AC su AC circuit breaker Yes, with automatic disconne	urge arresters r with door control ection (for each power stage)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections	Type 2 AC su AC circuit breaker Yes, with automatic disconne	urge arresters r with door control
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features	Type 2 AC su AC circuit breake Yes, with automatic disconn AC fuses, AC short circuits and	urge arresters  r with door control  ection (for each power stage)  overloads (for each power stage)
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency	Type 2 AC su AC circuit breaker Yes, with automatic disconn- AC fuses, AC short circuits and	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features	Type 2 AC su AC circuit breake Yes, with automatic disconn AC fuses, AC short circuits and	urge arresters  r with door control  ection (for each power stage)  overloads (for each power stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features  Maximum efficiency Stand-by consumption <sup>(4)</sup>	Type 2 AC su AC circuit breaker Yes, with automatic disconn- AC fuses, AC short circuits and	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections Features Maximum efficiency Stand-by consumption(4) General Information	Type 2 AC su AC circuit breaker Yes, with automatic disconn- AC fuses, AC short circuits and	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature	Type 2 AC su AC circuit breaker Yes, with automatic disconne AC fuses, AC short circuits and 98.5% 90 W	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing)	Type 2 AC su AC circuit breaker Yes, with automatic disconne AC fuses, AC short circuits and 98.5% 90 W -4 °F to 149 °F (-20 °C to 65 °C)	urge arresters r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class	Type 2 AC st AC circuit breaker Yes, with automatic disconne AC fuses, AC short circuits and 98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95%
Output protections  Overvoltage protections  AC breaker  Anti-islanding protection  Other protections  Features  Maximum efficiency	Type 2 AC su  AC circuit breaker  Yes, with automatic disconne  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup>	Type 2 AC su  AC circuit breaker  Yes, with automatic disconne  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)	urge arresters  r with door control ection (for each power stage)  overloads (for each power stage)  98.6%  120 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system	Type 2 AC st.  AC circuit breaker  Yes, with automatic disconner  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control (37.96 ft³/s (fans: 1,300 VA)	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption(4)  General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude(5) Cooling system Air volume	Type 2 AC st AC circuit breaker  Yes, with automatic disconnous AC fuses, AC short circuits and  98.5% 90 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) Forced air with temperature control (37.96 ft³/s (fans: 1,300 VA)  <55 dB(A) at 4 m and <67 dB(A) at 1 m	urge arresters  r with door control ection (for each power stage) overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m) (230 V phase + neutral power supply) 45.56 ft³/s (fans: 1,500 VA)
Output protections Overvoltage protections AC breaker Anti-islanding protection Other protections  Features Maximum efficiency Stand-by consumption <sup>(4)</sup> General Information Ambient temperature Relative humidity (non-condensing) Protection class Max. altitude <sup>(5)</sup> Cooling system Air volume Noise emission	Type 2 AC st  AC circuit breaker  Yes, with automatic disconne  AC fuses, AC short circuits and  98.5%  90 W  -4 °F to 149 °F (-20 °C to 65 °C)  0 - 95%  NEMA 3R  9,842 ft (3,000 m)  Forced air with temperature control (  37.96 ft³/s (fans: 1,300 VA)  <55 dB(A) at 4 m and <67 dB(A) at 1 to CE,	urge arresters  r with door control ection (for each power stage)  overloads (for each power stage)  98.6% 120 W  -4 °F to 149 °F (-20 °C to 65 °C) 0 - 95% NEMA 3R 9,842 ft (3,000 m)  (230 V phase + neutral power supply)  45.56 ft³/s (fans: 1,500 VA)  m with fans working at maximum power

**Notas:** <sup>(1)</sup> Potencia AC hasta 122 °F (50 °C) de temperatura ambiente. La potencia de salida se reducirá un 1% por cada 1 °F (0,56 °C) de incremento <sup>(2)</sup> Para Pac>25% de la potencia nominal <sup>(3)</sup> Para Pac>25% de la potencia nominal y tensión según IEC 61000-3-4 <sup>(4)</sup> Consumo desde baterías <sup>(5)</sup> Por encima de 3.300 ft, la temperatura para potencia nominal 122 °F (50 °C) se reduce a razón de 2,42 °F por cada 1.000 m adicionales.



### INGECON SUN STORAGE Box



A Plug & Play solution for energy storage

### All-in-one battery box

All the necessary equipment is integrated in a single enclosure, facilitating the installation and supply. The metallic pregalvanized enclosure is suitable for indoor and outdoor applications.

### Maximum security

The system includes an overload and short-circuit protection, by means of magneto-thermic breaker. This equipment is supplied with the batteries already integrated and ready to use.

### **Greatest compatibility**

The battery box features a pre-charge logic to direct connect with INGECON® SUN STORAGE 1Play converters, obtaining a totally compatible range of products from Ingeteam.

#### Modular system

It is possible to connect together many battery boxes increasing the total capacity of the whole storage system. Both series (suggested) and parallel compositions are supported. Thanks to its modularity, the original schema is scalable and it can be adapted to suit the requirements of any kind of project.

### **Battery Technologies**

The INGECON® SUN STORAGE Box can be equipped with two different battery solutions:

### OPZV-GEL BLOCK

OPzV Block batteries belong to the highest EUROBAT classification for maintenance-free lead-acid batteries: >12 years long life.

- Capacity: 110Ah C10 (52 kg) or 167Ah C10 (74 kg).
- Sealed and maintenance-free operation.
- Maximum temperature up to 45 °C.
- Up to 3000 cycles at 50% DOD.
- Optimal solution for deep cycle applications.

### AGM BATTERIES

AGM series batteries designed for deep discharge application, with special chemical formula for plates active paste material, slightly stronger electrolyte and low temperature design, which can withstand repeated deep cyclic application.

- Capacity: 95Ah C10 (30 kg) or 150Ah C10 (37 kg).
- Sealed and maintenance-free operation.
- Maximum temperature up to 40 °C.
- Up to 2000 cycles at 30% DOD.
- Low self-discharge characteristic.

### PROTECTIONS


- Magneto-thermal protection.
- DC pre-charge.

## Configuration with OPzV-GEL Block


	Nominal	Nominal	Size	Weight	Applic	ations	
	Capacity	Voltage	(LxWxH)		Single-phase	Three-phase	
Small enclosure							
	6.6 kWh	60 V	600x800x850 mm	290 kg	✓	-	
	7.9 kWh	72 V	600x800x850 mm	342 kg	✓	-	
Medium enclosure							
	14 kWh	84 V	800x1200x850 mm	549 kg	✓	✓	
	16 kWh	96 V	800x1200x850 mm	624 kg	✓	✓	
	18 kWh	108 V	800x1200x850 mm	698 kg	✓	✓	
Large enclosure							
	20 kWh	120 V	1000x1200x850 mm	772 kg	✓	✓	
	22 kWh	132 V	1000x1200x850 mm	846 kg	✓	✓	
	24 kWh	144 V	1000x1200x850 mm	920 kg	<b>√</b>	✓	

## Configurations AGM Battery


	Nominal	Nominal	Size	Weight	Applic	ations	
	Capacity	Voltage	(LxWxH)		Single-phase	Three-phase	
Small enclosure							
	5.7 kWh	60 V	600x800x850 mm	180 kg	✓	-	
	6.8 kWh	72 V	600x800x850 mm	210 kg	✓	-	
	9 kWh	60 V	600x800x850 mm	215 kg	✓	-	
	10.8 kWh	72 V	600x800x850 mm	252 kg	✓	-	
Medium enclosure							
	12.6 kWh	84 V	800x1200x850 mm	289 kg	✓	✓	
	14.4 kWh	96 V	800x1200x850 mm	326 kg	✓	✓	
	16.2 kWh	108 V	800x1200x850 mm	363 kg	✓	✓	
	18 kWh	120 V	800x1200x850 mm	400 kg	✓	✓	
	19.8 kWh	132 V	800x1200x850 mm	437 kg	✓	✓	
	21.6 kWh	144 V	800x1200x850 mm	474 kg	✓	✓	
Large enclosure							
	23.4 kWh	156 V	1000x1200x850 mm	511 kg	✓	✓	
	25.2 kWh	168 V	1000x1200x850 mm	548 kg	✓	✓	
	27 kWh	180 V	1000x1200x850 mm	585 kg	✓	✓	
	28.8 kWh	192 V	1000x1200x850 mm	622 kg	✓	✓	



**Small enclosure**Single-phase applications




**Medium enclosure**Single-phase and three-phase applications



Large enclosure Single-phase and three-phase applications





INGECON INVIND

MICRO-WIND INVERTERS

## INGECON IIWIND

With transformer



### 2.5 / 3.3 / 5

The best option for managing and isolating small micro-wind systems

## Maximum energy extraction at all times

Designed to control and convert the energy captured and deliver it to a single phase grid. Adaptable to suit a wide range of wind turbines from 2.5 to 5 kW.

### Complete micro-wind system safety

Featuring the communication and monitoring interfaces required for local and remote system surveillance.

### Wind turbine adaptable

Possibility of adjusting the maximum power point tracking (optimal speed of rotation) by means of a Power-Voltage curve of up to 15 points.

### Maximun efficiency

MPP control of the system, and energy conversion for delivery to the grid. It can be installed either by itself or together with the INGECON® µWIND Interface.

### Easy to install

Fast on connectors for the DC and AC sides, and RS-485 communications. No additional items required. Manual grid disconnection feature.

### Ease of maintenance

Internal datalogger for up to 3 months data storage, which can be controlled from either a remote PC or on-site from the inverter front keypad. LED status and alarm indicators and LCD screen. Useful life of more than 20 years.

### Software included

Included at no extra cost are the INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor smartphone version for monitoring and recording the inverter data over the internet.

## Standard 5 year warranty, extendable for up to 25 years




### PROTECTIONS

- Galvanic isolation between the DC and AC side.
- Reverse polarity.
- Input and output overvoltage.
- Output short-circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic. disconnection.

### OPTIONAL ACCESSORIES

- DC switch.
- Inter-inverter communication via Ethernet or Bluetooth.
- Modem for GSM / GPRS remote communication.
- Potential free contact for insulation fault indication (by default) or inverter connected to the grid (optional).

### Size and weight (mm)




	2.5	3.3	5
Input (DC)			
Voltage range MPP	45 - 450 V	45 - 450 V	40 - 550 V
Maximum voltage(1)	40 - 550 V	40 - 550 V	40 - 550 V
Maximum current	16 A	22 A	33 A
MPPT	1	1	1
Output (AC)			
Rated power <sup>(2)</sup>	2.5 kW	3.3 kW	5 kW
Maximum current	12 A	16 A	22 A
Rated voltage	230 V	230 V	230 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1
Phi Cosine adjustable	Yes. Smax=2.7 kVA	Yes. Smax=3.7 kVA	Yes. Smax=5.5 kVA
THD	3%	3%	3%
Efficiency			
Maximum efficiency	94.7%	95%	95.1%
Euroefficiency	93.8%	94%	94.3%
General Information			
Stand-by consumption	<10 W	<10 W	<10 W
Ambient temperature	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%
Protection class	IP65	IP65	IP65

Compliance with standards: EN50178, EN61000-6-2, EN61000-6-3, EN62109-1-2, VDE-AR-N 4105, G83/1-1, CEI 0-21, CEI 11-20, RD1699/2011, VDE0126-1-1, EN50438, CE Mark

Notes: (1) Never exceed 550 V. With no auxiliary supply, the minimum start-up voltage is 80 V (2) AC Power for 45 °C ambient temperature. For each °C of increase, the output power will be reduced at the rate of 1.8%.

## Wiring diagram without INGECON® µWIND Interface



## Wiring diagram with INGECON® µWIND Interface



## INGECON INVIND

### **Transformerless**



### 2.5TL / 3TL / 3.3TL / 3.68TL / 3.8TL / 4.6TL / 5TL / 6TL

The best option for managing small micro-wind systems

### Maximum energy extraction at all times

Designed to control and convert the energy captured and deliver it to a single phase grid. Adaptable to suit a wide range of wind turbines from 2.5 to 6 kW.

### Complete micro-wind system safety

Featuring the communication and monitoring interfaces required for local and remote system surveillance.

### Wind turbine adaptable

Possibility of adjusting the maximum power point tracking (optimal speed of rotation) by means of a Power-Voltage curve of up to 15 points.

### Maximun efficiency

MPP control of the system, and energy conversion for delivery to the grid. It can be installed either by itself or together with the INGECON® µWIND Interface.

### Easy to install

Fast on connectors for the DC and AC sides, and RS-485 communications. No additional items required. Manual grid disconnection feature.

### Ease of maintenance

Internal datalogger for up to 3 months data storage, which can be controlled from either a remote PC or on-site from the inverter front keypad. LED status and alarm indicators and LCD screen. Useful life of more than 20 years.

### Software included

Included at no extra cost are the INGECON® SUN Manager, INGECON® SUN Monitor and its iSun Monitor smartphone version for monitoring and recording the inverter data over the internet.

## Standard 5 year warranty, extendable for up to 25 years

#### PROTECTIONS

- Reverse polarity.
- Input and output overvoltage.
- Output short circuits and overloads.
- Insulation failures.
- Anti-islanding with automatic shutdown.

#### OPTIONAL ACCESSORIES

- DC switch.
- Inter-inverter communication via Ethernet or Bluetooth.
- Modem for GSM / GPRS remote communication.
- Potential free contact for insulation fault indication (by default) or inverter connected to the grid (optional).

### Size and weight (mm)



**2.5TL / 3TL** 18.3 kg.

**3.3TL / 3.68TL** 19.7 kg.

**4.6TL / 5TL / 6TL** 23.3 kg.

**7.5TL / 8.2TL / 8.6TL / 10TL** 25.2 kg.




	2.5TL	3TL	3.3TL	3.68TL	3.8TL	4.6TL	5TL	6TL
Input (DC)								
Voltage range MPP	45 - 450 V	45 - 450 V	45 - 450 V	45 - 450 V	45 - 450 V	45 - 450 V	45 - 450 V	45 - 450 V
Maximum voltage <sup>(1)</sup>	40 - 550 V	40 - 550 V	40 - 550 V	40 - 550 V	40 - 550 V	40 - 550 V	40 - 550 V	40 - 550 V
Maximum current	16 A	16 A	22 A	22 A	33 A	33 A	33 A	33 A
MPPT	1	1	1	1	1	1	1	1
Output (AC)								
Rated power <sup>(2)</sup>	2.5 kW	3 kW	3.3 kW	3.68 kW	3.8 kW	4.6 kW	5 kW	6 kW
Maximum current	13 A	13.5 A	17 A	17 A	18.8 A	24.2 A	25.5 A	26.2 A
Rated voltage	230 V	230 V	230 V	230 V	230 V	230 V	230 V	230 V
Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Phi Cosine	1	1	1	1	1	1	1	1
Phi Cosine adjustable	Yes. Smax=2.7 kVA	Yes. Smax=3 kVA	Yes. Smax=3.7 kVA	Yes. Smax=3.68 kVA	Yes. Smax=3.9 kVA	Yes. Smax=5 kVA	Yes. Smax=5.5 kVA	Yes. Smax=6 kVA
THD	3%	3%	3%	3%	3%	3%	3%	3%
Efficiency								
Maximum efficiency	96.6%	96.6%	96.8%	96.8%	97%	97%	97%	97%
Euroefficiency	95%	95.1%	95.2%	95.2%	95.6%	96%	96.1%	96.1%
General Information								
Stand-by consumption	<10 W	<10 W	<10 W	<10 W	<10 W	<10 W	<10 W	<10 W
Ambient temperature	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C	-20 °C to +70 °C
Relative humidity (non-condensing)	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%	0 - 95%
Protection class	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65

Compliance with standards: EN50178, EN61000-6-2, EN61000-6-3, EN62109-1-2, VDE-AR-N 4105, G83/1-1, CEI 0-21, CEI 0-16, RD1699/2011, VDE0126-1-1, EN50438, CE Mark

Notes: (1) Never exceed 550 V. With no auxiliary supply, the minimum start-up voltage is 80 V (2) AC Power for 45 °C ambient temperature. For each °C of increase, the output power will be reduced at the rate of 1.8%.

## Wiring diagram without INGECON® µWIND Interface



## Wiring diagram with INGECON® µWIND Interface



### INGECON PWIND Interface



System protection and AC / DC conversion in a single unit

## Maximum protection and safety for the wind turbine and inverter

The INGECON® µWind Interface provides overpower and overvoltage protection for the inverter whilst also protecting the wind turbine against overspeeding through a PWM progressive braking system with a high capacity discharge resistor. It extends the wind turbine operating range to include high wind speeds, for increased productivity.

It is also equipped with interlocking contactors to short-circuit and block the wind turbine.

### **Greater control features**

Remote control and additional monitoring of meteorological variables. Measurement of the wind turbine speed of rotation. Remote operation of the wind turbine start-stop system.

## Suitable for wind turbines with AC or DC outputs

AC / DC conversion between the wind turbine output and the inverter input. Also valid for DC wind turbines.

## Standard 5 year warranty, extendable for up to 25 years

### PROTECTIONS

- Against overvoltage.
- Against overspeeding.
- Against power boosts.
- Braking system and positive latching (HW resistor).


#### OPTIONAL

- Two 0 24 V digital inputs.
- Two digital outputs, of type NO potential free contact and with an opening capacity of 250 V / 2 A.


	Interface	
Input values		
Power range	2.5 - 18 kW	
Maximum AC voltage	450 Vrms	
Maximum AC current	23 Arms	
Maximum DC voltage	600 V	
Maximum DC current	30 A	
Wind turbine speed capture range <sup>(1)</sup>	0 - 600 rpm	
Analog inputs		
Number	2	
Туре	0 - 10 V / 0 - 20 mA (configurable)	
General information		
Communication system	RS-485 and bus CAN	
Remote control system	Through Ethernet and PC application	

Compliance with standards: EN 50178, EN61000-6-2, EN61000-6-3, CE Mark

Notes: (1) The maximum limit will depend on the electrical characteristics of the wind turbine.



### Wiring diagram







INGECON EMS

**ENERGY MANAGEMENT SOLUTIONS** 

## **Ingeteam Smart House**

Complete self-consumption and energy management solutions for homes and industries

#### SYSTEM HIGHLIGHTS

- Savings in energy consumption.
- Optimisation and maximum use of own production
- Shorter investment pay-back times for the renewable system.
- Customised consumption strategy adapted to the specific circumstances of each installation.
- Easy installation.

MINIMUM ELEMENTS FOR THE CONNECTION DIAGRAM

- INGECON® EMS Manager.
- INGECON® EMS Power Meter.
- Renewable generation (INGECON® SUN and / or INGECON® μWIND).

ADDITIONAL ELEMENTS

- INGECON® SUN STORAGE 1Play.

- 1 PV panel
- 2 Wind turbine
- 3 Public grid
- 4 Monitoring software INGECON® EMS Tools
- 5 Energy manager INGECON® EMS Manager
- 6 Loads
- 7 Radiator
- 8 Boiler
- 9 Battery inverter INGECON® SUN STORAGE 1Play
- 10 Wind converter INGECON® μWIND
- 11 Protection system INGECON® µWIND Interface
- 12 PV inverter INGECON® SUN 1Play
- 13 Charging station INGEREV® GARAGE
- 14 Two-way meter INGECON® EMS Power Meter
- 15 Electric vehicle
- 16 Batteries

DC

AC



#### Load control

For those plants in which generation is not in line with demand, the self-consumption ratio can be increased, including load control in order to activate consumption at times of peak production. The INGECON® EMS Manager manages the connection and disconnection of controlable loads and the energy production, based on the generating data obtained from the power converters and from the total plant consumption.

The INGECON® EMS Manager allows you to select the times for the connection and disconnection of the various loads coupled to the system, such as electric boilers, radiators, pumps, electric vehicles, etc. by adjusting total plant consumption to the renewable energy production. The INGECON® EMS Manager can be configured so that zero energy is delivered to the grid.

#### Maximum energy control

Thanks to the INGECON® EMS Power Meter, the system continuously measures the two-way power flow between the public grid and the plant. In addition, this advanced wattmeter makes it

possible to decouple the system from the grid, to become a stand-alone system. For this purpose, a battery system needs to be coupled to the plant.

#### Energy storage system

This system supports the inclusion of a battery system, controlled through the INGECON® SUN STORAGE 1Play two-way inverter, making it ossible to operate in back-up mode, in the event of power failures. Furthermore, this system offers a wider range of possibilities for a more efficient management of own energy production.




#### Maximum self-consumption

As can be seen in the graph, the implementation of a system of this type makes it possible to achieve high levels of self-consumption, given the fact that it is possible to store the energy produced for use at peak consumption times. The INGECON® EMS Manager always seeks to minimize grid consumption, with the subsequent reduction in the user's electricity bill.

#### Fast investment pay-back

In addition the plant payback period is much shorter, due to the fact that the excess energy produced during the middle of the day (when energy consumption is lower) can be delivered to the grid.



- Injection into the grid
- Consumption from the grid
- Battery load
- Consumption from batteries
- Self-consumed power

#### INGECON EMS Manager



The most efficient energy management solution for self-consumption

This innovative energy management solution developed by Ingeteam Power Technology, for the domestic, commercial and industrial markets, allows for increased self-consumption, by matching energy production and consumption.

#### The smart energy manager

The INGECON® EMS Manager controls the energy generation from renewable sources, based on the power production data obtained from the power converters and on total system consumption. Furthermore, it allows the connection and disconnection of controllable loads. The INGECON® EMS Manager implements management strategies based on the different devices connected to the system, making it possible to plan how and when to consume the power produced. The INGECON® EMS Manager is designed to optimise any electricity system in terms of energy usage and cost savings.

#### Consumption management

Consumption management is the basis of a truly effective energy management system. Thanks to the potential-free outputs it is possible to determine the connection and disconnection times for the various loads coupled to the

system. This allows for the connection of electric boilers, radiators, pumps, electric vehicles etc, constantly adapting total system consumption to the renewable energy produced.


## Maximum control of the energy consumed

The system energy manager constantly controls the amount of energy exchanged with the public grid. Thanks to the potential-free outputs it is possible the system constantly meters the two-way power flow between the grid and the system. This information is transferred in real time to the INGECON® EMS Manager. Furthermore, the INGECON® EMS Power Meter allows the system to be decoupled from the grid, to become an off-grid network. In order to do so, the INGECON® Home battery inverter is required, associated with a storage system.

#### **Continuous communication**

The INGECON® EMS Manager also acts as a communications centre, constantly exchanging information with the INGECON® EMS Power Meter and the system converters. It also sends orders to the INGECON® EMS Load Control through Bluetooth or RS-485 to control the loads.

	EMS Manager
Power supply	
Input voltage	100 - 240 Vac
Nominal frequency	50 / 60 Hz
Power consumption	5 - 8 W
Connectivity	
Ethernet	1
RS-485	1
USB	1
Potential free outputs	2 x (250 V, 6 A)
Communication interface with other equipment	
Ingeteam inverters	RS-485, Ethernet, Bluetooth
Monitoring systems	Ethernet, GPRS
INGECON® EMS Power Meter	RS-485
INGECON® EMS Load Control	Bluetooth





## **Solutions for Self-consumption**

Self-consumption allows the consumer to have his own energy supply by installing a renewable energy source (photovoltaic or wind) on his own installation.

The new solution for energy management is called INGECON® EMS Manager. Thanks to this device, self-consumption rates of 100% are achieved during the central hours of the day. The power excess can be then injected into the grid, obtaining an economic benefit and shortening payback times. These two graphics show the consumption, injection and self-consumption profiles of a residential photovoltaic installation.

#### When do I need it?


The INGECON® EMS Manager is necessary when:

- it is needed to monitor the installation,
- it is wanted to include an energy storage system,
- there are several inverters,
- it is a three-phase installation,
- a load management is desired,
- it is needed to combine different renewable energy sources (PV and micro-wind).


#### How does it work?


This equipment analyses the power flow at the connection point of the installation through a wattmeter and it determines the power instructions for the operation of the PV inverters. This power instruction is sent in a linear way between 0 and 100% of the inverter's rated power, so that the manager can adjust the energy production to match the instruction with total precision.

#### Standard 3 year warranty









#### **INGECON EMS Plant Controller**



## PV plant control system

The INGECON® EMS Plant Controller helps the grid operator to predict the PV plant performance and to guarantee the quality and stability of the electricity supply.

#### Maximum PV plant control

An advanced control algorithm combined with a fast and efficient communications system, with response times of less than one second, permit precise control of the active and reactive power delivered by the plant to the grid.

The INGECON® EMS Plant Controller controls the PV inverters, ensuring compliance with the grid operator's requirements at the PV plant connection point. It is also possible to manage energy storage systems and other devices such as diesel generators, through the use of INGECON® SUN STORAGE PowerMax inverters.

This is a flexible system that can easily be adapted to the needs and configurations of each particular plant, whilst complying with the country-specific standards and regulations.

#### Description of the complete system

A PV plant with plant controller typically consists of:

- INGECON® EMS Plant Controller: Comprising two basic systems: measurement and control. It can additionally incorporate a communication channel with the grid operator in order to receive the operating setpoints.
- INGECON® SUN PV inverters connected to the PV array.
- INGECON® SUN STORAGE Power-Max battery inverters connected to the energy storage system. Only when energy storage systems are required to cover situations in which the solar radiation is too low or to provide energy for night-time use.
- SCADA, plant monitoring system.
- Communications network: Connecting the INGECON® EMS Plant Controller with the different inverters, transmitting the operating setpoints and monitoring the status of the equipment.

## Continuous communication with all devices

The INGECON® EMS Plant Controller permits the dynamic modification of the


grid operator setpoints. For this purpose, a number of communication protocols are incorporated such as Modbus TCP / RTU, IEC 61850, IEC 60870-5-101 and IEC 60870-5-104. Likewise, it is also possible to add digital and analogue I / O modules in order to extend the communication capabilities with third-party devices.

Furthermore, the INGECON® EMS Plant Controller permits communication with the plant SCADA to transmit the connection point data.

#### Operating mode

For the control, the INGECON® EMS Plant Controller takes the following data:

- Active power, reactive power, voltage and frequency at the connection point, provided by the integrated measurement unit.
- Grid operator requirements. To establish references for parameters such as voltage at the point of connection, active and reactive power, power ramps, active power reserve, etc. These requirements can be predetermined either by the grid operator or by the plant operator or dynamically modified through an external setpoint.



- Instantaneous active and reactive power values from the various inverters.
- With all this data, the control unit can determine the operating setpoints for each inverter integrated into the system and transmit the setpoints through the communications network.

#### Active power control

Some of the active power control functions that can be implemented in the INGECON® EMS Plant Controller are:

- Continuous control of the power at the output. To control the PV plant power output, limiting it to the desired value.
- Regulation of the active power variation rate. To control the power generated by the inverters, ensuring that the variation in the plant power output conforms to the established setpoint. So as to control variations in power shortfalls, it is necessary to add energy storage systems and INGECON® SUN STORAGE Power-Max inverters to the plant in order to deliver energy to the system when no PV resources are available.

- Power regulation in the event of a frequency variation.
- Active power reserve. The INGECON®
   EMS Plant Controller incorporates a
   patented innovative control strate gy (PCT/ES 2008/000560) to gua rantee an active power reserve with
   no need to include storage systems
   (depending on the availability of the
   PV resource).

#### Reactive power control

Some of the reactive power control functions that can be implemented in the INGECON® EMS Plant Controller are:

- Regulation of the reactive power output. To control the plant reactive power output, adjusting it to a given reference, including the possibility of providing reactive power at night time.
- Regulation of the power factor at the connection point.
- Voltage control The INGECON® EMS
   Plant Controller controller makes it
   possible to regulate the plant voltage
   at the connection point.


#### ITEMS INCLUDED

- PLC.
- Power meter.
- Communications switch.
- Power supply.
- Protections.

#### SYSTEM HIGHLIGHTS

- Frequency regulation.
- Active power reserve regulation.
- Constant active power level at the output.
- Active power ramp regulation.
- Reactive power control.
- Power factor control.
- Voltage control.





#### Evolution of the price of Diesel and Solar systems



#### **Diesel-PV Solutions**

Integration of photovoltaics into diesel grids

The power generation from diesel gensets plays a key role for industrial companies and rural communities all over the world, especially in remote regions without a good grid infrastructure. They permit to create simple off-grid networks with a moderate initial investment.

However these applications have some disadvantages. First, the grid they create is totally dependent on diesel, which is a non-renewable and scarce energy source. On the other hand, the energy generated is expensive due to high prices of fuel and the difficulty of supplying and storing it. Furthermore, diesel-based systems have to face constant price increases and high OPEX -Operational Expenditures- directly related to the use of fuel.


Apart from that,  ${\rm CO}_2$  emissions increase with the use of gensets. This fact has to be taken into account, not only as a moral exigence towards global warming, but also because it could entail governmental fines, affecting operational expenditures.


PV system prices have fallen in the last years, allowing nowadays generating energy to a more competitive cost compared to fuel. In regions with high solar irradiation levels and expensive fuel prices, PV systems can be amortized in less than four years. Furthermore, PV plants require little maintenance and they can be configured according to specific energy demands. Moreover, photovoltaics do not produce CO<sub>2</sub> emissions.


The integration of PV systems into diesel grids offers large industries and rural communities a way of saving fuel with a natural and renewable resource. This can be achieved by adding INGECON® SUN PV inverters and Ingeteam's Diesel-PV controllers to the diesel grid. The use of photovoltaics reduces the energy generated by the gensets and, therefore, the fuel consumption.

Challenges of Diesel-PV integration:

- To guarantee a minimum load for the generators, to ensure longer engine life.
- To protect against reverse power, in case of a total load disconnection.
- To ensure stability against irradiance variations due to cloud shading.







#### A scalable system to satisfy every project needs


Ingeteam's Diesel-PV controllers monitor the power flows of the system and manage the PV injected to the diesel grid in order to guarantee the system stability, allowing achieving up to a 70 percent of PV penetration compared to the total diesel capacity.


Diesel systems can be classified in two main types depending on the generators operation: continuous operation diesel systems or on-demand diesel systems. Continuous operation diesel systems are based on one or more gensets operating permanently, no matter the load level. On-demand diesel systems fea-

ture an external controller that selects the number of gensets that will operate depending on the load requirement.


Ingeteam has developed different solutions for each system type that can be easily implemented in both new and already existing diesel systems.

#### Continuous operation diesel systems






#### On-demand diesel systems



## Continuous operation diesel systems

Schema with INGECON® EMS Manager



#### Operating mode

In those cases in which one or more gensets are operating permanently to satisfy the energy demand, the INGECON® EMS Manager can be used to control the PV inverters.

Photovoltaic inverters inject current to the diesel grid, being detected by the genset as a load reduction. INGECON® EMS Manager will control the energy production of the PV inverters depending on the energy required by the loads. Moreover, it will also act as a communications center, as it enables to remotely access all the system's relevant data.

#### Elements of the Diesel-PV Solution:

- INGECON® SUN PV inverters
- INGECON® EMS Manager
- Wattmeter

#### System features:

- Minimum diesel load
   It guarantees that the diesel generator does not operate under a minimum load level, in order to ensure a longer engine life.
- Reverse power protection
   It avoids a power flow from the inverter to the genset, for example, in the event of a total load disconnection.
- Stability against irradiance variations
   In continuous operation diesel systems, stability against irradiance variation it is guaranteed by the spinning reserve of the genset, previously sized for the maximum possible load.

#### Monitoring


The installation can be monitored by using the software INGECON® EMS Tools. Also, an internal datalogger allows to store more than 30 days historical data.

#### Load control

The INGECON® EMS Manager allows switching loads on when the genset load level is low and there is a PV generation surplus.

#### On-demand diesel systems

Schema with INGECON® EMS Plant Controller



#### Operating mode

In those cases in which an external diesel controller determines the number of operating gensets, the INGECON® EMS Plant Controller is used to guarantee a proper PV integration in the diesel grid.

Photovoltaic inverters inject current to the diesel grid, being detected by the genset as a load reduction. INGECON® EMS Plant Controller monitors the genset units, obtaining which ones are operating as well as their load level. This information is used to determine the maximum power that the solar inverters can supply in order to guarantee the system stability, i.e. in a cloud shading event.

The monitoring process of the genset units can be made by a Power Meter device or by an Ethernet Modbus / TCP straight from the genset (if available). The general system can be monitored via SCADA or dedicated software.

The INGECON® EMS Plant Controller features an auto-learning algorithm that allows maximizing the PV energy injected and minimizing the number of connections and disconnections of the gensets.

#### Elements of the Diesel-PV Solution:

- INGECON® SUN PV inverters
- INGECON® EMS Plant Controller (PLC, communication switch, power supply and protections).
- Power Meter Unit (Wattmeter, communication switch, power supply and protections).

#### System features:


- Minimum diesel load

It guarantees that the diesel generators do not operate under a minimum load level, in order to ensure a longer engine life.

- Reverse power protection
   It avoids a power flow from the inverter to the genset, for example, in the event of a total load disconnection.
- Stability against irradiance variations INGECON® EMS Plant Controller limits the PV output power to guarantee that the available spinning reserve is enough to meet the energy demand in a cloud shading event.
- Monitoring
   The installation can be monitored by using a SCADA.
- Reactive Power Support from the PV inverters, for those installations with high reactive power consumption.

## On-demand diesel systems


Schema with INGECON® EMS Plant Controller and energy storage



<sup>\*</sup> Not supplied by Ingeteam.

#### A battery bank adds many advantages

The addition of an energy storage system allows increasing the PV penetration. In this case, the spinning reserve is not needed to absorb the irradiance variations in the plant, because the batteries supply the necessary power when PV generation decreases due to passing clouds.



#### Operating mode

Photovoltaic inverters inject current to the diesel grid, being detected by the genset as a load reduction. INGECON® EMS Plant Controller monitors the loads and determines the maximum PV power that can be injected into the diesel grid. Furthermore, in a cloud shading event, the INGECON® EMS Plant Controller together with the battery inverters INGECON® SUN STORAGE Power-Max, reduce the output power with a established ramp rate, that will allow to the diesel controller to switch-on the required generators.

In these installations, the storage system has to provide the energy needed for the genset start-up.

The system can be monitored via SCA-DA or dedicated software.

The INGECON® EMS Plant Controller features an auto-learning algorithm that

allows maximizing the PV energy injected and minimizing the number of connections and disconnections of the gensets.

#### Elements of the Diesel-PV Solution:

- INGECON® SUN PV inverters
- INGECON® EMS Plant Controller (PLC, communication switch, power supply and protections).
- INGECON® SUN STORAGE Power-Max battery inverters
- Power Meter Unit (Wattmeter, communication switch, power supply and protections).

#### System features:

Minimum diesel generation. It guarantees that the diesel generators provide a minimum energy level, in order to guarantee the grid stability when load steps happen, or the loads are unbalanced or they present current harmonics.


- Reverse power protection
   It avoids a power flow from the inver-
- ter to the genset, for example, in the event of a total load disconnection.
- Stability against irradiance variations INGECON® EMS Plant Controller together with the battery inverters INGECON® SUN STORAGE Power-Max, guarantee system stability in a cloud shading event.
- Monitoring
   The installation can be monitored by using a SCADA.
- Reactive Power Support from the PV inverters, for those installations with high reactive power consumption.

OPTIONAL

- Public grid power flow management (if available).







Accessories

MULTI-OPTIONS FOR PV PLANT CONTROL AND MONITORING



#### Communications centre

The INGECON® SUN ComBox enables remote communication with the inverters in a number of standards, thanks to its versatility to jointly process data coming from Ethernet, RS-485, GSM / GPRS, radio or Bluetooth networks.

The datalogger is able to store meteorological information and power setpoint data for one month.

## Measurement of meteorological variables

For the measurement of meteorological variables, the INGECON® SUN ComBox

analogue input data storage and reading functions are far more accurate than those of standard cards.

The following inputs are available:

- 2 inputs for PT100.
- 4 inputs 0..10 V or 0..20 mA.

#### Media converter


For added versatility when selecting the means of communication with the plant.

#### Power setpoint control

Due to the need to improve the grid integration of the energy generated by renewable sources, the new grid regulations

now require these sources to help maintain the stability of the power grid, as is already demanded of conventional generation.

With 4 digital inputs and control software especially developed by Ingeteam Power Technology, the INGECON® SUN ComBox manages, for the entire plant, all the power setpoints established by the grid operators.



## INGECON SUN WeatherBox



#### Maximum control over the PV system parameters

INGECON® SUN WeatherBox offers the possibility of storing meteorological data for up to 30 days.

#### **Outdoor installation**

The INGECON® SUN WeatherBox has been especially designed for outdoor installation, with a protection rating of IP65. Sensors can be connected to measure a number of parameters such

as module irradiation, wind speed, module temperature, etc., for optimum PV plant control.

#### Easy communication


INGECON® SUN WeatherBox acts as one more slave in the communication network, in addition to the PV inverters. Communication with the INGECON® SUN WeatherBox can be established either by RS-485 cable or with the Bluetooth wireless version.


#### Meteorological values measurement


The WeatherBox integrates the functions of measuring and storing data received from analog inputs with a greater precision than normal boards.

The following inputs are available:

- 2 inputs for PT100.
- 4 inputs 0..10 V o 0..20 mA.







#### INGECON SUN Communication



A range of PC-to-Inverter communication options

Ingeteam offers its customers the very latest technology in communication boards. Thanks to the hardware developed by the Ingeteam engineers, it is possible to establish local communication with the PV inverters and / or remote communication through a PC. In this way, all the PV system variables (operating parameters and historical data files) can be monitored simply and conveniently. This communication can be made through a number of boards that can be incorporated into the inverter.

All these boards feature a unified connector in order to facilitate the connection of any of them in every inverter from Ingeteam's product range. **RS-485** communication is the easiest and fastest way to interconnect a number of inverters and is supplied as standard in many inverter families. For those inverters that do not feature standard RS-485 communication, Ingeteam can optionally supply an RS-485 board to provide this.

Mention should be made of communication via **Ethernet**, for which Ingeteam has two different boards. Both include conversion to RS-485. One is an **Ethernet-RS485** communication gateway whilst the other also adds the possibility of inverter communication via Modbus-TCP.

One of Ingeteam's latest developments in communication boards is the **Wi-Fi** board, for wireless communication, and which also includes conversion to RS-485.

For its part, the **Bluetooth** board offers the possibility of creating communication networks between various inverters, in order to establish wireless contact with a PC located in the vicinity. This inverter network can also be connected via Bluetooth with the INGECON® SUN ComBox in order to communicate with any PC over the Internet. This board includes conversion to RS-485.

Finally, the **GSM / GPRS** board permits remote communication with the inverters through a GSM / GPRS network and also includes conversion to RS-485.

#### Wireless communications designed by Ingeteam



#### Communication boards by Ingeteam



## INGECON SUN Manager



#### PV plant monitoring software

PC software operating in a Windows® graphical environment for PV plant management and monitoring.

Integration of single phase and three phase inverters and string control devices in a single software package.

Communication through different ways: RS-485, Ethernet and modem.

This software can be downloaded, free of charge, from the **www.ingeteam.com** website.

#### SOFTWARE FEATURES

- Individual configuration of each PV plant inverter.
- On-line display of the inverter internal variables.
- Display of all the plant inverters on a single screen.
- Multi-PV plant management from a single PC.
- Historical data capture and disc storage possibility.
- Data log display in a number of graph or table formats.
- Data storage in XML format.
- Modem configuration for receiving SMS alarm messages.
- Available in English,
   Spanish, German, French,
   Italian, Czech and
   Chinese.
- Configuration of the INGECON® EMS Manager.

#### ON-SCREEN DATA DISPLAY

Full-screen data display, with customisable wallpaper, for viewing the most important plant parameters:

- Accumulated energy.
- Instantaneous power.
- Irradiance\*.
- Module temperature\*.
- Ambient temperature\*.
- Wind speed\*.
- \* If a ComBox with the appropriate sensors has been installed.

#### VARIABLES VIEWABLE ON-LINE

List of the variables that are viewable on-line, stored in the inverter memory:

- Total energy delivered to the grid.
- Total time in operating status.
- Total number of grid connections.
- Total number of errors.
- Alarm status.
- Internal operating status.
- Solar panel voltage.
- Solar panel current and power.
- Output current and power to the grid.
- Phi cosine.
- Phi sine positive / negative.
- Grid voltage.
- Grid frequency.
- Actual date and time.

## INGECON SUN Monitor



#### Web portal for PV plant access

With the INGECON® SUN Monitor software, PV plant data can be accessed from any PC with an Internet connection (www.ingeconsunmonitor.com). Its ease of access facilitates owner, installer or promoter plant control. This software provides information on the PV

plant status and production, either in list and graphic format or through an e-mailed production report. This software has been designed to facilitate owner, installer or promoter plant control, providing information on the PV plant status in the form of lists and graphs,

whilst there is also the possibility of receiving an e-mailed production report. Data are recorded and stored throughout the useful life of the inverter. An iSun Monitor iPhone application is available at the App Store.









## INGECON SUN Planner



#### PV plant dimensioning

The new INGECON® SUN Planner software offers the possibility of optimally customising each specific project. In just three fast, simple steps users can correctly dimension a PV plant, by selecting the type of PV module and

INGECON® SUN inverter that best suits the system, using a database comprising an extensive range of different modules for each manufacturer. There is also the option of selecting different parameters for the plant, for customized dimensioning, to meet the end customer's requirements. Registration and access are free of charge and can be quickly and easily made

through one of the following websites: www.ingeconsunplanner.com or www.ingeteam.com, to quickly enjoy all the advantages offered by this software tool from any web browser, IPod, IPhone, IPad or Android tablet.

#### Plant configuration in just 3 simple steps




Step 1
Select the INGECON® SUN
Inverter

Step 2
Select the PV panel

**Step 3**Dimensioning of the PV plant completed

## INGECON EMS Tools



#### Software to configure and monitor self-consumption systems

The INGECON® EMS Tools software is the PC application for the monitoring and configuration of self-consumption systems governed by the INGECON® EMS Manager.

This tool seeks to offer users a software close to the Plug & Play philosophy: a very simple, intuitive interface with regard to installation and operation.

This program can be downloaded free of charge from our website: **www.ingeteam.com.** Compatible with 32 and 64 bit configurations, the software requires the Microsoft .NET Framework 4.0 platform (normally included as part of the operating system) and Windows XP or higher.

#### Operating modes

- On-line mode: a direct connection is established with the INGECON® EMS Manager device with all functionalities available to the user. Communication with the INGECON® EMS Manager can either be made remotely through the Ingeteam servers or directly by TCP / IP using the device IP address.
- Off-line mode: users can view the parameters configured and the historical data previously downloaded.

THE SOFTWARE ALLOWS USERS TO

- Configure the INGECON® EMS Manager.
- Individually configure each PV plant inverter and other devices.
- Control the loads.
- View the plant wiring diagrams and communications network.
- View the production data.
- Start-up and manage the various PV plants from a PC.
- Data capture, save a file to the disc and get a graphic display of the historical data.

Configuration of the system in 3 simple steps



Step 1
Installation of the software

Step 2
Configuration of the INGECON® EMS Manager

**Step 3**Plant configuration and start-up

## INGECON SUN SCADA



## Remote operation and SCADA

Remote control enables real time operation and supervision of the PV installations and is an essential tool for guaranteeing the highest level of availability.

It is adapted to the requirements of each installation and can incorporate

new features based on modular SCADA architecture.

It is scalable and flexible thanks to its OPC based client / server architecture.

The Remote Controller can integrate the Substation and any other device that

may be remotely controlled. It is compatible with a multitude of protocols and supports (ADSL, RDSI, GSM, GPRS, Internet, fibre optics, radio, microwaves, and satellite).

#### **Remote Communication**

In the case that signals not coming from the inverter should be implemented in the SCADA, such as the status of automatics, temperatures, etc., communication remotes would need to be installed in each of the enclosures. In the case of INGECON® SUN PowerMax Inverters, this remote would need to be installed in the AC and auxiliary services enclosure.

#### SOME POSSIBLE COMMUNICATION PROTOCOLS

- Interbus-S.
- Profibus-DP.
- CAN.
- OPC DA & OPC XML Data Client and Server.
- IEC 61850 Client and Server.
- IEC 61400-25 Client and Server.
- IEC 60870-5- 101/104 102 Master-Slave.
- DNP 3.0 Master-Slave.
- Modbus ASCII-RTU/TCP Master-Slave.
- Other protocols can be done through a Client / Server architecture based on OPC.

## INGECON SUN StringControl



#### String current monitoring

The INGECON® SUN String Control is a device for measuring each PV generator string current and detecting defective string currents through INGECON® SUN Manager software.

String currents can be monitored through the RS-485 communication cards, GSM / GPRS, Ethernet or Wi-Fi.

It is easy to mount and is suitable for outdoor installations.

It is particularly recommended for three phase inverters.

#### PROTECTIONS

- Individual string fuse protection.
- IP65 protection for outdoor installation.

#### OPTIONAL

- SMS alarm functionality for any faulty currents.
- DC overvoltage dischargers.
- DC switch.

String Control 160	String Control 320
16	32*
16	16
10 Adc	20 Adc
160 Adc	320 Adc
16	16
1,000 Vdc	1,000 Vdc
PV connectors type 4	PV connectors type 4
PG M55 (up to 300 mm <sup>2</sup> )	PG M55 (up to 2 x 300 mm <sup>2</sup> )
RS-485, GSM / GPRS, Ethernet, Wi-Fi, fibre optics card	RS-485, GSM / GPRS, Ethernet, Wi-Fi, fibre optics card
-20 °C to +65 °C	-20 °C to +65 °C
IP65	IP65
PG M16 (35 mm²)	PG M16 (35 mm²)
	16  10 Adc  160 Adc  160 Adc  16  1,000 Vdc  PV connectors type 4  PG M55 (up to 300 mm²)  RS-485, GSM / GPRS, Ethernet, Wi-Fi, fibre optics card  -20 °C to +65 °C  IP65

\* Type 4 PV connectors with T connection excluded from supply.

# Size and weight (mm) 15 kg.




#### INTEGRATED AND OPTIONAL ACCESSORIES

	SUN 1Play TL M	SUN 1Play HF	SUN 1Play TL U M	SUN 1Play HF U	SUN Lite TL	SUN 3Play TL	SUN 3Play TL M	SUN 3Play TL U M	SUN Power	SUN Power TL	SUN Power U Outdoor	SUN Power TL U Outdoor	SUN PowerMax TL B	SUN PowerMax TL M	SUN PowerMax TL X	SUN PowerMax TL U X
Protections	요그	ાડ 	ี รี่ ⊏	공표	าร	าร	요드	요다	าร	ાડ -	รัก	್ಷ⊏	요ㅋ	ธุ	요ㅋ	ร =
	_	1		1				_	,		,		_			
Galvanic isolation DC-AC  Reverse Polarity		-	-		-	_	-	_	1	-	1					-
Input overvoltage	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	✓	<b>√</b>	<b>√</b>	<b>√</b>	<b>V</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>
(type 2 surge arresters)	_	-	_	_	-	0	0	0	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>
Output overvoltage (type 2 surge arresters)	-	-	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
Output shortcircuits and overloads	✓	1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Insultaion failure DC	✓	1	✓	✓	✓	✓	✓	<b>√</b>	✓	✓	✓	✓	✓	✓	✓	✓
Insultaion failure AC	-	-	-	-	-	-	-	-	-	-	-	-	0	0	0	-
Anti-islanding with automatic shutdown	✓	1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DC fuse-holders	-	-	-	-	-	0	0	0	✓	✓	✓	✓	0	✓	✓	✓
DC fuses	-	-	-	-	-	0	0	0	✓	✓	✓	✓	0	0	0	0
DC switch	0	0	0	0	0	0	0	0	✓	✓	✓	✓	✓	✓	✓	✓
AC circuit breaker	-	-	-	-	-	-	-	_	✓	✓	✓	✓	0	0	0	<b>√</b> 3
Accessories																
Multicontact 4	✓	1	✓	✓	✓	0	0	-	-	-	-	-	-	-	-	_
Potential-free contact	✓	1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Self-consumption kit	0	0	0	0	0	0	0	0	-	-	-	-	-	-	-	-
Self-consumption kit with EMS Manager	0	0	0	0	0	0	0	0	0	0	-	-	-	-	-	-
Heating kit (-30°C/-22°F)	0	0	0	0	0	-	-	-	0	0	0	0	0	0	0	0
Grounding kit	-	0	-	0	-	-	-	-	0	0	-	-	0	-	0	-
Sync kit	-	-	-	-	-	-	-	-	-	<b>O</b> 1	-	0	<b>√</b> 1	$\checkmark$ 1	$\sqrt{1}$	✓
Night-time power supply	0	0	0	0	0	0	0	0	0	0	0	0	✓	0	0	<b>√</b>
AC wattmete	-	-	-	-	-	-	-	-	-	-	-	-	0	0	0	0
DC string current measurement	-	-	-	-	-	0	0	-	-	_	_	-	0	0	0	0
Blown fuse detector	-	-	-	-	-	-	-	-	-	-	-	-	-	0	0	✓
Firmware updatable via SD card	✓	✓	✓	✓	-	✓	✓	✓	-	-	-	-	-	-	-	-
Firmware updatable via communication	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Low voltage ride-through capability	✓	1	1	1	1	1	1	1	0	0	0	0	1	0	0	0
Digital inputs	✓	✓	✓	✓	✓	✓	✓	✓	-	-	-	-	-	-	-	-
Communications																
RS-485	0	0	0	0	✓	✓	✓	<b>√</b>	✓	0	0	0	✓	✓	✓	1
Ethernet	0	0	0	0	0	0	0	0	✓	0	0	0	✓	0	0	0
GPRS	0	0	0	0	0	0	0	0	✓	0	0	0	-	0	0	0
USB	✓	✓	✓	✓	-	-	-	-	-	-	-	-	-	-	-	-
Wi-Fi	0	0	0	0	0	0	0	0	-	-	-	-	-	-	-	-
Bluetooth	0	0	0	0	0	0	0	0	-	-	-	-	-	-	-	-
Plant power control <sup>(2)</sup>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Software																
INGECON® SUN Manager for plant management	✓	<b>√</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
INGECON® SUN Monitor for plant monitoring	✓	✓	✓	✓	✓	✓	✓	<b>✓</b>	✓	✓	✓	✓	<b>√</b>	✓	✓	<b>✓</b>

**Notes:** <sup>(1)</sup> For inter-inverter synchronization, request a quote <sup>(2)</sup> Equipment prepared. An external control is required <sup>(3)</sup> AC switch, not circuit breaker <sup>(4)</sup> For other output options, please contact Ingeteam <sup>(5)</sup> It also integrates digital outputs and analogue inputs.

	STORAGE 1Play	STORAGE 1Play TL	STORAGE Power	STORAGE PowerMax TL X	STORAGE PowerMax TL U X	STORAGE PowerMax TL B	μWind	µWind TL	μWind Interface	EMS Manager	EMS Plant Controller	SUN ComBox	SUN WeatherBox	SUN StringControl
Protections														
Galvanic isolation DC-AC	<b>√</b>	_	1	_	_	_	1	_	_	_	_	_	_	_
Reverse Polarity	_	_	_	_	1	_	1	1	1	_	_	_	_	_
Input overvoltage (type 2 surge arresters)	_	_	0	<b>√</b>	<b>√</b>	✓	-	-	<b>√</b>	_	_	_	_	0
Output overvoltage (type 2 surge arresters)	✓	1	1	1	1	1	-	_	✓	_	_	-	_	_
Output shortcircuits and overloads	1	1	1	1	1	<b>√</b>	1	1	_	_	_	_	_	_
Insultaion failure DC	<b>√</b>	<b>√</b>	1	<b>V</b>	<b>√</b>	<b>√</b>	1	<b>√</b>	_	_	_	_	_	_
Insultaion failure AC	_	_	_	0	_	_	_	_	_	_	_	_	_	_
	_	_				_	,	/						
Anti-islanding with automatic shutdown			_	<b>√</b>	<b>√</b>		<b>√</b>	<b>√</b>	_	_	_	_	_	-
DC fuse-holders	_	_	0	<b>√</b>	<b>√</b>	-	-	0	_	_	_	_	_	<b>√</b>
DC fuses	-	_	0	0	0	0	-	0	-	_	-	_	-	<b>√</b>
DC switch	0	0	✓	<b>√</b>	✓	<b>√</b>	0	0	-	-	-	-	-	0
AC circuit breaker	-	-	✓	0	<b>√</b> 3	0	-	-	_	-	-	-	-	-
Accessories														
Multicontact 4	0	0	_	-	_	✓	✓	✓	_	-	-	-	-	<b>√</b> 4
Potential-free contact	1	1	1	1	1	✓	✓	1	_	-	-	-	-	-
Self-consumption kit	0	0	_	-	-	_	0	0	-	-	-	-	_	_
Self-consumption kit with EMS Manager	0	0	_	_	_	_	0	0	_	_	-	_	-	_
Heating kit (-30°C/-22°F)	_	_	0	0	0	0	0	0	_	_	0	_	_	_
Grounding kit	_	_	0	0	_	0	_	_	_	_	_	_	_	_
Sync kit	_	_	_	<b>√</b> 1	1	_	_	_	_	_	_	_	_	_
Night-time power supply	0	0	1	0	<b>√</b>	1	0	0	0	_	_	_	_	_
AC wattmete	U	-	0		0	0	-	-	0	_				
				0		_					<b>√</b>	_	_	-
DC string current measurement	_			0	0		_	_			_		_	<b>√</b>
Blown fuse detector	_	_	_	0	<b>√</b>	_	_	_	_	_	_	_	_	_
Firmware updatable via SD card	_	_	_	_	_	-	-	_	_	_	-	_	_	_
Firmware updatable via communication	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Low voltage ride-through capability	-	_	_	0	0	_	✓	✓	_	-	0	-	-	-
Digital inputs	✓	1	✓	-	_	✓	✓	✓	✓	_	<b>√</b> 5	✓	-	-
Communications														
RS-485	0	0	✓	✓	✓	0	✓	✓	✓	✓	0	✓	✓	0
Ethernet	0	0	0	0	0	<b>√</b>	0	0	0	1	<b>√</b>	✓	<b>√</b>	0
GPRS	0	0	0	0	0	0	0	0	0	0	-	0	-	0
USB	-	-	-	-	-	-	_	_	_	0	<b>√</b>	1	-	-
Wi-Fi	_	_	_	_	_	_	0	0	0	_	0	0	_	_
Bluetooth	_	_	_	_	_	_	0	0	0	_	_	0		0
Plant power control <sup>(2)</sup>	_	_		1	1	_	<b>√</b>	<b>√</b>	✓			,		
Software				<b>V</b>	<b>√</b>		<b>V</b>	<b>√</b>	<b>√</b>	_	_			
INGECON® SUN Manager	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	-	<b>√</b>	<b>√</b>	1
for plant management  INGECON® SUN Monitor	<b>√</b>	1	1	<b>√</b>	1	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	_	_	_	_	1
for plant monitoring														





INGECON SUN Training

THE BEST TRAINING PLATFORM FOR PROFESSIONALS

## INGECON SUN Training



Training for professionals in the PV sector

INGECON® SUN Training is a training platform directed at facilitating the work of all those professionals whose job involves handling the Ingeteam PV inverters.

At INGECON® SUN Training, we aim to share our knowledge and experience in the belief that this is the best way for all of us to progress together.

What's more, the site is intended to serve as a meeting point for all those professionals working in the PV sector, whatever their area of specialisation.

#### More info at:

www.ingeconsuntraining.com training.energy@ingeteam.com TRAINING COURSES

#### On-site courses

General and specific, commercial and technical; free and subsidised. Get more information on the training available at: **www.ingeconsuntraining.com** 

#### **Tailored courses**

Tell us your needs and we'll design a customised training program. We can even give the course at your facilities.

#### Live webinars

You can also do a course from your own home or office. You simply need a computer, Internet connection and a microphone headset.

ADDITIONAL SUPPORT

#### Visits

You're welcome to visit our facilities. We'd like you to get to know our equipment right from its origins.

#### **Audiovisual material**

Our website offers access to videos, presentations and technical documentation with relevant information on technological developments, technical support etc.

#### **FAQ**

The FAQ section on our website allows you to check out the answers to the main doubts raised by our customers. You even have the opportunity to ask us about any other doubts or question you may have.

#### **Technical articles**

Keep up-to-date with technical articles on the very latest technological developments achieved by our team of engineers.





#### **Efficiency**

Our goal is to ensure that our inverters deliver the highest energy efficiency rates possible. We'll help you to get the most out of our products.

#### Certification

Our training courses are certified by the most reputed solar education and renewable energy training organizations worldwide.

#### **Flexibility**

We can adapt to suit your own particular needs and circumstances, with customised courses, either online or face-to-face, depending on your own specific requirements.

#### **Excellence**

Our training personnel are involved in R&D work, and are therefore always upto-date with the very latest PV technology.







Service partner

Becoming an INGECON® SUN Service Partner is fast and easy. You simply need to attend a special course and meet the minimum requirements.

You will get a certification which licences you to perform specific handling and manipulation tasks on the INGECON® SUN equipment.

#### BENEFITS OF BEING A SERVICE PARTNER

- Technical support 24 hours a day, 365 days a year.
- Access to specific technical documentation.
- Specific training courses.
- Immediate availability of spares.
- Authorisation to use our logo on your communications.
- Marketing and Merchandising support.
- Worldwide authorised installers.





# SERVICE AND MAINTENANCE



## CHOOSE FROM A COMPLETE PORTFOLIO OF SERVICE SOLUTIONS

At Ingeteam, as well as the design and manufacture of PV plant Inverters, we are also concerned with providing an excellent maintenance service to guarantee an increased equipment lifespan and maximum performance.

Ingeteam offers solutions for any PV system configuration, ensuring that our inverters maintain their robustness, reliability and efficiency. Our concept is based on providing a tailored, flexible service. Combine the modules as you please, to ensure that all your maintenance requirements are covered.

#### Select your combination



Extended warranty



Commissioning



Online supervision



Maintenance



Diagnostics and repair



Spares guarantee



**Availability** 

#### Ingeteam Service

We offer you 7 service modules to cover each and every PV inverter maintenance requirement. Select those modules that are best suited to your system and combine them to ensure a reliable operation.



#### Services offered after-sales

## **Extended Warranty:**

- A full guarantee for your inverter.
- Repair of parts under warranty.
- Return expenses included.
- Diagnostic and advisory services.

#### Commissioning:

- Commissioning based on the manufacturer's protocol.
- Assistance in planning the commissioning process.
- Troubleshooting during commissioning.

## Online Supervision:

- Support service through our call centre.
- Pro-active service from the control centre.
- Regular monitoring reports.

## Maintenance:

- All costs included.
- Manufacturer's protocol.
- Flexibility when selecting the type of maintenance.

### Diagnostics and Repair:

- On-site assistance at your plant.
- Assistance within 24 hours1.

## Spares guarantee:

- Guaranteed stock for the contract duration.
- Shipping costs included.
- Supply in less than 48 hours<sup>2</sup>.
- Diagnostic and advisory service.

## Availability:

- Compensation for loss of the established availability.

#### **Ingeteam Service Centers**

Ingeteam maintains strategic centres covering the entire country so as to provide rapid efficient service for any of our customers' solar energy installations.

Our international brand expansion makes us capable of offering these services any place in the world.

<sup>&</sup>lt;sup>1</sup>Depending on the contract conditions.

<sup>&</sup>lt;sup>2</sup> For the countries selected in the map.

# TAILORED SOLUTIONS

As well as designing and manufacturing the power and control electronics for PV plants and other renewable energy generation systems, Ingeteam has also been concerned with offering the best possible maintenance service to ensure optimum plant performance and continuous operation.





# Maximum performance

The PV plant must achieve maximum performance, with as few interruptions as possible. Get the most from your PV plant through correct maintenance.

At Ingeteam, efficiency is a core value.

Right from commissioning and startup, and throughout the entire useful life of your plant, we can offer you an all-inclusive maintenance service that is the result of our experience, assurance and specialization. Our secret is based on proactivity.

A key factor that sets us apart from the rest.

# Guaranteed optimization

In the knowledge that it is essential to get the best performance out of the PV plant at the lowest operating cost, the maintenance service provided by Ingeteam allows you to adjust and lower your operating costs, for greater profitability.

Our strategy is based on an optimum all-inclusive maintenance policy, to ensure the continuous operation of your plant.

# Risk-free financial returns

The solvency, technical capability and financial standing of a sector leader, such as Ingeteam, with its extensive track record and experience, represent a real guarantee when considering plant profitability.

With its expertise in maintenance engineering, on-going investment in R&D&I and commitment to developing optimum programs that adequately cover the existing risk, Ingeteam is ideally positioned to work alongside its customers.

Optimum plant maintenance also signifies maintaining the business risk well under control.





# Spares always on hand

A smooth running supply chain and the continuous availability of all those parts required for your PV system, are both key aspects in our all-inclusive maintenance service. You can rest assured in the knowledge that we will handle all the logistics to ensure the rapid replacement of any equipment parts. We offer continuous status monitoring and information reporting so as to anticipate your needs.

Ingeteam can always guarantee the supply of parts, regardless of the system technology.

# True adaptability

The solutions provided by Ingeteam for any type of PV system, guarantee reliability and maximum efficiency.

Tell us what you want, and we will tailor our service to meet your requirements, right from the contract conclusion stage, to offer you the best possible service at all times.









# OVER 4 GW INSTALLED

# EQUIPPED WITH INGECON® SUN INVERTERS

Ingeteam boasts a long, proven track record in the industrial and energy sectors, which stretches back to 1972, clearly demonstrating the company's ongoing policy of technological development. In the nineties, Ingeteam became more involved in the development of electrical and control systems specific to the renewable energies sector; this was initially directed at the wind power and hydroelectric sectors and then, from 2001 onwards, our company broadened its scope to encompass the PV solar energy sector as well.

Since then we have provided our customers with more than 4 GW of power with INGECON® SUN pho-

tovoltaic inverters. This confirms Ingeteam as one of the world leaders in the PV sector.

At Ingeteam, we have extensive experience in the design and supply of on-grid inverters for power ratings ranging from 2.5 to 1000 kW, for large-scale PV plants. We also specialize in the design and manufacture of highpower battery inverters for stand-alone installations, having supplied this type of inverters principally to the regions of Pacific Asia and Africa.

One of our key benchmark projects is the PV plant at San Bellino (Italy); this plant is one of the largest of its kind in the world, having an installed rated power of 70 MWp.

The 60 MWp Nobesol solar plant situated in Olmedilla de Alarcón (Spain) is another important project in which Ingeteam has participated, supplying more than 450 INGECON® SUN 100 inverters.

Ingeteam has also supplied on-grid PV inverters to some of the most relevant commercial installations, like the world's largest PV greenhouse, a 20 MWp installation in Sardinia (Italy).









2. Royalla Solar Farm (Australia)
20 MW (10 INGECON® SUN PowerStation)

ACCIONA SOLAR
3. PV array at Amareleja (Portugal)
46 MWp (70 INGECON® SUN PowerMax)

4. CANTIERI ITALIANI
Concrete housing at Sardegna (Italy)
9 MW (10 INGECON® SUN PowerMax)

5. NOBESOLPV array at Olmedilla de Alarcón (Spain)60 MWp (452 INGECON® SUN Power)















20. **SUNEDISON PV array at Copiapó (Chile)**46.7 MW (68 INGECON® SUN PowerMax)

21. MARTIFER

PV on-roof installation at Mineirao

Stadium (Brazil)

1.5 MW (89 INGECON® SUN Smart TL)

22. GREEN APPLE ENERGY

Domestic installation at
New Jersey (USA)
25 kW (5 INGECON® SUN Lite TL U)

Ingeteam

23. SUNCO Sistemi Fotovoltaici
PV array at Pichincha (Ecuador)
2 MW (1 INGECON® SUN PowerStation









24. **SYDIS** 

Stand-alone installation at Albacete (Spain) 5 kW FV + 45 kWh batteries (3 INGECON® SUN STORAGE 1Play, 3 INGECON® SUN Lite) 25. SUNPOWER

PV industrial system for self-consumption at Valdemoro (Spain) 100 kW (18 INGECON® SUN Lite, 2 INGECON® EMS Manager) 26. INGENIERÍA Y SOLUCIONES FOTOVOLTAICAS

PV domestic system for self-consumption at Zizur Mayor (Spain)

3.3 kW (1 INGECON® SUN Lite, 1 INGECON® EMS Manager)







27. AKUO ENERGY

PV installation with energy storage in La Réunion island (France)

9 MW PV + 9 MWh batteries (10 INGECON® SUN PowerMax,

6 INGECON® SUN STORAGE PowerMax)



28. GROUPE VALECO
PV installation in Gers (France)
10 MWp (9 INGECON® SUN PowerMax)

PV plant in Baltimore, MD (USA)
1 MW (2 INGECON® SUN PowerMax TL U)









30. ACCIONA
Sishen Solar (South Africa)
78 MW (39 INGECON® SUN PowerStation)

31. HALF MOON VENTURES
PV plant in Jefferson, WI (USA)
1.2 MW (2 INGECON® SUN
PowerMax TL U)

32. ENERPRO
Diesel-PV installation in
Baltra airport (Galapagos, Ecuador)
75 kW (3 INGECON® SUN Smart U)

33. WINDMAR RENEWABLE ENERGY INC. PV plant in Aguada (Puerto Rico) 500 kW (1 INGECON® SUN PowerMax T U)

NOTES	









#### Ingeteam Power Technology, S.A.

Avda. Ciudad de la Innovación, 13 31621 SARRIGUREN (Navarra) - Spain Tel.: +34 948 288 000 / Fax: +34 948 288 001 e-mail: solar.energy@ingeteam.com

#### Ingeteam S.r.I.

Via Emilia Ponente, 232 48014 CASTEL BOLOGNESE (RA) - Italy Tel.: +39 0546 651 490 / Fax: +39 054 665 5391 e-mail: italia.energy@ingeteam.com

#### Ingeteam GmbH

Herzog-Heinrich-Str. 10 80336 MUNICH - Germany Tel.: +49 89 99 65 38 0 / Fax: +49 89 99 65 38 99 e-mail: solar.de@ingeteam.com

# Ingeteam SAS

La Naurouze B - 140 rue Carmin 31670 Labège - France Tel: +33 (0)5 61 25 00 00 / Fax: +33 (0)5 61 25 00 11 e-mail: france@ingeteam.com

#### Ingeteam INC.

5201 Great American Parkway, Suite 320 SANTA CLARA, CA 95054 - USA Tel.: +1 (415) 450 1869 / +1 (408) 524 2929 / Fax: +1 (408) 824 1327 e-mail: solar.us@ingeteam.com

#### Ingeteam INC.

3550 W. Canal St. MILWAUKEE, WI 53208 - USA Tel.: +1 (414) 934 4100 / +1 (855) 821 7190 / Fax: +1 (414) 342 0736 e-mail: solar.us@ingeteam.com

#### Ingeteam, a.s.

Technologická 371/1 70800 OSTRAVA - PUSTKOVEC Czech Republic Tel.: +420 59 732 6800 / Fax: +420 59 732 6899 e-mail: czech@ingeteam.com

#### Ingeteam Shanghai, Co. Ltd. Shanghai Trade Square, 1105

188 Si Ping Road 200086 SHANGHAI - P.R. China Tel.: +86 21 65 07 76 36 / Fax: +86 21 65 07 76 38 e-mail: shanghai@ingeteam.com

## Ingeteam, S.A. de C.V.

Ave. Revolución, nº 643, Local 9 Colonia Jardín Español - MONTERREY 64820 - NUEVO LEÓN - México Tel.: +52 81 8311 4858 / Fax: +52 81 8311 4859 e-mail: northamerica@ingeteam.com

# Ingeteam Ltda.

Estrada Duílio Beltramini, 6975 Chácara Sao Bento 13278-078 VALINHOS SP - Brazil Tel.: +55 19 3037 3773 / Fax: +55 19 3037 3774 e-mail: brazil@ingeteam.com

### Ingeteam Pty Ltd.

Unit 2 Alphen Square South 16th Road, Randjiespark, Midrand 1682 - South Africa Tel.: +2711 314 3190 / Fax: +2711 314 2420 e-mail: southafrica@ingeteam.com

## Ingeteam SpA

Cerro El Plomo 5630, Piso 9, Oficina 901 7560742 Las Condes - Santiago de Chile - Chile Tel.: +56 2 26664370 e-mail: chile@ingeteam.com

#### Ingeteam Power Technology India Pvt. Ltd. 2nd Floor, 431

Udyog Vihar, Phase III 122016 Gurgaon (Haryana) - India Tel.: +91 124 420 6491-5 / Fax: +91 124 420 6493 e-mail: india@ingeteam.com

#### Ingeteam Sp. z o.o.

UI. Koszykowa 60/62 m 39 00-673 Warszawa - Poland Tel.: +48 22 821 9930 / Fax: +48 22 821 9931 e-mail: polska@ingeteam.com

## Ingeteam Australia Pty Ltd.

Suite 112, Level 1, Mike Codd Biulding 232 Innovation Campus, Squires Way North Wollongong, NSW 2500 - Australia Tel.: +61 499 988 022 e-mail: australia@ingeteam.com

# Ingeteam